ZI Haneboesch L-4562 Differdange I UXFMBOURG Phone: +352 58 22 82 1 Fax: +352 58 49 35 E-mail : sales@airtech.lu Website : www.airtech.lu

Data Sheet

AIRSEAL 2

Economical vacuum bag sealant tape

DESCRIPTION

Airseal 2 is a cost effective vacuum bag sealant tape for room and medium temperature applications. Airseal 2 has been specially formulated to provide excellent tack, firm feel, good clean-up and long shelf life. It can also be used for higher temperature envelope bag applications.

Airseal 2 - Standard tack version.

Airseal 2 Tacky - Superior tack for colder environments.

Airseal 2 Super Tacky - Very soft and very high tack version.

BENEFITS

- · Lower material cost.
- Long shelf life reduces waste.
- Tacky versions have better tack for colder environments.

TECHNICAL DATA

Colour Black

Base material Sythetic rubber

Maximum use temperature 150°C (bag to tool)
180°C (bag to bag)

Shelf life 18 months from the date of manufacture

Storage conditions Tape must be stored flat in original packaging at 22°C

Do not refrigerate

SIZES

Dimensions	Dimensions	Packaging
3 mm x 12 mm x 15 m	1/8 inch x 1/2 inch x 50 feet	20 rolls per case
3 mm x 9 mm x 15 m	1/8 inch x 1/3 inch x 50 feet	20 rolls per case
2 mm x 10 mm x 20 m	1/12 inch x 2/5 inch x 65,6 feet	20 rolls per case
2 mm x 7 mm x 20 m	1/12 inch x 1/4 inch x 65,6 feet	20 rolls per case
4 mm diameter bead x 7,5 m	1/6 inch diameter bead x 25 feet	40 rolls per case



NOTES

- For clean removal from moulds, it is recommended to strip the tape from the mould surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated: 2015-10-14