according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARADUR® 3486 BD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Hardener

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA

Address : Everslaan 45

3078 Everberg

Belgium

Telephone : +41 61 299 20 41 Telefax : +41 61 299 20 40

E-mail address of person

responsible for the SDS

: Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : Centres Antipoison et de Toxicovigilance:

ANGERS: 02 41 48 21 21 BORDEAUX: 05 56 96 40 80

LILLE: 0 825 812 822 LYON: 04 72 11 69 11 MARSEILLE 04 91 75 25 25 NANCY: 03 83 32 36 36 PARIS: 01 40 05 48 48 RENNES: 02 99 59 22 22 STRASBOURG: 03 88 37 37 37 TOULOUSE: 05 61 77 74 47 EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888

+86 532 83889090 India: + 91 22 42 87 5333 Australia: 1800 786 152 New Zealand: 0800 767 437 USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H332: Harmful if inhaled.

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

Skin corrosion, Sub-category 1A H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard,

Category 3

H412: Harmful to aquatic life with long lasting

effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting

effects.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours. P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing.

Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh

air and keep comfortable for breathing.

Immediately call a POISON

CENTER/doctor.

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia

3-Aminomethyl-3,5,5-trimethylcyclohexylamine

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine)

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concent ration (% w/w)
Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	- - 01-2119557899-12	Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 60 - < 100
3-Aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 612-067-00-9 01-2119514687-32	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 13 - < 30
2,2'-Dimethyl-4,4'- methylenebis(cyclohexylamine)	6864-37-5 229-962-1 612-110-00-1 01-2119497829-12	Acute Tox. 4; H302 Acute Tox. 3; H311 Acute Tox. 2; H330 Skin Corr. 1A; H314 Aquatic Chronic 2; H411 STOT RE 2; H373	>= 7 - < 13

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with

difficulty.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

Version Revision Date: SDS Number: Date of last issue: 08.09.2016 400001014180 1.1 10.10.2018 Date of first issue: 08.09.2016

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

: Keep respiratory tract clear. If swallowed

Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not use a solid water stream as it may scatter and spread

Do not allow run-off from fire fighting to enter drains or water

courses.

5.3 Advice for firefighters

for firefighters

Special protective equipment : Wear self-contained breathing apparatus for firefighting if

necessary.

Specific extinguishing

methods

: No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and

contaminated fire extinguishing water must be disposed of in

accordance with local regulations.

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

Version Revision Date: SDS Number: Date of last issue: 08.09.2016
1.1 10.10.2018 400001014180 Date of first issue: 08.09.2016

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See Section 1 for emergency contact information., For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Local/Total ventilation : Ensure adequate ventilation.

Advice on safe handling : Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat, drink or smoke. Wash hands

before breaks and at the end of workday.



ARADUR® 3486 BD

Version Revision Date: SDS Number: Date of last issue: 08.09.2016
1.1 10.10.2018 400001014180 Date of first issue: 08.09.2016

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep containers tightly closed in a cool, well-ventilated place. Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label

precautions. Keep in properly labelled containers.

Advice on common storage

: For incompatible materials please refer to Section 10 of this

SDS.

Further information on

storage stability

: No decomposition if stored and applied as directed.

Recommended storage

temperature

: 2 - 40 °C

Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-dimethyl-4,4'- methylenebis(cyclohex ylamine)	Workers	Inhalation	Long-term systemic effects	0,6 mg/m3
	Workers	Inhalation	Long-term local effects	0,96 mg/m3
	Workers	Dermal	Long-term systemic effects	0,06 mg/kg
3-aminomethyl-3,5,5- trimethylcyclohexylami ne	Workers	Inhalation	Systemic effects, Short-term exposure	20,1 mg/m3
	Workers	Inhalation	Local effects, Short- term exposure	20,1 mg/m3
	Consumers	Oral	Systemic effects, Long-term exposure	0,526 mg/kg bw/day
Reaction products of di-, tri- and tetra-propoxylated propane-	Workers	Inhalation	Long-term systemic effects	1,36 mg/m3

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

1,2-diol with ammonia				
	Workers	Dermal	Long-term systemic effects	2,5 mg/kg bw/day
2,2'-Dimethyl-4,4'- methylenebis(cyclohex ylamine)	Workers	Inhalation	Long-term systemic effects	0,6 mg/m3
	Workers	Inhalation	Long-term local effects	0,96 mg/m3
	Workers	Dermal	Long-term systemic effects	0,06 mg/kg
3-Aminomethyl-3,5,5- trimethylcyclohexylami ne	Workers	Inhalation	Systemic effects, Short-term exposure	20,1 mg/m3
	Workers	Inhalation	Local effects, Short- term exposure	20,1 mg/m3
	Consumers	Oral	Systemic effects, Long-term exposure	0,526 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name		Environmental Compartment	Value
2,2'-dimethyl-4,4'- methylenebis(cyclohexylamine)		Fresh water	0,4 mg/l
		Marine water	0,04 mg/l
		Freshwater - intermittent	0,046 mg/l
		Sewage treatment plant	1,6 mg/l
		Fresh water sediment	17,4 mg/kg
		Marine sediment	17,4 mg/kg
		Soil	4,56 mg/kg
3-aminomethyl-3,5,5- trimethylcyclohexylamine		Fresh water	0,06 mg/l
Remarks:	Assessme	ent Factors	
	•	Marine water	0,006 mg/l
Assessme Assessme Assessme Assessme Assessme		ent Factors	
		Freshwater - intermittent	0,23 mg/l
		ent Factors	
		Sewage treatment plant	3,18 mg/l
		ent Factors	
		Fresh water sediment	5,784 mg/kg
		nt Factors	·
		Marine sediment	0,578 mg/kg
		nt Factors	<u> </u>
		Soil	1,121 mg/kg

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

Version Revision Date: SDS Number: Date of last issue: 08.09.2016
1.1 10.10.2018 400001014180 Date of first issue: 08.09.2016

	Assessm	ent Factors	
		Secondary Poisoning	
	Assessment Factors		
Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia		Fresh water	0,015 mg/l
		Marine water	0,014 mg/l
		Fresh water sediment	0,132 mg/kg dry weight (d.w.)
		Marine sediment	0,125 mg/kg dry weight (d.w.)
		Sewage treatment plant	7,5 mg/l
		Secondary Poisoning	6,93 mg/kg
		Freshwater - intermittent	0,15 mg/l
		Soil	0,018 mg/kg dry weight (d.w.)
2,2'-Dimethyl-4,4'- methylenebis(cyclohexy	lamine)	Fresh water	0,4 mg/l
		Marine water	0,04 mg/l
		Freshwater - intermittent	0,046 mg/l
		Sewage treatment plant	1,6 mg/l
		Fresh water sediment	17,4 mg/kg
		Marine sediment	17,4 mg/kg
		Soil	4,56 mg/kg
3-Aminomethyl-3,5,5- trimethylcyclohexylamin	e	Fresh water	0,06 mg/l
	Assessm	ent Factors	
		Marine water	0,006 mg/l
	Assessm	ent Factors	
		Freshwater - intermittent	0,23 mg/l
	Assessm	ent Factors	
		Sewage treatment plant	3,18 mg/l
	Assessm	ent Factors	<u> </u>
		Fresh water sediment	5,784 mg/kg
	Assessm	ent Factors	<u> </u>
	<u> </u>	Marine sediment	0,578 mg/kg
	Assessm	ent Factors	
	1	Soil	1,121 mg/kg
			1 2 2

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

Assessment Factors			
	Secondary Poisoning		
Assessment Factors			

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : butyl-rubber

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

Material : Nitrile rubber Break through time : 10 - 480 min

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions

(mechanical strain, duration of contact).

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines

Recommended Filter type:

Combined particulates and organic vapour type

Filter type : Filter type A-P

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : colourless

Odour : ammoniacal

Odour Threshold : No data is available on the product itself.

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

pH : No data is available on the product itself.

Freezing point : No data is available on the product itself.

Melting point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flash point : 123 °C

Method: Pensky-Martens closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Burning rate : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Relative density : 0,94

Density : 0,94 - 0,95 g/cm3 (20 °C)

Solubility(ies)

Water solubility : > 100 g/l partly soluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : No data is available on the product itself.

Viscosity

Viscosity, dynamic : 10 - 20 mPa.s (20 °C)

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

9.2 Other information

No data available

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

Version Revision Date: SDS Number: Date of last issue: 08.09.2016 400001014180 1.1 10.10.2018 Date of first issue: 08.09.2016

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

Stable under normal conditions.

10.3 Possibility of hazardous reactions

: Stable under normal conditions. Hazardous reactions

No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid None known.

None known.

10.5 Incompatible materials

Materials to avoid Strong acids and strong bases

Strong oxidizing agents

None known.

10.6 Hazardous decomposition products

Carbon oxides

Nitrogen oxides (NOx)

Burning produces noxious and toxic fumes.

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

: Acute toxicity estimate : > 2 000 mg/kg Acute oral toxicity - Product

Method: Calculation method

Acute inhalation toxicity -

: Acute toxicity estimate : 4,48 mg/l Exposure time: 4 h

Product

Test atmosphere: dust/mist

Method: Calculation method

Acute dermal toxicity -

: Acute toxicity estimate : > 2 000 mg/kg

Product

Method: Calculation method

Acute toxicity (other routes of : No data available

administration)

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

Skin corrosion/irritation

Components:

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Corrosive after 1 to 4 hours of exposure

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Species: Rabbit Result: Causes burns.

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine):

Species: Rabbit

Method: OECD Test Guideline 404

Result: Causes burns.

Serious eye damage/eye irritation

Components:

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia:

Species: Rabbit

Assessment: Corrosive

Method: OECD Test Guideline 405 Result: Irreversible effects on the eye

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine):

Species: Rabbit Exposure time: 24 h Assessment: Corrosive

Method: OECD Test Guideline 405

Result: Corrosive

Respiratory or skin sensitisation

Components:

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Exposure routes: Skin Species: Guinea pig

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 406 Result: Causes sensitisation.

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine):

Test Type: Maximisation Test

Exposure routes: Skin Species: Guinea pig

Method: OECD Test Guideline 406 Result: Does not cause skin sensitisation.

Assessment: No data available

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

Germ cell mutagenicity

Components:

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia:

Genotoxicity in vitro : Concentration: 0 - 10000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

: Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

: Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

: Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Components:

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia:

Genotoxicity in vivo : Application Route: Oral

Dose: 500 mg/kg

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

No data available

Carcinogenicity - Assessment

: No data available

Reproductive toxicity

Components:

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia:

Effects on fertility : Species: Rat, male and female

Application Route: Dermal

Method: OECD Test Guideline 421

Result: Animal testing did not show any effects on fertility.

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine):

Species: Rat, male and female

Application Route: Oral

Dose: 0, 15, 50 and 100 mg/kg/day Frequency of Treatment: 7 days/week

General Toxicity - Parent: No observed adverse effect level:

15 mg/kg body weight

General Toxicity F1: No observed adverse effect level: 15

mg/kg body weight

Method: OECD Test Guideline 422

Components:

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Effects on foetal : Species: Rat, female development : Application Route: Oral

General Toxicity Maternal: No-observed-effect level: 50 mg/kg

body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine):

Species: Rat

Application Route: Oral

Dose: 5, 15 and 45 mg/kg bw /day Frequency of Treatment: 7 days/week

General Toxicity Maternal: No observed adverse effect level: 5

mg/kg body weight

Developmental Toxicity: No observed adverse effect level: 45

mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Reproductive toxicity -

Assessment

: No data available

STOT - single exposure

No data available

STOT - repeated exposure

Components:

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine):

Exposure routes: Ingestion

Target Organs: Liver, Kidney, Adrenal gland, Heart, Blood

Assessment: May cause damage to organs through prolonged or repeated exposure.

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

Repeated dose toxicity

Components:

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia:

Species: Rat, male and female

NOAEL: 250

Application Route: Skin contact

Exposure time: 2 160 hNumber of exposures: 5 d

Method: Subchronic toxicity

Species: Rat, male and female

NOAEL: 239

Application Route: Ingestion

Exposure time: 744 hMethod: Subchronic toxicity

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Species: Rat, male and female

NOEC: 60 mg/kg, 200 Application Route: Ingestion Test atmosphere: dust/mist

Exposure time: 216 hNumber of exposures: 6 h

Method: Subchronic toxicity

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine):

Species: Rat, male and female

NOEC: 12

Application Route: Inhalation Test atmosphere: vapour

Number of exposures: 5 days/week Method: OECD Test Guideline 413

Species: Rat, male and female

NOAEL: 2,5 mg/kg

Application Route: oral (gavage)

Exposure time: 3 months Number of exposures: 5 days/week

Dose: 2.5, 12, 60 mg/kg bw/day Method: OECD Test Guideline 408

Target Organs: Liver, Blood, Kidney, Adrenal gland, Heart

Repeated dose toxicity -

Assessment

: No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia:

Toxicity to fish : EC50 (Oncorhynchus mykiss (rainbow trout)): > 15 mg/l

Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

LC50 : 772,14 mg/l Exposure time: 96 h Test Type: static test

Test substance: Marine water Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 80 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

EC50 (Acartia tonsa): 418,34 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Marine water

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 15 mg/l

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

ErC10 (Selenastrum capricornutum (green algae)): 1,4 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 110 mg/l

Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other

aquatic invertebrates

: EC50 : 23 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae : EC50 : 37 mg/l

Exposure time: 72 h
Test Type: static test

Test substance: Fresh water

Method: Directive 67/548/EEC, Annex V, C.3.

Toxicity to microorganisms : EC10 : 1 120 mg/l

Exposure time: 18 h Method: Measured

(Pseudomonas putida): 1 120 mg/l

Exposure time: 18 h Test Type: static test

Test substance: Fresh water

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine):

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): 22,4 mg/l

Exposure time: 96 h Test Type: semi-static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 4,57 mg/l

Exposure time: 48 h
Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Other): 7,9 mg/l

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

Toxicity to microorganisms : EC20 (activated sludge): 160 mg/l

Exposure time: 30 min Test Type: static test Method: ISO 8192

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC: 4 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia:

Biodegradability : Inoculum: Mixture

Result: Not biodegradable Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Stability in water : Degradation half life (DT50): 12 Months (25 °C)

pH: 6,5

Method: No information available.

Remarks: Fresh water

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Biodegradability : Inoculum: activated sludge

Concentration: 6,9 mg/l

Result: Not readily biodegradable.

Biodegradation: 8 % Exposure time: 28 d

Method: Directive 67/548/EEC Annex V, C.4.A.

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301C

Inoculum: activated sludge Result: Not biodegradable

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

Biodegradation: < 1 % Exposure time: 28 d

Method: OECD Test Guideline 302B

12.3 Bioaccumulative potential

Components:

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia:

Partition coefficient: n- : log Pow: 1,34 (25 °C)

octanol/water

3-Aminomethyl-3,5,5-trimethylcyclohexylamine:

Partition coefficient: n- : log Pow: 0,99 (23 °C)

octanol/water pH: 6,34

Method: OECD Test Guideline 107

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine):

Bioaccumulation : Species: Cyprinus carpio (Carp)

Exposure time: 28 d

Bioconcentration factor (BCF): < 60 Test substance: Fresh water Method: flow-through test

Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 2,3 (23 °C)

octanol/water pH: 10

Method: OECD Test Guideline 107

12.4 Mobility in soil

Components:

3-Aminomethyl-3,5,5-trimethylcyclohexylamine: Distribution among : Koc: 928

environmental compartments

2,2'-Dimethyl-4,4'-methylenebis(cyclohexylamine): Distribution among : Koc: 1195

environmental compartments

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

Version Revision Date: Date of last issue: 08.09.2016 SDS Number: 400001014180 1.1 10.10.2018 Date of first issue: 08.09.2016

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of contents/ container to an approved waste disposal

plant.

Empty remaining contents. Contaminated packaging

> Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

IATA

14.1 UN number : UN 2735

14.2 UN proper shipping : Polyamines, liquid, corrosive, n.o.s.

name

14.3 Transport hazard : 8

class(es)

14.4 Packing group : 11

Labels : Corrosive 855

Packing instruction (cargo

aircraft)

Packing instruction : 851

(passenger aircraft)

IMDG

14.1 UN number : UN 2735

14.2 UN proper shipping : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

name

(ISOPHORONE DIAMINE, cycloaliphatic polyamine)

(ISOPHORONE DIAMINE, cycloaliphatic polyamine)

14.3 Transport hazard : 8

class(es)

14.4 Packing group Ш Labels 8 EmS Code F-A, S-B

14.5 Environmental hazards

Marine pollutant : no

ADR

14.1 UN number : UN 2735

14.2 UN proper shipping : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

name

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

Version Revision Date: SDS Number: Date of last issue: 08.09.2016 400001014180 1.1 10.10.2018 Date of first issue: 08.09.2016

(ISOPHORONE DIAMINE, cycloaliphatic polyamine)

14.3 Transport hazard : 8

class(es)

14.4 Packing group : 11 Labels 8

14.5 Environmental hazards

Environmentally hazardous : no

RID

14.1 UN number : UN 2735

14.2 UN proper shipping : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

name

(ISOPHORONE DIAMINE, cycloaliphatic polyamine)

14.3 Transport hazard : 8

class(es)

14.4 Packing group : 11 Labels 8

14.5 Environmental hazards

Environmentally hazardous : no

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: This product does not contain substances of very high concern

(Regulation (EC) No

1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

REACH - List of substances subject to authorisation -

Future sunset date

: Not applicable

Occupational Illnesses (R-

: 49, 49 bis

461-3, France)

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

Version Revision Date: SDS Number: Date of last issue: 08.09.2016
1.1 10.10.2018 400001014180 Date of first issue: 08.09.2016

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H311 : Toxic in contact with skin.
H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H373 : May cause damage to organs through prolonged or repeated

exposure if swallowed.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Skin Corr. : Skin corrosion Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure

Further information

according to Regulation (EC) No. 1907/2006



ARADUR® 3486 BD

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.09.2016

 1.1
 10.10.2018
 400001014180
 Date of first issue: 08.09.2016

ssification procedure:
15

Acute Tox. 4	H332	Calculation method
Skin Corr. 1A	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.