according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ARALDITE® CW 229-3 GB

Unique Formula Identifier

(UFI)

: QUSE-60X7-T00A-1KKT

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Component used for the manufacture of electrical insulation

Substance/Mixture parts

## 1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe) BV

Address : Everslaan 45

3078 Everberg

Belgium

Telephone : +41 61 299 20 41 Telefax : +41 61 299 20 40

E-mail address of person

responsible for the SDS

: Global\_Product\_EHS\_AdMat@huntsman.com

## 1.4 Emergency telephone number

Emergency telephone number : Centres Antipoison et de Toxicovigilance:

BORDEAUX: 05 56 96 40 80 LILLE: 0 825 812 822 LYON: 04 72 11 69 11 MARSEILLE 04 91 75 25 25 NANCY: 03 83 32 36 36 PARIS: 01 40 05 48 48 RENNES: 02 99 59 22 22

ANGERS: 02 41 48 21 21

STRASBOURG: 03 88 37 37 37 TOULOUSE: 05 61 77 74 47 EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888 +86 532 83889090

India: + 91 22 42 87 5333 Australia: 1800 786 152 New Zealand: 0800 767 437 USA: +1 800-424-9300

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Long-term (chronic) aquatic hazard,

## Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Category 2

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

H411: Toxic to aquatic life with long lasting effects.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.
P391 Collect spillage.

#### Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bis oxirane

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

# **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

#### **Hazardous components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concent ration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxir ane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Skin Irrit. 2; H315 >= 5 % Eye Irrit. 2; H319 >= 5 %	>= 30 - < 50
methanol	67-56-1 200-659-6 603-001-00-X 01-2119433307-44	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370 (Bladder, Blood, Central nervous system, Eyes, Kidney, Liver, Nervous system, spleen)  specific concentration limit STOT SE 1; H370 >= 10 % STOT SE 2; H371 3 - < 10 %	>= 0,1 - < 1

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

## 4.2 Most important symptoms and effects, both acute and delayed

None known.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during : Do not allow run-off from fire fighting to enter drains or water

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

firefighting courses.

Hazardous combustion

products

: Carbon oxides

Halogenated compounds

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

# 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## 6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation

and/or dermatitis and sensitisation of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this

product.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

Version Revision Date: SDS Number: Date of last issue: 27.09.2018 01.06.2023 400001009319 2.1 Date of first issue: 13.09.2017

Print Date 01.07.2024

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

resealed and kept upright to prevent leakage. Keep in properly

labelled containers.

: For incompatible materials please refer to Section 10 of this Advice on common storage

SDS.

Recommended storage

temperature

: 2 - 18 °C

Further information on

storage stability

Stable under normal conditions.

7.3 Specific end use(s)

: No data available Specific use(s)

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
methanol	67-56-1	TWA	200 ppm	2006/15/EC
			260 mg/m3	
Further information	Indicative, Identifies the possibility of significant uptake through the skin			
		VME	200 ppm	FR VLE
			260 mg/m3	
Further information	Risk of penetration through skin, Regulatory binding exposure limits			
		VLCT (VLE)	1 000 ppm	FR VLE
			1 300 mg/m3	
Further information	Risk of penetration through skin, Indicative exposure limits			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

according to Regulation (EC) No. 1907/2006



**ARALDITE® CW 229-3 GB** 

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1- methylethylidene)bis( 4,1- phenyleneoxymethyle ne)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4,93 mg/m3
	Workers	Dermal	Long-term systemic effects	0,75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,87 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,5 mg/kg bw/day
methanol	Workers	Dermal	Systemic effects, Long-term exposure	40 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Long-term exposure	260 mg/m3
	Workers	Inhalation	Local effects, Long- term exposure	260 mg/m3
	Workers	Dermal	Systemic effects, Short-term exposure	40 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Short-term exposure	260 mg/m3
	Workers	Inhalation	Local effects, Short- term exposure	260 mg/m3
	Consumers	Dermal	Systemic effects, Long-term exposure	8 mg/kg bw/day
	Consumers	Inhalation	Systemic effects, Long-term exposure	50 mg/m3
	Consumers	Oral	Systemic effects, Long-term exposure	8 mg/kg bw/day
	Consumers	Inhalation	Local effects, Long- term exposure	50 mg/m3
	Consumers	Inhalation	Systemic effects, Short-term exposure	50 mg/m3
	Consumers	Inhalation	Local effects, Short- term exposure	50 mg/m3
	Consumers	Dermal	Systemic effects, Short-term exposure	8 mg/kg bw/day
	Consumers	Oral	Systemic effects, Short-term exposure	8 mg/kg bw/day

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

	, , , , , ,	
Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxira ne	Fresh water	0,006 mg/l
	Marine water	0,001 mg/l
	Fresh water sediment	0,341 mg/kg dry weight (d.w.)
	Marine sediment	0,034 mg/kg dry weight (d.w.)

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

	Soil	0,065 mg/kg dry weight (d.w.)		
	Sewage treatment plant	10 mg/l		
	Secondary Poisoning	11 mg/kg		
methanol	Fresh water	154 mg/l		
	Remarks: Assessment Factors	Remarks: Assessment Factors		
	Marine water	15,4 mg/l		
	Remarks: Assessment Factors	Remarks:Assessment Factors		
	Freshwater - intermittent	1540 mg/l		
	Remarks: Assessment Factors	Remarks: Assessment Factors		
	Sediment	570,4 mg/kg		
	Remarks:Equilibrium method			
	Secondary Poisoning			
	Sewage treatment plant	100 mg/l		
	Remarks: Assessment Factors	Remarks: Assessment Factors		
	Soil	23,5 mg/kg		
	Remarks:Equilibrium method			

## 8.2 Exposure controls

# Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : butyl-rubber

Break through time : > 8 h

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

Material : Nitrile rubber Break through time : 10 - 480 min

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain,

duration of contact).

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : WARNING! This product contains quartz, which has

been classified by IARC as carcinogenic for humans (Group 1), and which can cause silicosis and lung cancer following exposure to respirable dust. It is therefore important to take particular care to avoid inhalation exposure when

mechanically processing cured material (e.g. grinding,

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

sanding, sawing).

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : brown

Odour : slight

Odour Threshold : No data is available on the product itself.

pH : ca. 7 (20 °C)

Concentration: 500 g/l

Melting point/freezing point : No data is available on the product itself.

Boiling point : > 200 °C

Flash point : 180 °C

Method: Pensky-Martens closed cup

Flammability (solid, gas) : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : < 0,00001 hPa (20 °C)

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : 1,78 g/cm3 (25 °C)

Solubility(ies)

Water solubility : practically insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C

Viscosity

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

Viscosity, dynamic : 80 000 - 200 000 mPa.s (25 °C)

#### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

## 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

#### 10.4 Conditions to avoid

Conditions to avoid : None known.

## 10.5 Incompatible materials

Materials to avoid : None known.

# 10.6 Hazardous decomposition products

Hazardous decomposition : carbon dioxide products : carbon monoxide

Halogenated compounds

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

## **Acute toxicity**

# **Product:**

Acute oral toxicity : LD50 (Rat): > 5 000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2 000 mg/kg

Method: Calculation method

#### Components:

## 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg

Method: OECD Test Guideline 420

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

Assessment: The substance or mixture has no acute oral

toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

methanol:

Acute oral toxicity : LD50 (Rat): 5 628 mg/kg

Assessment: The component/mixture is toxic after single

ingestion.

Acute inhalation toxicity : LC50 (Rat, male and female): 128,2 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Other guidelines

Assessment: The component/mixture is toxic after short term

inhalation.

Acute dermal toxicity : LD50 (Rabbit): 15 800 mg/kg

Assessment: The component/mixture is toxic after single

contact with skin.

#### Skin corrosion/irritation

#### **Components:**

# 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rabbit Exposure time : 4 h

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

methanol:

Species : Rabbit

Assessment : No skin irritation
Method : Other guidelines
Result : No skin irritation

#### Serious eye damage/eye irritation

## **Components:**

# 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rabbit

Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Result : Irritating to eyes.

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

methanol:

Species : Rabbit

Result : No eye irritation

#### Respiratory or skin sensitisation

Product:

Exposure routes : Skin Species : Guinea pig

Result : Causes sensitisation.

#### **Components:**

#### 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin Species : Mouse

Method : OECD Test Guideline 429

Result : The product is a skin sensitiser, sub-category 1B.

methanol:

Exposure routes : Skin Species : Guinea pig

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

#### Germ cell mutagenicity

#### **Components:**

# 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: without metabolic activation

Result: positive

Test Type: reverse mutation assay
Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse

mutation assay) Result: negative

Genotoxicity in vivo : Test Type: in vivo assay

Species: Mouse (male) Cell type: Germ Application Route: Oral Dose: 3333, 10000 mg/kg

Result: negative

Test Type: gene mutation test

Species: Rat (male) Cell type: Somatic Application Route: Oral

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

Dose: 50,250,500,1000 mg/kg bw/day Method: OECD Test Guideline 488

Result: negative

methanol:

Genotoxicity in vitro : Concentration: 15.8 - 63.3 mg/ml

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Concentration: 5 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Concentration: ca 40 mg/ml Metabolic activation: negative

Result: negative

Genotoxicity in vivo : Application Route: Intraperitoneal injection

Dose: 1920 - 4480 mg/kg

Method: OECD Test Guideline 474

Result: negative

#### Carcinogenicity

#### **Product:**

Carcinogenicity - Assessment

: Not classifiable as a human carcinogen.

## Components:

# 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male
Application Route : Oral
Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week NOAEL : 15 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Mouse, male
Application Route : Dermal
Exposure time : 24 month(s)

Dose : 0, 0.1, 10, 100 mg/kg bw/day

Frequency of Treatment : 3 days/week

NOEL : 0,1 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

Species : Rat, female
Application Route : Dermal
Exposure time : 24 month(s)

Dose : 0.1, 100, 1000 mg/kg bw/day

Frequency of Treatment : 5 days/week

NOEL : 100 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative

Species : Rat, female Application Route : Oral

Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week NOAEL : 100 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Rat, females

Application Route : Oral

Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week NOEL : 2 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

methanol:

Species : Rat, male and female

Application Route : Inhalation

Exposure time : 24 month(s)

Dose : >= 1300 mg/m³

Frequency of Treatment : 20 hour

Method : OECD Test Guideline 453

Result : negative

Species : Mouse, male and female

Application Route : Inhalation
Exposure time : 18 month(s)
Dose : 13 - 1300 mg/m³

Frequency of Treatment : 19 hour

Method : OECD Test Guideline 453

Result : negative

# Reproductive toxicity

#### Components:

## 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 180, 540 or 750 milligram per kilogram

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

Duration of Single Treatment: 238 d Frequency of Treatment: 1 daily

General Toxicity - Parent: NOEL: 540 mg/kg body weight General Toxicity F1: NOEL: 750 mg/kg body weight

Symptoms: No adverse effects Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Effects on foetal development

Species: Rabbit, female Application Route: Dermal

Dose: 0, 30, 100 or 300 milligram per kilogram

Duration of Single Treatment: 28 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight

Method: Other guidelines Result: No teratogenic effects

Test Type: Pre-natal Species: Rabbit, female Application Route: Oral

Dose: 0, 20, 60 or 180 milligram per kilogram

Duration of Single Treatment: 13 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 60 mg/kg body weight Developmental Toxicity: NOAEL: 180 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Test Type: Pre-natal Species: Rat, female Application Route: Oral

Dose: 0, 60, 180 and 540 milligram per kilogram

Duration of Single Treatment: 10 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 180 mg/kg body weight Developmental Toxicity: NOAEL: > 540 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

#### methanol:

Effects on fertility : Species: Rat, male and female Application Route: Inhalation

Method: OECD Test Guideline 416

Result: negative

Species: Monkey, female Application Route: Inhalation

Result: negative

Species: Mouse, male Application Route: Oral Result: negative

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

Effects on foetal : Species: Monkey

development Application Route: Inhalation

General Toxicity Maternal: NOAEL: 2 390 mg/m<sup>3</sup>

Result: No teratogenic effects

# STOT - single exposure

#### **Components:**

methanol:

Target Organs : Bladder, Blood, Central nervous system, Eyes, Kidney, Liver,

Nervous system, spleen

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 1.

## STOT - repeated exposure

No data available

#### Repeated dose toxicity

## **Components:**

## 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male and female

NOAEL : 50 mg/kg
Application Route : oral (gavage)
Exposure time : 14 Weeks

Number of exposures : 7 d

Dose : 0, 50, 250, 1000 mg/kg/day Method : OECD Test Guideline 408

Species : Rat, male and female

NOAEL : >= 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks

Number of exposures : 5 d

Dose : 0, 10, 100, 1000 mg/kg/day Method : OECD Test Guideline 411

Species: Mouse, maleNOAEL: 100 mg/kgApplication Route: Skin contactExposure time: 13 Weeks

Number of exposures : 3 d

Dose : 0, 1, 10, 100 mg/kg/day
Method : OECD Test Guideline 411

#### methanol:

Species : Monkey
NOEC : 13 mg/m3
Test atmosphere : vapour
Exposure time : 5 040 h
Number of exposures : 21 h

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

Species : Monkey, male and female

NOEC : 6660 mg/m3
Application Route : Ingestion
Test atmosphere : vapour
Exposure time : 72 h
Number of exposures : 6 h

Method : OECD Test Guideline 412

Species : Monkey
NOEC : 1300 mg/m3
Test atmosphere : vapour
Exposure time : 1 440 h
Number of exposures : 21 h

Species : Monkey
LOEC : 3990 mg/m3
Test atmosphere : vapour
Exposure time : 480 h
Number of exposures : 21 h

## **Aspiration toxicity**

#### **Components:**

## methanol:

May be harmful if swallowed and enters airways.

## 11.2 Information on other hazards

## **Endocrine disrupting properties**

# **Product:**

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher

#### **Experience with human exposure**

No data available

## Toxicology, Metabolism, Distribution

No data available

## **Neurological effects**

No data available

#### **Further information**

#### Components:

## methanol:

Remarks : Solvents may degrease the skin.

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

Version Revision Date: SDS Number: Date of last issue: 27.09.2018 400001009319 2.1 01.06.2023 Date of first issue: 13.09.2017

Print Date 01.07.2024

# **SECTION 12: Ecological information**

## 12.1 Toxicity

#### **Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1,8 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50: 11 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: EPA-660/3-75-009

NOEC: 4,2 mg/l Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: EPA-660/3-75-009

Toxicity to microorganisms IC50 (activated sludge): > 100 mg/l

> Exposure time: 3 h Test Type: static test

Test substance: Fresh water

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 0,3 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test Test substance: Fresh water Method: OECD Test Guideline 211

**Ecotoxicology Assessment** 

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects.

methanol:

Toxicity to fish LC50 (Lepomis macrochirus (Bluegill sunfish)): 15 400 mg/l

Exposure time: 96 h

Test Type: flow-through test Test substance: Fresh water

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10 000 mg/l

Exposure time: 48 h Test Type: static test

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

Test substance: Fresh water

Method: DIN 38412

Toxicity to algae/aquatic

plants

ErC50 (Selenastrum capricornutum (green algae)): ca. 22 000

mg/l

Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to microorganisms : IC50 (activated sludge): > 1 000 mg/l

Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Method: OECD Test Guideline 209

## 12.2 Persistence and degradability

#### **Components:**

# 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge, non-adapted

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)

pH: 4

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)

pH: 9

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)

pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

methanol:

Biodegradability : Inoculum: Marine water

Result: Readily biodegradable. Biodegradation: 69 - 97 % Exposure time: 5 - 20 d

Photodegradation : Test Type: Air

Rate constant: 0.0093

Degradation (direct photolysis): 50 %

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

#### 12.3 Bioaccumulative potential

# **Components:**

## 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31

Remarks: Does not bioaccumulate.

Partition coefficient: n-

octanol/water

log Pow: 3,242 (25 °C)

pH: 7,1

Method: OECD Test Guideline 117

methanol:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)

Exposure time: 3 d

Bioconcentration factor (BCF): < 10 Test substance: Fresh water

Partition coefficient: n-

octanol/water

log Pow: -0,77

# 12.4 Mobility in soil

## **Components:**

# 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among : Koc: 445

environmental compartments

#### 12.5 Results of PBT and vPvB assessment

## **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

# 12.6 Endocrine disrupting properties

## **Product:**

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher

#### 12.7 Other adverse effects

# Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

## **SECTION 14: Transport information**

# 14.1 UN number or ID number

ADN : UN 3082
ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA : UN 3082

## 14.2 UN proper shipping name

**ADN** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN)

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(BISPHENOL A EPOXY RESIN)

## 14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 9
ADR : 9
RID : 9
IMDG : 9
IATA : 9

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

## 14.4 Packing group

**ADN** 

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

**ADR** 

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

**RID** 

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

**IMDG** 

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction : 964

(passenger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

## 14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

**RID** 

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV)

: Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

: This product does not contain

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:

Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

4,4'-isopropylidenediphenol (Number on list 66, 30)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

**ENVIRONMENTAL HAZARDS** 

Occupational Illnesses (R-

: 51, 84, 44

461-3, France)

Installations classified for the

: 4511, 4722

protection of the environment (Environment Code R511-9)

#### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

E2

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

## The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AIIC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA : On or in compliance with the active portion of the TSCA

inventory

ENCS : Update: manually maintained

On the inventory, or in compliance with the inventory

#### **Inventories**

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

# 15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

## **SECTION 16: Other information**

# **Full text of H-Statements**

H225 : Highly flammable liquid and vapour.

H301 : Toxic if swallowed.

H311 : Toxic in contact with skin. H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H319 : Causes serious eye irritation.

H331 : Toxic if inhaled.

H370 : Causes damage to organs.

H411 : Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure 2006/15/EC : Europe. Indicative occupational exposure limit values

FR VLE : France. Occupational Exposure Limits

2006/15/EC / TWA : Limit Value - eight hours
FR VLE / VME : Time Weighted Average
FR VLE / VLCT (VLE) : Short Term Exposure Limit

#### **Further information**

## Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method
Eye Irrit. 2 H319 Calculation method
Skin Sens. 1 H317 Calculation method
Aquatic Chronic 2 H411 Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY. EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

according to Regulation (EC) No. 1907/2006



# **ARALDITE® CW 229-3 GB**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.09.2018

 2.1
 01.06.2023
 400001009319
 Date of first issue: 13.09.2017

Print Date 01.07.2024