

ZI Haneboesch L-4562 Differdange LUXEMBOURG Phone : +352 58 22 82 1 Fax : +352 58 49 35 E-mail : sales@airtech.lu Website : www.airtech.lu

Data Sheet

ECONOSTITCH® G

Polyester peel ply with black tracers

DESCRIPTION

Econostitch[®] G is an economical, heat set and scoured peel ply with good performance when used with both polyester and epoxy resins. It has black tracers with high visibility to reduce the risk of peel ply being left on the part.

Our Econo peel plies are designed to work in resin infusion or hand lay-up processes. Econostitch[®] G assists or eliminates the need for sanding or abrading on your composite laminate.

BENEFITS

- Peel plies strip off of cured laminates leaving a textured surface, reducing time spent hand finishing.
- Lower cost tightly woven fabric reduces material cost and is easier to remove, reducing labour cost.
- Black pin stripes make fabric more visible to reduce risk of leaving in place after cure.

TECHNICAL DATA

Maximum use temperature	190°C	
Fibre type	Polyester	
Weight	85 g/m ²	
Thickness	0,127 mm (0,005 inch)	
Colour	White	
Tracer	Black	
Extractables	<0,5 % by weight	
Shelf life	Unlimited when stored in original packaging at 22°C	

SIZES

Width	Length	Packaging
180 cm (71 inches)	200 m (218 yards)	1 roll

NOTES

- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.
- Hot knife (sealed edge) slitting upon request with 1 roll as minimum order quantity.
- Watch a demo video of Econostitch[®] G in the "Media Center" on our website.

Last updated : 2015-08-04

Catalogue position : Release fabrics / Peel plies

As the conditions or methods of use, including storage, are beyond our control, Airtech Europe does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech Europe disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes. This translation is provided for your convenience only. The official language is English and the official law is Luxembourg.