

## Data Sheet

## KNITFLOW 105 HT

High temperature resin flow medium

### DESCRIPTION

Knitflow 105 HT is designed to assist resin flow through the part during the vacuum assisted resin infusion process when elevated temperatures are used. Our resin flow medium works well with polyester, vinylester and epoxy resins. This product is a knitted flow medium.

### TECHNICAL DATA

Material type	Polyester
Colour	Clear
Configuration of net	Knitted
Maximum use temperature	200°C
Mesh weight	105 g/m <sup>2</sup>
Shelf life	Unlimited when stored in original packaging at 22°C

### SIZES

Thickness	Width	Length
0,7 mm	2,5 m	40 m
0,7 mm	2,5 m	80 m



### NOTES

- Other sizes available upon request. Minimum order required.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated : 2020-01-02

Catalogue position : [Resin infusion products](#)

As the conditions or methods of use, including storage, are beyond our control, Airtech Europe does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech Europe disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes. This translation is provided for your convenience only. The official language is English and the official law is Luxembourg.