

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® 403 RESIN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Adhesives
Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40
E-mail address of person : Global_Product_EHS_AdMat@huntsman.com
responsible for the SDS

1.4 Emergency telephone number

Emergency telephone number : Centres Antipoison et de Toxicovigilance:
ANGERS: 02 41 48 21 21
BORDEAUX: 05 56 96 40 80
LILLE: 0 825 812 822
LYON: 04 72 11 69 11
MARSEILLE 04 91 75 25 25
NANCY: 03 83 32 36 36
PARIS: 01 40 05 48 48
RENNES: 02 99 59 22 22
STRASBOURG: 03 88 37 37 37
TOULOUSE: 05 61 77 74 47
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

Eye irritation, Category 2

H319: Causes serious eye irritation.

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard,
Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

: Warning

Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:	
P261	Avoid breathing mist or vapours.
P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
Response:	
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P391	Collect spillage.

Hazardous components which must be listed on the label:

Phenol, polymer with formaldehyde, glycidyl ether

GLYCOLS, POLYPROPYLENE, 2,3-EPOXYPROPYL

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Phenol, polymer with	28064-14-4	Skin Irrit. 2; H315	>= 30 -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version 1.0 Revision Date: 30.09.2019 SDS Number: 400001008258 Date of last issue: -
Date of first issue: 30.09.2019

Print Date 30.01.2024

formaldehyde, glycidyl ether	Polymer	Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	< 50
GLYCOLS, POLYPROPYLENE, 2,3-EPOXYPROPYL	9072-62-2 -	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 2,5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Metal oxides Carbon dioxide (CO ₂) Carbon monoxide

5.3 Advice for firefighters

Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Specific extinguishing methods	:	No data is available on the product itself.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Refer to protective measures listed in sections 7 and 8.
----------------------	---	--

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
---------------------------	---	---

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
-------------------------	---	---

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information.,
For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8.
-------------------------	---	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium	7429-90-5	VME	10 mg/m3	FR VLE
Further information	Indicative exposure limits			
		VME (powder)	5 mg/m3	FR VLE
Further information	Indicative exposure limits			
Silicon dioxide	7631-86-9	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
Further information	Carcinogens or mutagens			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version 1.0 Revision Date: 30.09.2019 SDS Number: 400001008258 Date of last issue: -
Date of first issue: 30.09.2019

Print Date 30.01.2024

Substance name	End Use	Exposure routes	Potential health effects	Value
Silicon dioxide	Workers	Inhalation	Long-term systemic effects	4 mg/m3

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Material : butyl-rubber
Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Neoprene gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : paste

Colour : grey

Odour : slight

Odour Threshold : No data is available on the product itself.

pH : ca. 7 (20 °C)
Concentration: 500 g/l

Freezing point : No data is available on the product itself.

Melting point : No data is available on the product itself.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

Boiling point	: > 200 °C
Flash point	: 245 °C Method: Pensky-Martens closed cup
Evaporation rate	: No data is available on the product itself.
Flammability (solid, gas)	: No data is available on the product itself.
Burning rate	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Vapour pressure	: < 0,0001 hPa (20 °C)
Relative vapour density	: No data is available on the product itself.
Relative density	: 1,35 (25 °C)
Density	: 1,35 g/cm ³ (25 °C)
Solubility(ies)	
Water solubility	: practically insoluble (20 °C)
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.
Auto-ignition temperature	: No data is available on the product itself.
Decomposition temperature	: No data is available on the product itself.
Viscosity	
Viscosity, dynamic	: 1 200 000 - 1 700 000 mPa.s (25 °C)
Explosive properties	: No data is available on the product itself.
Oxidizing properties	: No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids
Strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : aluminium oxide
carbon dioxide
carbon monoxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

GLYCOLS, POLYPROPYLENE, 2,3-EPOXYPROPYL:

Acute oral toxicity : LD50 (Rat): > 2 000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : No data available

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

GLYCOLS, POLYPROPYLENE, 2,3-EPOXYPROPYL:

Acute dermal toxicity : LD50 (Rat): > 2 000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

GLYCOLS, POLYPROPYLENE, 2,3-EPOXYPROPYL:

Species: No information available.

Assessment: Irritant

Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Irritating to eyes.

GLYCOLS, POLYPROPYLENE, 2,3-EPOXYPROPYL:

Species: No information available.

Assessment: Moderate eye irritant

Result: Irritating to eyes.

Respiratory or skin sensitisation

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Exposure routes: Skin

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLYCOLS, POLYPROPYLENE, 2,3-EPOXYPROPYL:

Exposure routes: Skin

Species: No information available.

Result: May cause sensitisation by skin contact.

Assessment: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

Germ cell mutagenicity

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Result: positive

: Concentration: 0 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Result: positive

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Result: negative

Carcinogenicity

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Species: Rat, male and female
Application Route: Oral
Exposure time: 24 month(s)
Dose: 15 mg/kg
Frequency of Treatment: 7 daily
Method: OECD Test Guideline 453
Result: negative

Species: Mouse, male
Application Route: Dermal
Exposure time: 24 month(s)
Dose: .1 mg/kg
Frequency of Treatment: 3 daily
Method: OECD Test Guideline 453
Result: negative

Species: Rat, female
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 1 mg/kg
Frequency of Treatment: 5 daily
Method: OECD Test Guideline 453
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

Carcinogenicity - : No data available
Assessment

Reproductive toxicity

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Effects on foetal : Species: Rabbit, female
development Application Route: Dermal
General Toxicity Maternal: No observed adverse effect level:
30 mg/kg body weight
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - : No data available
Assessment

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Species: Rat, male and female
NOAEL: 50 mg/kg
Application Route: Ingestion
Exposure time: 14 Weeks Number of exposures: 7 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

Method: Subchronic toxicity

Species: Rat, male and female

NOEL: 10 mg/kg

Application Route: Skin contact

Exposure time: 13 WeeksNumber of exposures: 5 d

Method: Subchronic toxicity

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 WeeksNumber of exposures: 3 d

Method: Subchronic toxicity

Repeated dose toxicity - : No data available
Assessment

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

SECTION 12: Ecological information

12.1 Toxicity

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,5 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,7 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

EC50 (Daphnia magna (Water flea)): 2,7 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 9,4 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to fish (Chronic toxicity) : GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

GLYCOLS, POLYPROPYLENE, 2,3-EPOXYPROPYL:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 67 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 90 mg/l
Exposure time: 48 h

12.2 Persistence and degradability

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

GLYCOLS, POLYPROPYLENE, 2,3-EPOXYPROPYL:

Biodegradability : Result: Not biodegradable
Biodegradation: 7 %
Exposure time: 28 d
Method: OECD Test Guideline 302B

Result: Not readily biodegradable.
Biodegradation: 8 - 27 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117

12.4 Mobility in soil

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Distribution among environmental compartments : Koc: 445

12.5 Results of PBT and vPvB assessment

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

IATA

14.1 UN number : UN 3082
14.2 UN proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(EPOXY PHENOL NOVOLAC RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : Class 9 - Miscellaneous dangerous substances and articles
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IMDG

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(EPOXY PHENOL NOVOLAC RESIN)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
EmS Code : F-A, S-F
14.5 Environmental hazards
Marine pollutant : yes

ADR

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(EPOXY PHENOL NOVOLAC RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
14.5 Environmental hazards
Environmentally hazardous : yes

RID

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(EPOXY PHENOL NOVOLAC RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
14.5 Environmental hazards
Environmentally hazardous : yes

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - List of substances subject to authorisation - Future sunset date : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
E2 ENVIRONMENTAL HAZARDS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

Occupational Illnesses (R-461-3, France) : 51

Installations classified for the protection of the environment (Environment Code R511-9) : 4511

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOIC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.09.2019	400001008258	Date of first issue: 30.09.2019

Print Date 30.01.2024

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
FR VLE	: France. Occupational Exposure Limits (INRS)
2004/37/EC / TWA	: Long term exposure limit
FR VLE / VME	: Time Weighted Average

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 403 RESIN

Version
1.0

Revision Date:
30.09.2019

SDS Number:
400001008258

Date of last issue: -
Date of first issue: 30.09.2019

Print Date 30.01.2024