ZI Haneboesch L-4562 Differdange I UXFMBOURG Phone: +352 58 22 82 1 Fax: +352 58 49 35 E-mail : sales@airtech.lu Website : www.airtech.lu

## **Data Sheet**

# **AIRWEAVE® N4**

## Medium weight non-woven polyester breather/ bleeder

### DESCRIPTION

Airweave® N4 is a good breather for low pressure cures. It conforms well and can be used as a bleeder at any pressure.

#### BENEFITS

- Good breather performance at low pressure, reducing trapped volatiles.
- Efficient bleeder at any pressure for controlled resin bleed.
- Available in regular or fire retardant version.

## TECHNICAL DATA

 $\begin{array}{lll} \mbox{Fibre type} & \mbox{Polyester} \\ \mbox{Colour} & \mbox{White} \\ \mbox{Weight (approx.)} & 140 \mbox{ g/m}^2 \\ \mbox{Maximum use temperature} & 204 \mbox{°C} \\ \mbox{Fire retardant} & \mbox{N/A} \\ \end{array}$ 

Shelf life Unlimited when stored in original packaging at 22°C

#### SIZES

Width	Length	Packaging
152 cm (60 inches)	100 m (109 yards)	1 roll
up to 457 cm (80 inches)	91 m (100 yards)	special order

## NOTES

- Material can be slit in special widths upon request (1 standard roll as minimum order quantity).
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.
- A fire retardant version is available, see Airweave® N4 FR data sheet.

Last updated: 2015-08-10

Catalogue position: Breathers & Bleeders