

MOLYKOTE® G-56 Grease

Lithium soap silicone grease with solid lubricants for plastic/plastic and metal/plastic lubrication

Features

- Compatibility with many plastics
- Broad service temperature range
- Good lubrication for plastics

Composition

- Silicone oil
- Lithium soap
- Solid lubricants and additives

Applications

- Suitable for plastic/plastic and plastic/metal lubrication
- Control cables, sliding parts

How to use

MOLYKOTE® G-56 Grease is easy to apply. First, clean the surface to be lubricated. Then, apply the grease using a brush, a spatula, a grease gun or an automatic lubricating device. During longer production interruptions (e.g., overnight), release pressure from the pump system. Do not mix MOLYKOTE® G-56 Grease with other greases. Before using the product, compatibility tests with plastics should be carried out for swelling and shrinkage, stress cracking, changes in strength and hardness.

Handling precautions

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION.

Usable life and storage

When stored between 0°C and 40°C in the original unopened containers, this product has a usable life of 60 months from the date of production.

Typical properties

Specification writers: These values are not intended for use in preparing specifications. Please contact your local MOLYKOTE® sales representative prior to writing specifications on this product.

Standard ⁽¹⁾	Test	Unit	Result
	Color		Off-white
DIN 51818	NLGI Consistency class		1-2
ISO 2137	Worked Penetration	mm/10	280-340
	Service Temperature range	°C	-40 to 180
ISO 2176	Drop point	°C	> 200
DIN 51 817	Bleed, 24H/150°C	%	≤ 5%
DIN 51 817	Evaporation, 24H/150°C	%	≤ 2%
DIN 51 562	Base oil viscosity at 25°C	cst	350
ASTM D1478-80	Low temperature toque test at -40°C		
	Starting torque	Nm*10 ⁻³	44.3
	Running torque	Nm*10 ⁻³	5.9

⁽¹⁾DIN: Deutsche Industrie Norm. ISO: International Standardization. ASTM: American Society for Testing and Materials.

Packaging

This product is available in different standard container sizes. Detailed container size information should be obtained from your nearest MOLYKOTE® sales office or MOLYKOTE® distributor.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.
© 2022 DuPont.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.