ZI Haneboesch L-4562 Differdange I UXFMBOURG Phone: +352 58 22 82 1 Fax: +352 58 49 35 E-mail : sales@airtech.lu Website : www.airtech.lu

## **Data Sheet**

**GS-213-3** 

# Higher temperature version of GS-213

#### DESCRIPTION

GS-213-3 is a higher temperature version of GS-213. It has slightly lower tack and excellent clean-up on any surface. It is usable up to 232°C.

#### BENEFITS

- Lower tack level, so vacuum bags can be easily repositioned.
- High temperature rating for safer high temperature cures.
- Removes cleanly after cure reducing cost of tool cleaning.

#### TECHNICAL DATA

Colour Light green
Base material Synthetic rubber

Maximum use temperature 232°C

Shelf life 12 months from date of manufacture

Storage conditions

Tape must be stored flat in original packaging at 22°C

Do not refrigerate

#### SIZES

Dimensions	Packaging
3 mm x 12 mm x 7,5 m (1/8 inch x 1/2 inch x 25 feet)	32 rolls per case
3 mm x 19 mm x 7,5 m (1/8 inch x 3/4 inch x 25 feet)	20 rolls per case



### NOTES

- For clean removal, it is recommended to strip the tape from the mould surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated: 2015-08-24

Catalogue position: Vacuum bag sealant tapes