according to Regulation (EC) No. 1907/2006



REN HY 5212

Version	R
1.0	06

levision Date: 6.04.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

[:] REN HY 5212

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Hardener

1.3 Details of the supplier of the safety data sheet

Company Address	 Huntsman Advanced Materials (Europe)BVBA Everslaan 45 3078 Everberg Belgium
Telephone Telefax	: +41 61 299 20 41 : +41 61 299 20 40
E-mail address of person responsible for the SDS	: Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin corrosion, Category 1A	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	H360F: May damage fertility.

according to Regulation (EC) No. 1907/2006

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

Specific target organ toxicity - single exposure, Category 3, Respiratory system

Specific target organ toxicity - repeated exposure, Category 2, Pancreas, Liver, Kidney

Acute aquatic toxicity, Category 1

Chronic aquatic toxicity, Category 1

H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure if swallowed.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Signal word

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

	INU 12/2/200	0)		
:		A Real Provide A real and a read	Ł	
:	Danger			

Hazard statements	: H302 + H312 H314 H317 H335 H360F H373 H410	Harmful if swallowed or in contact with skin Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation. May damage fertility. May cause damage to organs (Pancreas, Liver, Kidney) through prolonged or repeated exposure if swallowed. Very toxic to aquatic life with long lasting effects.
Precautionary statements	: Prevention: P201 P260 P280 Response: P303 + P361 +	Obtain special instructions before use. Do not breathe mist or vapours. Wear protective gloves/ protective clothing/ eye protection/ face protection. P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304 + P340 +	P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
	P305 + P351 +	P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.



.. .

according to Regulation (EC) No. 1907/2006



REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

P308 + P313

IF exposed or concerned: Get medical advice/ attention.

Hazardous components which must be listed on the label: 3,5-Diethyl-2,4-diaminotoluene

1,2-diaminocyclohexane

4,4'-isopropylidenediphenol

Additional Labelling:

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concent ration (% w/w)
Diethylmethylbenzenediamine	68479-98-1 270-877-4 612-130-00-0 01-2119486805-25	Acute Tox. 4; H302 Acute Tox. 4; H312 Eye Irrit. 2; H319 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	60 - 100
Cyclohex-1,2-ylenediamine	694-83-7 211-776-7 -	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Corr. 1A; H314 STOT SE 3; H335	13 - 30
4,4'-Isopropylidenediphenol	80-05-7 201-245-8 604-030-00-0 01-2119457856-23	Eye Dam. 1; H318 Skin Sens. 1; H317 Repr. 1B; H360F STOT SE 3; H335 Aquatic Chronic 2; H411	7 - 13
Toluene-4-sulphonic acid	104-15-4 203-180-0 -	STOT SE 3; H335 Skin Irrit. 2; H315 Eye Irrit. 2; H319	1 - 3

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006



REN HY 5212

Version Rev 1.0 06.0

Revision Date: 06.04.2017

SDS Number: 400001009577

Date of last issue: -Date of first issue: 06.04.2017

SECTION 4: First aid measures

4.1 Description of first aid measures			
General advice	 Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended. 		
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.		
In case of skin contact	 Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. If on skin, rinse well with water. If on clothes, remove clothes. 		
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. 		
If swallowed	 Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital. 		

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: High volume water jet

5.2 Special hazards arising from the substance or mixture

according to Regulation (EC) No. 1907/2006

REN HY 5212



Enriching lives through innovation

Version 1.0	Revision Date: 06.04.2017	SDS Number: 400001009577	Date of last issue: - Date of first issue: 06.04.2017
Spec firefig	ific hazards during hting	: No data is ava	ilable on the product itself.
		Do not allow recourses.	un-off from fire fighting to enter drains or water
Haza produ	rdous combustion lcts	: No hazardous	combustion products are known
		No data is ava	ilable on the product itself.
5.3 Advic	e for firefighters		
	ial protective equipment efighters	: Wear self-con necessary.	tained breathing apparatus for firefighting if
Spec meth	ific extinguishing ods	: No data is ava	ilable on the product itself.
Furth	er information	must not be di Fire residues a	ninated fire extinguishing water separately. This scharged into drains. and contaminated fire extinguishing water must f in accordance with local regulations.

SECTION 6: Accidental release measures

• •	e equipment and emergency procedures Use personal protective equipment. Ensure adequate ventilation.			
6.2 Environmental precautions				
Environmental precautions :	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.			
6.3 Methods and material for containment and cleaning up				
Methods for cleaning up :	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.			

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:

Avoid formation of aerosol. Do not breathe vapours/dust.

according to Regulation (EC) No. 1907/2006

HUNTSMAN

REN HY 5212

Version 1.0	Revision Date: 06.04.2017		OS Number: 0001009577	Date of last issue: - Date of first issue: 06.04.2017
			Avoid contact with For personal prot Smoking, eating a application area. Provide sufficient To avoid spills du Dispose of rinse v regulations. Persons suscepti allergies, chronic	obtain special instructions before use. h skin and eyes. ection see section 8. and drinking should be prohibited in the air exchange and/or exhaust in work rooms. Iring handling keep bottle on a metal tray. water in accordance with local and national ble to skin sensitisation problems or asthma, or recurrent respiratory disease should not ny process in which this mixture is being
	rice on protection against and explosion	:	Normal measures	s for preventive fire protection.
Нус	iene measures	:		ot eat or drink. When using do not smoke. The breaks and at the end of workday.
7.2 Con	ditions for safe storage,	inc	luding any incom	patibilities
	quirements for storage as and containers	:	place. Containers resealed and kep precautions. Elec	ghtly closed in a dry and well-ventilated which are opened must be carefully t upright to prevent leakage. Observe label trical installations / working materials must echnological safety standards.
	commended storage perature	:	2 - 40 °C	
0.1			N I I I I I I I I I I	

7.3 Specific end use(s)

Other data

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
4,4'- isopropylidenediph enol	80-05-7	TWA (inhalable dust)	10 mg/m3	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the			
	long-term exposure should be used			
		TWA (inhalable dust)	10 mg/m3	2009/161/EU
Further information	Indicative	•		

: No decomposition if stored and applied as directed.

8.2 Exposure controls

Personal protective equipment

according to Regulation (EC) No. 1907/2006

REN HY 5212

_



Enriching lives through innovation

Version 1.0	Revision Date: 06.04.2017		S Number: 0001009577	Date of last issue: - Date of first issue: 06.04.2017
Eye	e protection	:	Eye wash bottle w Tightly fitting safet Wear face-shield a problems.	
Ma	nd protection terial eak through time		butyl-rubber > 8 h	
Ma	terial	: Solvent-resistant gloves (butyl-rubber)		gloves (butyl-rubber)
	terial eak through time	:	Nitrile rubber 10 - 480 min	
Rei	marks	:		a specific workplace should be discussed of the protective gloves.
Ski	n and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work p		ection according to the amount and
Res	spiratory protection	:	In the case of vaper approved filter.	our formation use a respirator with an
Filte	er type	:	Combined particul	ates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid	
Colour	: yellow	
Odour	: slight	
Odour Threshold	: No data is available on the product itself.	
рН	: No data is available on the product itself.	
Freezing point	: No data is available on the product itself.	
Melting point	No data is available on the product itself.	
Boiling point	No data is available on the product itself.	
Flash point	: > 150 °C Method: Pensky-Martens closed cup, closed cup	
Evaporation rate	: No data is available on the product itself.	
Flammability (solid, gas)	: No data is available on the product itself.	

according to Regulation (EC) No. 1907/2006

REN HY 5212



Version 1.0	Revision Date: 06.04.2017	SDS Number: 400001009577	Date of last issue: - Date of first issue: 06.04.2017
Burnir	ng rate	: No data is	available on the product itself.
Upper	r explosion limit	: No data is	available on the product itself.
Lower	r explosion limit	: No data is	available on the product itself.
Vapoι	ur pressure	: <0,1 hPa	(25 °C)
Relati	ve vapour density	: No data is	available on the product itself.
Relati	ve density	: No data is	available on the product itself.

Density	: 1 g/cm3 (20 °C)
Solubility(ies) Water solubility	: partly soluble (20 °C)
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n- octanol/water	: No data is available on the product itself.
Auto-ignition temperature	: No data is available on the product itself.
Decomposition temperature	: >200 °C
Viscosity Viscosity, dynamic	: 250 - 350 mPa,s (25 °C)
Explosive properties	: No data is available on the product itself.

9.2 Other information

No data available

Oxidizing properties

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

: No data is available on the product itself.

10.4 Conditions to avoid

Conditions to avoid : No data available

according to Regulation (EC) No. 1907/2006

REN HY 5212

Version	Revisi
1.0	06.04.

Revision Date: 06.04.2017

SDS Number: 400001009577



Enriching lives through innovation

Date of last issue: -Date of first issue: 06.04.2017

10.5 Incompatible materials

10.6 Hazardous decomposition products

Carbon oxides Nitrogen oxides (NOx) Burning produces noxious and toxic fumes.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity - Product	:	Acute toxicity estimate : 632,04 mg/kg Method: Calculation method
Acute inhalation toxicity - Product	:	Acute toxicity estimate : > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity - Product	:	Acute toxicity estimate : 1 340 mg/kg Method: Calculation method
Acute toxicity (other routes of administration)	:	No data available

Skin corrosion/irritation

Components:

diethyltoluenediamine: Species: Rabbit Assessment: No skin irritation Method: OECD Test Guideline 404 Result: No skin irritation

1,2-diaminocyclohexane: Species: Rabbit Method: OECD Test Guideline 404 Result: Causes severe burns. GLP: no

4,4'-isopropylidenediphenol: Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation

P-toluenesulphonic acid: Species: Rabbit Method: OECD Test Guideline 404 Result: Irritating to skin.

according to Regulation (EC) No. 1907/2006

REN HY 5212

Version 1.0

Revision Date: 06.04.2017



Enriching lives through innovation

Date of last issue: -Date of first issue: 06.04.2017

Serious eye damage/eye irritation

Components:

diethyltoluenediamine: Species: Rabbit Assessment: Irritant Result: Irritating to eyes.

Species: Rabbit Assessment: Irritant Method: OECD Test Guideline 405 Result: Normally reversible injuries

1,2-diaminocyclohexane: Species: Rabbit Result: Risk of serious damage to eyes. GLP: no

4,4'-isopropylidenediphenol: Species: Rabbit Method: OECD Test Guideline 405 Result: Irreversible effects on the eye

P-toluenesulphonic acid: Species: Rabbit Result: Irritation to eyes, reversing within 7 days

Assessment: Irritating to eyes. Result: Irritating to eyes.

Respiratory or skin sensitisation

Components:

diethyltoluenediamine: Exposure routes: Skin Species: Guinea pig Result: Does not cause skin sensitisation.


1,2-diaminocyclohexane: Exposure routes: Skin Species: Guinea pig Result: negative

4,4'-isopropylidenediphenol: Exposure routes: Skin Species: Mouse Method: OECD Test Guideline 429 Result: Does not cause skin sensitisation.

Exposure routes: Skin Species: Humans Assessment: May cause sensitisation by skin contact. Result: Causes sensitisation.

according to Regulation (EC) No. 1907/2006

REN HY 5212





according to Regulation (EC) No. 1907/2006

REN HY 5212



		5212			
Ver 1.0	rsion	Revision Date: 06.04.2017	SDS Number: 400001009577	Date of last issue: - Date of first issue: 06.04.2017	
			Result: negative		
	diethylt	onents: oluenediamine: oxicity in vivo	: Application Rou Method: OECD Result: negative	Test Guideline 474	
		minocyclohexane: oxicity in vivo	: Application Rou Exposure time: Dose: 1.6 - 160 Method: OECD Result: negative GLP: yes	13 Weeks mg/m3 Test Guideline 474	
			Application Rou Dose: 75 - 750 r Method: OECD Result: negative GLP: yes	ng/kg Test Guideline 475	
		propylidenediphenol: xicity in vivo	: Method: OECD Result: negative	Test Guideline 474	
		nesulphonic acid: oxicity in vivo	: Application Rou Exposure time: Dose: 4467 mg/ Method: OECD Result: negative	72 h kg Test Guideline 474	
			Application Rou Exposure time: Dose: 580 mg/k Method: EPA O Result: negative	g TS 798.5395	

Carcinogenicity

Components:

diethyltoluenediamine: Species: Rat, (male and female) Application Route: Oral Exposure time: 24 month(s)

according to Regulation (EC) No. 1907/2006

REN HY 5212

Version 1.0	Revision Date: 06.04.2017	SDS Number: 400001009577	Date of last issue: - Date of first issue: 06.04.2017
Frequ Metho Resul	1.8 - 3.2 mg/kg ency of Treatment: 7 da od: OECD Test Guidelin t: negative opropylidenediphenol:		
Applic Expos Frequ	es: Rat, (male and fema ation Route: Oral sure time: 103 weeks ency of Treatment: 7 da t: negative		
Speci Applic Expos Dose: Frequ Metho	enesulphonic acid: es: Rat, (male and fema ation Route: Oral sure time: 24 month(s) >= 240 mg/kg ency of Treatment: 5 da od: OECD Test Guidelin t: negative	aily	
	nogenicity - sment	: No data availab	le
Repro	oductive toxicity		
1,2-di	oonents: aminocyclohexane: s on fertility	: Species: Rat, m Application Rou Method: OECD GLP: yes	
4,4'-is	opropylidenediphenol:		te: Oral Test Guideline 416 toxic effects and adverse effects on the
1,2-di Effect	ponents: aminocyclohexane: s on foetal opment	ca. 184 mg/kg b	te: Oral y Maternal: No observed adverse effect level: body weight Test Guideline 414
4,4'-is	opropylidenediphenol:	Species: Rat, fe Application Rou	



Enriching lives through innovation

according to Regulation (EC) No. 1907/2006

REN HY 5212



ersion .0	Revision Date: 06.04.2017	SDS Number: 400001009577	Date of last issue: - Date of first issue: 06.04.2017
		< 160 mg/kg bo Method: OECE	ty Maternal: No observed adverse effect level: ody weight) Test Guideline 416 togenic effects
P-tolu	ienesulphonic acid:	> 936 mg/kg b	ute: Oral ty Maternal: No observed adverse effect level:
	<u>ponents:</u> sopropylidenediphenol		ltogenic effects

: Clear evidence of adverse effects on sexual function and

fertility, based on animal experiments.

STOT - single exposure

Reproductive toxicity -

Components:

Assessment

1,2-diaminocyclohexane: Exposure routes: Inhalation Target Organs: Respiratory Tract Assessment: May cause respiratory irritation.

4,4'-isopropylidenediphenol:

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

P-toluenesulphonic acid: Target Organs: Respiratory Tract Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

STOT - repeated exposure

Components:

diethyltoluenediamine: Exposure routes: Ingestion Target Organs: Pancreas, Liver, Kidney Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

diethyltoluenediamine: Species: Rat, male and female NOAEL: 8 - 10 mg/kg Application Route: Ingestion

according to Regulation (EC) No. 1907/2006



REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

Exposure time: 2 160 hMethod: Subchronic toxicity

1,2-diaminocyclohexane:
Species: Rat, male and female
: 16
Test atmosphere: dust/mist
Exposure time: 13 WeeksMethod: OECD Test Guideline 413

4,4'-isopropylidenediphenol:
Species: Dog, male and female
: 75 mg/kg, 10
Application Route: Ingestion
Test atmosphere: dust/mist
Exposure time: 2 160 hNumber of exposures: 7 d
Method: Subchronic toxicity

Species: Rat, male and female LOAEL: 600 mg/kg Application Route: Ingestion Exposure time: 672 hNumber of exposures: 7 d Method: Subchronic toxicity

P-toluenesulphonic acid: Species: Rat, male and female NOAEL: >= 500 mg/kg Application Route: Ingestion Exposure time: 672 hNumber of exposures: 7 d Method: Subchronic toxicity

Repeated dose toxicity - : No data available Assessment

Aspiration toxicity

No data available

Experience with human exposure

General Information:	No data available
Inhalation:	No data available
Skin contact:	No data available
Eye contact:	No data available
Ingestion:	No data available

according to Regulation (EC) No. 1907/2006

REN HY 5212

Version 1.0 Revision Date: 06.04.2017

SDS Number: 400001009577

HUNTSMAN

Enriching lives through innovation

Date of last issue: -Date of first issue: 06.04.2017

Toxicology, Metabolism, Distribution No data available

Neurological effects

No data available

Further informationIngestion:No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:		
diethyltoluenediamine:		
Toxicity to fish	: LC50 (Leuciscus idus (Golden orfe)): 200 mg/l Exposure time: 48 h Test Type: static test Test substance: Fresh water Method: DIN 38412	
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 0,5 mg/l Exposure time: 48 h Test Type: static test Test substance: Fresh water Method: Directive 67/548/EEC, Annex V, C.2.	
Toxicity to algae	 ErC50 (Desmodesmus subspicatus (Scenedesmu subspicatus)): ca. 104 mg/l Exposure time: 72 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 201 	IS
M-Factor (Acute aquatic toxicity)	: 1	
Toxicity to microorganisms	 EC50 (Pseudomonas putida): >= 170 mg/l Exposure time: 24 h Test Type: static test Test substance: Fresh water 	
1,2-diaminocyclohexane:		
Toxicity to fish	: LC50 (Leuciscus idus (Golden orfe)): 200 mg/l Exposure time: 48 h Test substance: Fresh water Method: DIN 38412	

according to Regulation (EC) No. 1907/2006

REN HY 5212



Versior 1.0	n	Revision Date: 06.04.2017		S Number: 0001009577	Date of last issue: - Date of first issue: 06.04.2017
				GLP: yes Remarks: Toxic to	aquatic organisms.
	Toxicity to daphnia and other aquatic invertebrates		:	EC50 (Daphnia m Exposure time: 48 Test Type: static t Test substance: F Method: OECD Te GLP: no	est resh water
Тс	Toxicity to algae		:	EC50 : 29,6 mg/l Exposure time: 72 h	
	oxicity xicity	y to fish (Chronic ′)	:	GLP: yes	
ac	quatio	y to daphnia and other c invertebrates ic toxicity)	:	NOEC: 4,16 mg/l Exposure time: 21 Species: Daphnia Test Type: semi-s Test substance: F Method: OECD Te	magna (Water flea) tatic test resh water
		ppropylidenediphenol: y to fish	:	LC50 (Oncorhync Exposure time: 96	hus mykiss (rainbow trout)): 7,5 mg/l 5 h
		y to daphnia and other invertebrates	:	EC50 : 3,9 - 10,2 Exposure time: 48	
				(Ceriodaphnia du	bia (Water flea)):
Тс	oxicit	y to algae	:	EC50 (Selenastru mg/l Exposure time: 96	m capricornutum (green algae)): 2,5 - 3,1 5 h
	oxicity xicity	y to fish (Chronic ')	:	Test Type: flow-th Test substance: F Method: EPA OPI	4 d Iles promelas (fathead minnow) rough test resh water
	-Fact xicity	tor (Chronic aquatic ′)	:	1	
		icology Assessment c aquatic toxicity	:	Toxic to aquatic li	e with long lasting effects.
		enesulphonic acid: y to fish	:	LC50 (Leuciscus i Exposure time: 96	dus (Golden orfe)): 325 mg/l s h

according to Regulation (EC) No. 1907/2006

REN HY 5212



Enriching lives through innovation

	1 5212			
Version 1.0	Revision Date: 06.04.2017	SDS Number: 400001009577	Date of last issue: - Date of first issue: 06.04.2017	
			tatic test nce: Fresh water CD Test Guideline 203	
	ity to daphnia and other ic invertebrates	Exposure tir Test Type: s Test substa		
Toxici	ity to algae	Exposure tir Test Type: s Test substa		1
		subspicatus Exposure tir Test Type: s Test substa	ne: 72 h	
		mg/l Exposure tir Test Type: s		
		mg/l Exposure tir Test Type: s		
Toxici	ty to microorganisms	Exposure tir Test Type: s Test substa		
12.2 Persi	stence and degradabil	lity		
	oonents:			
•	Itoluenediamine: gradability	: Result: Not Biodegradat Exposure tir		
		Result: Not	readily biodegradable.	

Result: Not readily biodegradable. Biodegradation: < 1 % Exposure time: 28 d Method: OECD Test Guideline 301D

according to Regulation (EC) No. 1907/2006

REN HY 5212



1,2-dia	•		est Type: Air	
1,2-dia	minocyclohexane:			
-	•		ate constant: <	.00001
1,2-diaminocyclohexane: Biodegradability		E	esult: Readily k xposure time: 1 lethod: OECD ⁻	
Stability in water		: Method: No information available. GLP: No information available. Remarks: see user defined free text		
Photod	legradation		ate constant: < LP: no	.001
4,4'-isopropylidenediphenol: Biodegradability		В	esult: Not read iodegradation: xposure time: 2	
P-toluenesulphonic acid: Biodegradability		В	esult: Readily k iodegradation: xposure time: 2	> 60 %
12.3 Bioaco	cumulative potential			
diethylt	onents: toluenediamine: umulation	R B	emarks: Bioaco	n factor (BCF): 13,82 cumulation is unlikely. n factor (BCF): 2,75 not bioaccumulate.
Partitio octanol	n coefficient: n- I/water		g Pow: 1,17 (2 lethod: OECD ⁻	5 °C) Test Guideline 107
1,2-diaminocyclohexane: Partition coefficient: n- octanol/water		pl M	g Pow: < -0,9 (H: 7 lethod: OECD ⁻ LP: yes	(20 °C) Test Guideline 107
Partitio	P-toluenesulphonic acid: Partition coefficient: n- octanol/water		g Pow: 0,41 (2 lethod: Partitior	
12.4 Mobilit	ty in soil			

Components: diethyltoluenediamine:

according to Regulation (EC) No. 1907/2006

REN HY 5212



Enriching lives through innovation

Version 1.0	Revision Date: 06.04.2017	SDS Number: 400001009577	Date of last issue: - Date of first issue: 06.04.2017
	bution among onmental compartments	: Koc: 132 - 170	
		: Koc: 31,72 - 551	
12.5 Resu	12.5 Results of PBT and vPvB assessment		
Prod	uct:		
Asse	ssment	to be either persi	nixture contains no components considered stent, bioaccumulative and toxic (PBT), or nd very bioaccumulative (vPvB) at levels of
12.6 Othe	r adverse effects		
Prod	uct:		
	ional ecological nation	unprofessional h	I hazard cannot be excluded in the event of andling or disposal. atic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods	
Product	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

IATA 14.1 UN number	: UN 2735
14.2 UN proper shipping	: Polyamines, liquid, corrosive, n.o.s.
name	(1,2-DIAMINO CYCLOHEXANE, DIETHYLTOLUENEDIAMINE)
14.3 Transport hazard class(es)	: 8
14.4 Packing group	: 11
Labels	: Corrosive
Packing instruction (cargo aircraft)	: 855
Packing instruction (passenger aircraft)	: 851

according to Regulation (EC) No. 1907/2006



REN HY 5212

_

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017
IMDG			

IMDG 14.1 UN number 14.2 UN proper shipping name	: UN 2735 : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
14.3 Transport hazard	(1,2-DIAMINO CYCLOHEXANE, DIETHYLTOLUENEDIAMINE) : 8
class(es) 14.4 Packing group Labels EmS Code 14.5 Environmental hazards	: II : 8 : F-A, S-B
Marine pollutant	: yes
ADR 14.1 UN number 14.2 UN proper shipping name	: UN 2735 : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
14.3 Transport hazard class(es)	(1,2-DIAMINO CYCLOHEXANE, DIETHYLTOLUENEDIAMINE): 8
14.4 Packing group Labels 14.5 Environmental hazards	: II : 8
Environmentally hazardous	: yes
RID 14.1 UN number 14.2 UN proper shipping name	: UN 2735 : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
14.3 Transport hazard	(1,2-DIAMINO CYCLOHEXANE, DIETHYLTOLUENEDIAMINE) : 8
class(es) 14.4 Packing group Labels 14.5 Environmental hazards	: II : 8
Environmentally hazardous Transport in bulk according t	: yes o Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High : 4,4'-isopropylidenediphenol Concern for Authorisation (Article 59).

according to Regulation (EC) No. 1907/2006



REN HY 5212

Version	Revision Date:	SDS Number:	Date
1.0	06.04.2017	400001009577	Date

Date of last issue: -Date of first issue: 06.04.2017

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: Not in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

H302 :	Harmful if swallowed.
H312 :	Harmful in contact with skin.
H314 :	Causes severe skin burns and eye damage.
H315 :	Causes skin irritation.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.

according to Regulation (EC) No. 1907/2006

REN HY 5212



Enriching lives through innovation

Version 1.0	Revision Date: 06.04.2017	SDS Number: 400001009577	Date of last issue: - Date of first issue: 06.04.2017		
H319 H332 H335 H360 H373 H400 H410 H411 H411	2 5 DF 3 0	 May damage fe May cause dam exposure. Very toxic to aq Very toxic to aq Toxic to aquation 	ed. biratory irritation. ortility. nage to organs through prolonged or repeated		
Aquatic Acute: AcAquatic Chronic: ChEye Dam.: SeEye Irrit.: EyRepr.: ReSkin Corr.: ShSkin Irrit.: ShSkin Sens.: ShSTOT RE: Sp		 Acute aquatic to Chronic aquatic Serious eye dat Eye irritation Reproductive to Skin corrosion Skin irritation Skin sensitisatio Specific target of 	Reproductive toxicity Skin corrosion		
Furt	her information				
Classification of the mixture:		ure:	Classification procedure:		
	e Tox. 4	H302	Calculation method		
Acut	e Tox. 4	H312	Calculation method		
Skin	Corr. 1A	H314	Calculation method		
Eye	Dam. 1	H318	Calculation method		
Skin	Sens. 1	H317	Calculation method		
Repr		H360F	Calculation method		
STO	T SE 3	H335	Calculation method		
STO	T RE 2	H373	Calculation method		

Calculation method

Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

H400

H410

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Aquatic Acute 1

Aquatic Chronic 1

according to Regulation (EC) No. 1907/2006



REN HY 5212

Version Revisi 1.0 06.04

Revision Date: 06.04.2017

SDS Number: 400001009577

Date of last issue: -Date of first issue: 06.04.2017

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.