


## THERMAL PAD - DT25


### Features

- Thermal conductivity: 2.5 W/mK
- High conformability
- Cost effective solution
- Electrically insulating
- Naturally sticky
- High dielectric breakdown of up to 5.0 kV/mm
- Custom die-cut parts: custom configurations available



### Applications

- Between electronic components: semiconductors, ICs, CPUs, MOS and heatsink
- LEDs, LCD TV, telecom devices, wireless hubs, PCs, power supplies etc.
- Cooling and thermal modules
- In all applications where a metal housing is used as heatsink.



Part number code (example):

UDT 10/H10 - T 10

→ Thickness: 1.0 mm  
 → Hardness: 10 Shore C  
 → Thermal Conductivity: 1.0 W/mK  
 → UDT: Thermal Pad

### TECNITE DT25

| Properties                  | Unit                  | DT25                                                                                                                                                                                                                                                                                                                                     | Test Method   |
|-----------------------------|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| Composition                 |                       | Silicone & ceramic filled                                                                                                                                                                                                                                                                                                                |               |
| Colour                      |                       | Light yellow                                                                                                                                                                                                                                                                                                                             |               |
| Thickness range             | mm                    | 0.5 - 5.0                                                                                                                                                                                                                                                                                                                                |               |
| Hardness                    | Shore C               | 25                                                                                                                                                                                                                                                                                                                                       | ASTM D2240    |
| Density                     | g/ml                  | 2.93                                                                                                                                                                                                                                                                                                                                     | ASTM D792     |
| Elongation                  | %                     | 72                                                                                                                                                                                                                                                                                                                                       | ASTM D412     |
| Temperature range           | °C                    | -40 to 150                                                                                                                                                                                                                                                                                                                               | EN344         |
| Breakdown voltage           | kV/mm                 | ≥5.0                                                                                                                                                                                                                                                                                                                                     | ASTM D149     |
| Volume impedance            | ohm*cm                | 3.2*10 <sup>16</sup>                                                                                                                                                                                                                                                                                                                     | ASTM D257     |
| Dielectric constant         | @ 1 MHz               | 6.3                                                                                                                                                                                                                                                                                                                                      | ASTM D150     |
| Weight dampify              | %                     | ≥0.5                                                                                                                                                                                                                                                                                                                                     | @ 150 °C 240H |
| Thermal conductivity        | W/mK                  | 2.5                                                                                                                                                                                                                                                                                                                                      | ASTM E1461    |
| Thermal Resistance @ 40 psi | °C-in <sup>2</sup> /W | 0.355 @ 0.5 mm<br>0.542 @ 1.0 mm                                                                                                                                                                                                                                                                                                         |               |
| Compliances                 |                       | UL 94 V-0, RoHS, REACH                                                                                                                                                                                                                                                                                                                   |               |
| Sheet sizes                 |                       | Standard: 200*400 mm, 330*330 mm                                                                                                                                                                                                                                                                                                         |               |
| Custom configurations       |                       | Custom die-cut parts available.<br>Available with acrylic PSA tape for improved application on one or both sides: <ul style="list-style-type: none"> <li>• 3M Double Coated Tape 9448HK (will make the pad 0.15 mm thicker on both sides)</li> <li>• 3M Transfer Tape 3M467 (will make the pad 0.06 mm thicker on both sides)</li> </ul> |               |

### DISTRIBUTORS GROUP EUROPE

Handelsweg 6, NL - 2404 CD Alphen aan den Rijn, The Netherlands  
 Tel. 0031-172-436361 Fax 0031-172-420310  
 info@dge-europe.com www.dge-europe.com

