ZI Haneboesch L-4562 Differdange I UXFMBOURG Phone: +352 58 22 82 1 Fax: +352 58 49 35 E-mail : sales@airtech.lu Website : www.airtech.lu

### **Data Sheet**

# **AIRSEAL 5**

## Economic multi-purpose vacuum sealant tape

#### DESCRIPTION

Airseal 5 is a cost effective sealant tape with excellent tack and softness, designed for the wind energy market and marine industry for vacuum processing at medium temperature. It removes easily from all tool surfaces after cure. It is also suitable for high temperature envelope bagging applications.

### TECHNICAL DATA

Colour Black

Base material Synthetic rubber
Maximum use temperature 150°C bag to tool
180°C bag to bag

Shelf life 18 months from date of manufacture

Storage conditions

Tape must be stored flat in original packaging at 22°C

Do not refrigerate

#### SIZES

Dimensions	Packaging
3 mm x 12 mm x 15 m (1/8 inch x 1/2 inch x 50 feet)	20 rolls per case



#### NOTES

- For clean removal, it is recommended to strip the tape from the mould surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated: 2017-03-13

Catalogue position: Vacuum bag sealant tapes