

NEW PRODUCT INFORMATION

MOLYKOTE® 7325 Grease

DESCRIPTION:

MOLYKOTE® 7325 grease is a silicone oil/lithium soap grease containing EP additives.

TYPICAL USES:

Over-running clutch in starter motor.

TYPICAL PROPERTIES:

Color	light brown
Penetration, 60 worked	295
NLGI # (penetration)	1 to 2 (295 to 325)
Dropping point	>210°C
Corrosion test, DIN 51802	0 to 1 (no corrosion)
4 ball wear test 1420 rpm, 400 N, 1 hour	1.2 mm
4 ball EP test O.K. load	1600 N
Temperature range	40°C to 150°C

APPLICATION METHOD:

Conventional grease application methods (brush, grease gun or automatic) are suitable for use with MOLYKOTE 7325 Grease.

PACKAGING:

55 lb. (25 kg) drums

The information and data contained herein are based on information we believe reliable. You should thoroughly test any application and independently conclude satisfactory performance before commercialization. Suggestions of uses should not be taken as inducements to infringe any particular patent. Safe handling sheets are available from each Dow Corning office.

DOW CORNING CORPORATION
MIDLAND, MICHIGAN 48686-0994

"Molykote" and "Dow Corning" are registered trademarks of Dow Corning Corporation.

