



# SAFETY DATA SHEET

DOW FRANCE S.A.S.

Safety Data Sheet according to Reg. (EU) No 2015/830

**Product name:** SILASTIC™ 8257 Silicone Foam Black Part A

**Revision Date:** 29.10.2018

**Version:** 1.0

**Date of last issue:** -

**Print Date:** 31.10.2018

DOW FRANCE S.A.S. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

**Product name:** SILASTIC™ 8257 Silicone Foam Black Part A

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Polymer

### 1.3 Details of the supplier of the safety data sheet

#### COMPANY IDENTIFICATION

DOW FRANCE S.A.S.  
23 AVENUE JULES RIMET  
93210 LA PLAINE SAINT-DENIS  
FRANCE

**Customer Information Number:**

(31) 115 67 2626  
SDSQuestion@dow.com

### 1.4 EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 00 33 388 736 000

**Local Emergency Contact:** 00 33 388 736 000

**ORFILA:** + 33 (0)1 45 42 59 59

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008:

Flammable liquids - Category 3 - H226

Serious eye damage - Category 1 - H318

Long-term (chronic) aquatic hazard - Category 3 - H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008:**

**Hazard pictograms****Signal word: DANGER****Hazard statements**

- H226 Flammable liquid and vapour.  
H318 Causes serious eye damage.  
H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P303 + P361 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P305 + P351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.  
P310  
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

**Contains** propan-1-ol**2.3 Other hazards**

No data available

---

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

---

**Chemical nature:** Silicone elastomer**3.2 Mixtures**

This product is a mixture.

| CASRN /<br>EC-No. /<br>Index-No. | REACH<br>Registration<br>Number | Concentration | Component | Classification:<br>REGULATION (EC) No<br>1272/2008 |
|----------------------------------|---------------------------------|---------------|-----------|----------------------------------------------------|
|----------------------------------|---------------------------------|---------------|-----------|----------------------------------------------------|

|                                                                                             |                  |                     |                                     |                                                                    |
|---------------------------------------------------------------------------------------------|------------------|---------------------|-------------------------------------|--------------------------------------------------------------------|
| <b>CASRN</b><br>71-23-8<br><b>EC-No.</b><br>200-746-9<br><b>Index-No.</b><br>603-003-00-0   | 01-2119486761-29 | >= 3,0 - <= 5,0 %   | propan-1-ol                         | Flam. Liq. - 2 - H225<br>Eye Dam. - 1 - H318<br>STOT SE - 3 - H336 |
| <b>CASRN</b><br>110-63-4<br><b>EC-No.</b><br>203-786-5<br><b>Index-No.</b><br>—             | 01-2119471849-20 | >= 2,0 - <= 3,0 %   | Butylene glycol<br>(1,4-butanediol) | Acute Tox. - 4 - H302<br>STOT SE - 3 - H336                        |
| <b>CASRN</b><br>1314-13-2<br><b>EC-No.</b><br>215-222-5<br><b>Index-No.</b><br>030-013-00-7 | 01-2119463881-32 | >= 0,41 - <= 0,53 % | Zinc oxide                          | Aquatic Acute - 1 - H400<br>Aquatic Chronic - 1 - H410             |

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

#### General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

**Skin contact:** Wash off with plenty of water. Suitable emergency safety shower facility should be immediately available.

**Eye contact:** Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

**Ingestion:** No emergency medical treatment necessary.

### 4.2 Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician:** Maintain adequate ventilation and oxygenation of the patient. Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

---

## SECTION 5: FIREFIGHTING MEASURES

---

### 5.1 Extinguishing media

**Suitable extinguishing media:** Water spray Alcohol-resistant foam Carbon dioxide (CO<sub>2</sub>) Dry chemical

**Unsuitable extinguishing media:** High volume water jet Do not use direct water stream.

### 5.2 Special hazards arising from the substance or mixture

**Hazardous combustion products:** Silicon oxides Carbon oxides Metal oxides Fluorine compounds

**Unusual Fire and Explosion Hazards:** Flash back possible over considerable distance. Exposure to combustion products may be a hazard to health. Vapours may form explosive mixtures with air.

### 5.3 Advice for firefighters

**Fire Fighting Procedures:** Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Do not use a solid water stream as it may scatter and spread fire.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

**Special protective equipment for firefighters:** In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

**6.1 Personal precautions, protective equipment and emergency procedures:** Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

**6.2 Environmental precautions:** Do not release the product to the aquatic environment above defined regulatory levels Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**6.3 Methods and materials for containment and cleaning up:** Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

#### 6.4 Reference to other sections:

See sections: 7, 8, 11, 12 and 13.

## SECTION 7: HANDLING AND STORAGE

**7.1 Precautions for safe handling:** Avoid inhalation of vapour or mist. Do not swallow. Do not get in eyes. Avoid prolonged or repeated contact with skin. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Non-sparking tools should be used. Handle in accordance with good industrial hygiene and safety practice. Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Ground and bond container and receiving equipment.

**7.2 Conditions for safe storage, including any incompatibilities:** Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Gases. Unsuitable materials for containers: None known.

**7.3 Specific end use(s):** See the technical data sheet on this product for further information.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

| Component                        | Regulation | Type of listing          | Value/Notation    |
|----------------------------------|------------|--------------------------|-------------------|
| propan-1-ol                      | ACGIH      | TWA                      | 100 ppm           |
|                                  | FR VLE     | VME                      | 500 mg/m3 200 ppm |
| Butylene glycol (1,4-butanediol) | Dow IHG    | TWA                      | 10 mg/m3          |
| Zinc oxide                       | ACGIH      | TWA Respirable fraction  | 2 mg/m3           |
|                                  | ACGIH      | STEL Respirable fraction | 10 mg/m3          |
|                                  | FR VLE     | VME                      | 10 mg/m3          |
|                                  | FR VLE     | VME                      | 5 mg/m3           |
|                                  | FR VLE     | VME Fumes                | 5 mg/m3           |
|                                  | FR VLE     | VME Dust                 | 10 mg/m3          |

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

**Derived No Effect Level**

propan-1-ol

**Workers**

| <i>Acute systemic effects</i> |            | <i>Acute local effects</i> |            | <i>Long-term systemic effects</i> |            | <i>Long-term local effects</i> |            |
|-------------------------------|------------|----------------------------|------------|-----------------------------------|------------|--------------------------------|------------|
| Dermal                        | Inhalation | Dermal                     | Inhalation | Dermal                            | Inhalation | Dermal                         | Inhalation |
| n.a.                          | 1723 mg/m3 | n.a.                       | n.a.       | 136 mg/kg bw/day                  | 268 mg/m3  | n.a.                           | n.a.       |

**Consumers**

| <i>Acute systemic effects</i> |            |      | <i>Acute local effects</i> |            | <i>Long-term systemic effects</i> |            |                 | <i>Long-term local effects</i> |            |
|-------------------------------|------------|------|----------------------------|------------|-----------------------------------|------------|-----------------|--------------------------------|------------|
| Dermal                        | Inhalation | Oral | Dermal                     | Inhalation | Dermal                            | Inhalation | Oral            | Dermal                         | Inhalation |
| n.a.                          | 1036 mg/m3 | n.a. | n.a.                       | n.a.       | 81 mg/kg bw/day                   | 80 mg/m3   | 61 mg/kg bw/day | n.a.                           | n.a.       |

Butylene glycol (1,4-butanediol)

**Workers**

| <i>Acute systemic effects</i> |            | <i>Acute local effects</i> |            | <i>Long-term systemic effects</i> |            | <i>Long-term local effects</i> |            |
|-------------------------------|------------|----------------------------|------------|-----------------------------------|------------|--------------------------------|------------|
| Dermal                        | Inhalation | Dermal                     | Inhalation | Dermal                            | Inhalation | Dermal                         | Inhalation |
| n.a.                          | 958 mg/m3  | n.a.                       | n.a.       | 19 mg/kg bw/day                   | 136 mg/m3  | n.a.                           | n.a.       |

**Consumers**

| <i>Acute systemic effects</i> |            |      | <i>Acute local effects</i> |            | <i>Long-term systemic effects</i> |            |                | <i>Long-term local effects</i> |            |
|-------------------------------|------------|------|----------------------------|------------|-----------------------------------|------------|----------------|--------------------------------|------------|
| Dermal                        | Inhalation | Oral | Dermal                     | Inhalation | Dermal                            | Inhalation | Oral           | Dermal                         | Inhalation |
| n.a.                          | 340 mg/m3  | n.a. | n.a.                       | n.a.       | 8 mg/kg bw/day                    | 29 mg/m3   | 8 mg/kg bw/day | n.a.                           | n.a.       |

Zinc oxide

**Workers**

| <i>Acute systemic effects</i> |            | <i>Acute local effects</i> |            | <i>Long-term systemic effects</i> |            | <i>Long-term local effects</i> |            |
|-------------------------------|------------|----------------------------|------------|-----------------------------------|------------|--------------------------------|------------|
| Dermal                        | Inhalation | Dermal                     | Inhalation | Dermal                            | Inhalation | Dermal                         | Inhalation |
| n.a.                          | n.a.       | n.a.                       | n.a.       | 83 mg/kg bw/day                   | 5 mg/m3    | n.a.                           | n.a.       |

**Consumers**

| <i>Acute systemic effects</i> |            |      | <i>Acute local effects</i> |            | <i>Long-term systemic effects</i> |            |                   | <i>Long-term local effects</i> |            |
|-------------------------------|------------|------|----------------------------|------------|-----------------------------------|------------|-------------------|--------------------------------|------------|
| Dermal                        | Inhalation | Oral | Dermal                     | Inhalation | Dermal                            | Inhalation | Oral              | Dermal                         | Inhalation |
| n.a.                          | n.a.       | n.a. | n.a.                       | n.a.       | 83 mg/kg bw/day                   | 2,5 mg/m3  | 0,83 mg/kg bw/day | n.a.                           | n.a.       |

**Predicted No Effect Concentration**

propan-1-ol

| Compartment              | PNEC                         |
|--------------------------|------------------------------|
| Fresh water              | 10 mg/l                      |
| Marine water             | 1 mg/l                       |
| Intermittent use/release | 10 mg/l                      |
| Fresh water sediment     | 22,8 mg/kg dry weight (d.w.) |
| Marine sediment          | 2,28 mg/kg dry weight (d.w.) |
| Soil                     | 2,2 mg/kg                    |
| Sewage treatment plant   | 96 mg/l                      |

Butylene glycol (1,4-butanediol)

| Compartment              | PNEC        |
|--------------------------|-------------|
| Fresh water              | 0,813 mg/l  |
| Marine water             | 0,0813 mg/l |
| Intermittent use/release | 8,13 mg/l   |
| Sewage treatment plant   | 1554 mg/l   |
| Fresh water sediment     | 3,61 mg/kg  |
| Marine sediment          | 0,361 mg/kg |
| Soil                     | 0,244 mg/kg |

Zinc oxide

| Compartment            | PNEC        |
|------------------------|-------------|
| Fresh water            | 20,6 µg/l   |
| Marine water           | 6,1 µg/l    |
| Sewage treatment plant | 52 µg/l     |
| Fresh water sediment   | 117,8 mg/kg |
| Marine sediment        | 56,5 mg/kg  |
| Soil                   | 35,6 mg/kg  |

## 8.2 Exposure controls

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

### Individual protection measures

**Eye/face protection:** Use chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent. When handling hot material: Wear a face-shield which allows use of chemical goggles, or wear a full-face respirator (meeting standard EN 136), to protect face and eyes when there is any likelihood of splashes.

#### Skin protection

**Hand protection:** Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Use gloves with insulation for thermal protection (EN 407), when needed. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 3 or

higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Wear clean, body-covering clothing. When handling hot material, protect skin from thermal burns. Selection of specific items will depend on the operation.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. Use an approved air-purifying respirator when vapors are generated at increased temperatures or when dust or mist is present.

Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2 (meeting standard EN 14387).

#### Environmental exposure controls

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

#### Appearance

|                                      |                         |
|--------------------------------------|-------------------------|
| Physical state                       | viscous liquid          |
| Color                                | grey                    |
| Odor                                 | alcohol-like            |
| Odor Threshold                       | No data available       |
| pH                                   | No data available       |
| Melting point/range                  | No data available       |
| Freezing point                       | No data available       |
| Boiling point (760 mmHg)             | > 100 °C                |
| Flash point                          | <b>closed cup</b> 39 °C |
| Evaporation Rate (Butyl Acetate = 1) | No data available       |
| Flammability (solid, gas)            | Not applicable          |
| Lower explosion limit                | No data available       |

|                                        |                                                          |
|----------------------------------------|----------------------------------------------------------|
| Upper explosion limit                  | No data available                                        |
| Vapor Pressure                         | No data available                                        |
| Relative Vapor Density (air = 1)       | No data available                                        |
| Relative Density (water = 1)           | 1,06                                                     |
| Water solubility                       | No data available                                        |
| Partition coefficient: n-octanol/water | No data available                                        |
| Auto-ignition temperature              | No data available                                        |
| Decomposition temperature              | No data available                                        |
| Dynamic Viscosity                      | 23 000 mPa.s                                             |
| Kinematic Viscosity                    | No data available                                        |
| Explosive properties                   | Not explosive                                            |
| Oxidizing properties                   | The substance or mixture is not classified as oxidizing. |

## 9.2 Other information

|                  |                   |
|------------------|-------------------|
| Molecular weight | No data available |
| Particle size    | Not applicable    |

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## SECTION 10: STABILITY AND REACTIVITY

---

**10.1 Reactivity:** Not classified as a reactivity hazard.

**10.2 Chemical stability:** Stable under normal conditions.

**10.3 Possibility of hazardous reactions:** Can react with strong oxidizing agents. Vapours may form explosive mixture with air. Flammable liquid and vapour.

**10.4 Conditions to avoid:** Heat, flames and sparks.

**10.5 Incompatible materials:** Oxidizing agents

**10.6 Hazardous decomposition products:** Formaldehyde.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

*Toxicological information appears in this section when such data is available.*

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): Estimated.  
LD50, Rat, > 5 000 mg/kg

**Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s): Estimated.  
LD50, Rabbit, > 2 000 mg/kg

**Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility. Vapors/fumes released during thermal processing may cause respiratory irritation. May cause central nervous system effects.

As product: The LC50 has not been determined.

**Skin corrosion/irritation**

Brief contact is essentially nonirritating to skin.

Material may be handled at elevated temperatures; contact with heated material may cause thermal burns.

**Serious eye damage/eye irritation**

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

**Sensitization**

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Contains component(s) which are classified as specific target organ toxicant, single exposure, category 3.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Contains component(s) which have been reported to cause effects on the following organs in animals:  
Thymus.

Lung.

Central nervous system.

Bladder.

Liver.

**Carcinogenicity**

No relevant data found.

**Teratogenicity**

Contains component(s) which, in laboratory animals, have been toxic to the fetus only at doses toxic to the mother. At extremely high concentrations, n-propanol has been reported to cause birth defects in rats. At progressively lower concentrations there were no birth defects. These concentrations exceed relevant human dose levels.

**Reproductive toxicity**

Based on information for component(s): In animal studies, has been shown to interfere with fertility in males. Effects are reversible. These concentrations exceed relevant human dose levels.

**Mutagenicity**

Contains component(s) which were negative in some in vitro genetic toxicity studies and positive in others.

**Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

**COMPONENTS INFLUENCING TOXICOLOGY:****propan-1-ol****Acute inhalation toxicity**

Prolonged excessive exposure may cause adverse effects. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness.

LC50, Rat, male and female, 4 Hour, vapour, > 33,8 mg/l OECD Test Guideline 403

**Butylene glycol (1,4-butanediol)****Acute inhalation toxicity**

LC50, Rat, 4 Hour, dust/mist, > 5,1 mg/l The LC50 value is greater than the Maximum Attainable Concentration.

**Zinc oxide****Acute inhalation toxicity**

LC50, Rat, 4 Hour, dust/mist, > 5 mg/l No deaths occurred at this concentration.

---

**SECTION 12: ECOLOGICAL INFORMATION**

---

*Ecotoxicological information appears in this section when such data is available.*

**12.1 Toxicity****propan-1-ol****Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 4 555 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

LC50, scud Gammarus sp., static test, 48 Hour, 1 000 mg/l

EC50, Daphnia magna (Water flea), static test, 48 Hour, 3 644 mg/l, OECD Test Guideline 202 or Equivalent

**Acute toxicity to algae/aquatic plants**

EC50, Pseudokirchneriella subcapitata (green algae), static test, 48 Hour, Growth rate inhibition, 9 170 mg/l

**Toxicity to bacteria**

IC50, activated sludge, static test, 3 Hour, > 1 000 mg/l, OECD 209 Test

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, > 100 mg/l

**Butylene glycol (1,4-butanediol)****Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, > 30 000 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, 813 mg/l, OECD Test Guideline 202 or Equivalent

**Acute toxicity to algae/aquatic plants**

EbC50, alga Scenedesmus sp., 72 Hour, Biomass, > 1 000 mg/l, OECD Test Guideline 201 or Equivalent

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, > 85 mg/l

**Zinc oxide****Acute toxicity to fish**

Material is very toxic to aquatic organisms (LC50/EC50/IC50 below 1 mg/L in the most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 0,14 - 1,1 mg/l

LC50, Danio rerio (zebra fish), 96 Hour, 1 - 10 mg/l

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, 1 - 10 mg/l

**Acute toxicity to algae/aquatic plants**

IC50, Selenastrum capricornutum (green algae), 72 Hour, Growth rate, 0,136 mg/l

**Toxicity to bacteria**

Based on data from similar materials

EC50, 3 Hour, 5,2 mg/l, OECD Test Guideline 209

**Chronic toxicity to fish**

NOEC, Danio rerio (zebra fish), 32 d, mortality, >= 0,540 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, 0,04 mg/l

**12.2 Persistence and degradability****propan-1-ol**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 83 %

**Exposure time:** 5 d

**Method:** OECD Test Guideline 301D or Equivalent

10-day Window: Pass

**Biodegradation:** 83 - 92 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301F or Equivalent

**Theoretical Oxygen Demand:** 2,40 mg/mg

#### **Photodegradation**

**Test Type:** Half-life (indirect photolysis)

**Sensitization:** Ozone.

**Atmospheric half-life:** 23 Hour

**Method:** Estimated.

#### **Butylene glycol (1,4-butanediol)**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 96 %

**Exposure time:** 14 d

**Method:** OECD Test Guideline 301A or Equivalent

#### **Zinc oxide**

**Biodegradability:** Biodegradability is not applicable to inorganic substances.

### **12.3 Bioaccumulative potential**

#### **propan-1-ol**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 0,25 Measured

#### **Butylene glycol (1,4-butanediol)**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** -0,88 Measured

**Bioconcentration factor (BCF):** 3,16 Fish Estimated.

#### **Zinc oxide**

**Bioaccumulation:** Partitioning from water to n-octanol is not applicable.

**Bioconcentration factor (BCF):** 177 Fish

### **12.4 Mobility in soil**

#### **propan-1-ol**

Potential for mobility in soil is very high (Koc between 0 and 50).

**Partition coefficient (Koc):** 3 Estimated.

#### **Butylene glycol (1,4-butanediol)**

Potential for mobility in soil is very high (Koc between 0 and 50).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

**Partition coefficient (Koc):** 1 Estimated.

**Zinc oxide**

No relevant data found.

**12.5 Results of PBT and vPvB assessment**

**propan-1-ol**

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

**Butylene glycol (1,4-butanediol)**

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

**Zinc oxide**

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

**12.6 Other adverse effects**

**propan-1-ol**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

**Butylene glycol (1,4-butanediol)**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

**Zinc oxide**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

---

## **SECTION 13: DISPOSAL CONSIDERATIONS**

---

**13.1 Waste treatment methods**

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

---

## **SECTION 14: TRANSPORT INFORMATION**

---

**Classification for ROAD and Rail transport (ADR/RID):**

**14.1 UN number** UN 1993

**14.2 UN proper shipping name** FLAMMABLE LIQUID, N.O.S.(Propan-1-ol)

- 14.3 Transport hazard class(es) 3
- 14.4 Packing group III
- 14.5 Environmental hazards Not considered environmentally hazardous based on available data.
- 14.6 Special precautions for user Hazard Identification Number: 30

**Classification for SEA transport (IMO-IMDG):**

- 14.1 UN number UN 1993
- 14.2 UN proper shipping name FLAMMABLE LIQUID, N.O.S.(Propan-1-ol)
- 14.3 Transport hazard class(es) 3
- 14.4 Packing group III
- 14.5 Environmental hazards Not considered as marine pollutant based on available data.
- 14.6 Special precautions for user EmS: F-E, S-E
- 14.7 Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

- 14.1 UN number UN 1993
- 14.2 UN proper shipping name Flammable liquid, n.o.s.(Propan-1-ol)
- 14.3 Transport hazard class(es) 3
- 14.4 Packing group III
- 14.5 Environmental hazards Not applicable
- 14.6 Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

**SECTION 15: REGULATORY INFORMATION**

---

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH Regulation (EC) No 1907/2006

This product contains only components that have been either pre-registered, registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH). The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

**Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.**

Listed in Regulation: FLAMMABLE LIQUIDS

Number in Regulation: P5c

5 000 t

50 000 t

**Installations classified for the protection of the environment (Environment Code R511-9)**

4331: Flammable liquids category 2 or 3 excluding rubric 4330

**Occupational Illnesses (R-461-3, France):** Table: 84 (Health effects caused by professional use of liquid organic solvents (indicated in the table).)

**Further information**

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

**15.2 Chemical safety assessment**

Not applicable

---

## SECTION 16: OTHER INFORMATION

---

**Full text of H-Statements referred to under sections 2 and 3.**

|      |                                                       |
|------|-------------------------------------------------------|
| H225 | Highly flammable liquid and vapour.                   |
| H226 | Flammable liquid and vapour.                          |
| H302 | Harmful if swallowed.                                 |
| H318 | Causes serious eye damage.                            |
| H336 | May cause drowsiness or dizziness.                    |
| H400 | Very toxic to aquatic life.                           |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects.    |

**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008**

Flam. Liq. - 3 - H226 - Based on product data or assessment

Eye Dam. - 1 - H318 - Calculation method

Aquatic Chronic - 3 - H412 - Calculation method

**Revision**

Identification Number: 4130354 / A560 / Issue Date: 29.10.2018 / Version: 1.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

### Legend

|                 |                                                  |
|-----------------|--------------------------------------------------|
| ACGIH           | USA. ACGIH Threshold Limit Values (TLV)          |
| Dow IHG         | Dow Industrial Hygiene Guideline                 |
| FR VLE          | France. Occupational Exposure Limits (INRS)      |
| STEL            | Short-term exposure limit                        |
| TWA             | Time weighted average                            |
| VME             | Time Weighted Average                            |
| Acute Tox.      | Acute toxicity                                   |
| Aquatic Acute   | Short-term (acute) aquatic hazard                |
| Aquatic Chronic | Long-term (chronic) aquatic hazard               |
| Eye Dam.        | Serious eye damage                               |
| Flam. Liq.      | Flammable liquids                                |
| STOT SE         | Specific target organ toxicity - single exposure |

### Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW FRANCE S.A.S. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

FR