

Data Sheet

WRIGHTLON® 8400

Nylon vacuum bagging film

DESCRIPTION

Wrightlon® 8400 is a high temperature nylon vacuum bagging film with more than 30 years worldwide proven performance. It is called out on many aerospace specifications for use temperatures up to 232°C. It is recommended for cures with phenolic resins.

BENEFITS

- Heat resistance provides vacuum security during high temperature cures of expensive parts.
- Proven performance and approvals on specifications worldwide gained over more than 30 years.
- High strength and chemical resistance reduces bag failures with aggressive phenolic resins.


TECHNICAL DATA

		Test method
Material type	Nylon	
Elongation at break	350 %	ASTM D 882
Tensile strength	62 MPa	ASTM D 882
Maximum use temperature	232°C	
Flammability (self extinguishing)	Yes	ATP-5034
Materials to avoid	Strong oxidizers	
Colour	Blue	
Shelf life	Unlimited when stored in original packaging at 22°C	

SIZES

Thickness	Width	Forms Available*
50 µm (0,002 inch)	up to 3,66 m (144 inches)	SHT, CF, LFT
75 µm (0,003 inch)	up to 4,57 m (180 inches)	SHT, CF, LFT


- For more sizes, see the *Commonly Used Sizes* chart in this section.
- Custom shapes and sizes are available, please contact Airtech for more information.



*SHT=Sheeting




CF=Centerfold



LFT=Lay-Flat
Tubing



GT=Gusseted
Tubing



G=Gusseted

← Slit
Open Edge

NOTES

- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.