ZI Haneboesch L-4562 Differdange I UXFMBOURG Phone: +352 58 22 82 1 Fax: +352 58 49 35 E-mail : sales@airtech.lu Website : www.airtech.lu

Data Sheet

ECONOLEASE

Coated nylon peel ply

DESCRIPTION

Econolease is a silicone treated nylon peel ply which provides greater release in difficult environments.

Our Econo peel plies are designed to work in resin infusion or hand lay-up processes. All coated peel plies have the potential to transfer.

BENEFITS

• Lower cost fabric reduces overall cost of vacuum bag process materials.

• Release coating reduces the effort required to remove peel ply from laminate.

• Peel plies strip off cured laminates leaving a fine textured surface, reducing time spent hand finishing.

TECHNICAL DATA

Maximum use temperature 204°C Fibre type Nylon Weight 61 g/m²

Thickness 0,101 mm (0,004 inch)

Colour Light blue Coating type Silicone

Shelf life Unlimited when stored in original packaging at 22°C

SIZES

Width	Length	Packaging
152 cm (60 inch)	91 m (100 yards)	1 roll

NOTES

- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.
- Hot knife (sealed edge) slitting upon request with 1 roll as minimum order quantity.
- Certain phenolic resins will adhere to this product. Airtech recommends testing prior to use.

Last updated: 2015-08-04