



The Public Health and Safety Organization

## NSF Product and Service Listings

These NSF Official Listings are current as of **Tuesday, April 14, 2015** at 12:15 a.m. Eastern Time. Please contact NSF International to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:

<http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=13630&Standard=061&>

### NSF/ANSI 61 Drinking Water System Components - Health Effects

**NOTE:** Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of Abbreviations used in these Listings.

#### Dow Corning Corporation

P.O. Box 994

Mail No. C03101

Midland, MI 48686-0994

United States

989-496-4000

**Facility :** Elizabethtown, KY

#### Joining and Sealing Materials

Trade Designation	Size	Water	Water
		Contact	Contact
		Temp	Material
<b>Sealants</b>			
Dow Corning® 732 Gasket Sealant - Aluminum	[1]	C. HOT	SLC
Dow Corning® 732 Gasket Sealant - Black	[1]	C. HOT	SLC
Dow Corning® 732 Gasket Sealant - Bronze	[1]	C. HOT	SLC

Dow Corning® 732 Gasket Sealant - Clear	[1]	C. HOT	SLC
Dow Corning® 732 Gasket Sealant - White	[1]	C. HOT	SLC
Dow Corning® 732 Multipurpose - Aluminum	[1]	C. HOT	SLC
Dow Corning® 732 Multipurpose - Black	[1]	C. HOT	SLC
Dow Corning® 732 Multipurpose - Bronze	[1]	C. HOT	SLC
Dow Corning® 732 Multipurpose - Clear	[1]	C. HOT	SLC
Dow Corning® 732 Multipurpose - White	[1]	C. HOT	SLC
Dow Corning® 748 Non-Corrosive Sealant	[2]	C. HOT	SLC
Dow Corning® Linha Branca Tipo	[1]	C. HOT	SLC

[1] Certified for a maximum surface area to volume ratio of 14.5 sq. in./L.

[2] Certified for a maximum surface area to volume ratio of 0.4 sq. in./L.

## Facility : Greensboro, NC

### Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Lubricants			
Dow Corning® 111 Valve Lubricant & Sealant	[1]	C. HOT	SLC
Dow Corning® 4 Electrical Insulating Compound	[1]	C. HOT	SLC
Dow Corning® 7 Release Compound	[1]	C. HOT	SLC
Dow Corning® High Vacuum Grease	[1]	C. HOT	SLC
MOLYKOTE 111 Compound	[1]	C. HOT	SLC

[1] Certified for a maximum surface area to volume ratio of 40 sq. in./L.

### Sealants

Dow Corning® 732 Multipurpose - Aluminum	[2]	C. HOT	SLC
Dow Corning® 732 Multipurpose - Black	[2]	C. HOT	SLC
Dow Corning® 732 Multipurpose - Clear	[2]	C. HOT	SLC
Dow Corning® 732 Multipurpose - White	[2]	C. HOT	SLC
Dow Corning® 748 Non-Corrosive Sealant	[3]	C. HOT	SLC
Dow Corning® HM-2500 Assembly Sealant	[2]	C. HOT	SLC
Dow Corning® HM-2510 Assembly Sealant	[2]	C. HOT	SLC
Dow Corning® HM-2515 Assembly Sealant	[2]	C. HOT	SLC
Dow Corning® HM-2520 Assembly Sealant	[2]	C. HOT	SLC

- [2] Certified for a maximum surface area to volume ratio of 14.5 sq. in./L.  
 [3] Certified for a maximum surface area to volume ratio of 0.4 sq. in./L.

## Mechanical Plumbing Devices

### Trade Designation

*Miscellaneous Faucet Components*[1]

**Dow Corning 111 Valve Lubricant/Sealant**

**Dow Corning 7 Release Compound**

**Dow Corning 4 Electrical Insulating Compound**

**Dow Corning High Vacuum Grease**

**Molykote 111 Compound**

- [1] Certified for a maximum surface area to volume ratio of 40 sq. in./L.

**Facility :** Shanghai, China

## Joining and Sealing Materials

Trade Designation	Water		Water
	Size	Contact Temp	Contact Material
<b>Lubricants</b>			
Dow Corning® 4 Electrical Insulating Compound	[1]	C. HOT	LUB
Dow Corning® 7 Release Compound	[1]	C. HOT	LUB
Molykote® 111 Compound	[1]	C. HOT	LUB

[1] Certified for a maximum surface area to volume ratio of 40 sq. in./L.

**Mechanical Plumbing Devices**

**Trade Designation**

**Lubricants**

Dow Corning® 4 Electrical Insulating Compound[1]  
Dow Corning® 7 Release Compound[1]  
Molykote® 111 Compound[1]

[1] Certified for a maximum surface area to volume ratio of 40 sq. in./L.

**Facility :** Wiesbaden, Germany

**Joining and Sealing Materials**

Trade Designation	Size	Water	Water
		Contact	Contact
		Temp	Material
<b>Lubricants</b>			
Molykote® 111 Compound	[1]	C. HOT	LUB

[1] Certified for a maximum surface area to volume ratio of 40 sq. in./L.

**Mechanical Plumbing Devices**

**Trade Designation**

*Lubricants*

NA  
Molykote® 111 Compound[1]

[1] Certified for a maximum surface area to volume ratio of 40 sq. in./L.

**Facility :** Ashigara-Kamigun, Kanagawa, Japan

**Joining and Sealing Materials**

Trade Designation	Size	Water	Water
		Contact	Contact
		Temp	Material
<b>Lubricants</b>			
MOLYKOTE® 7508 Valve Grease	[1]	C. HOT	LUB

[1] Certified for a maximum surface area to volume ratio of 40 sq. in./L.

---

Number of matching Manufacturers is 1  
Number of matching Products is 40  
Processing time was 0 seconds

