

Data Sheet

AIRSEAL 5

Economic multi-purpose vacuum sealant tape

■ DESCRIPTION

Airseal 5 is a cost effective sealant tape with excellent tack and softness, designed for the wind energy market and marine industry for vacuum processing at medium temperature. It removes easily from all tool surfaces after cure. It is also suitable for high temperature envelope bagging applications.

■ TECHNICAL DATA

Colour	Black
Base material	Synthetic rubber
Maximum use temperature	150°C bag to tool 180°C bag to bag
Shelf life	18 months from date of manufacture
Storage conditions	Tape must be stored flat in original packaging at 22°C Do not refrigerate

■ SIZES

Dimensions	Packaging
3 mm x 12 mm x 15 m (1/8 inch x 1/2 inch x 50 feet)	20 rolls per case



■ NOTES

- For clean removal, it is recommended to strip the tape from the mould surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated : 2017-03-13

Catalogue position : [Vacuum bag sealant tapes](#)

As the conditions or methods of use, including storage, are beyond our control, Airtech Europe does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech Europe disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes. This translation is provided for your convenience only. The official language is English and the official law is Luxembourg.