

Data Sheet

AIRSEAL 2

Economical vacuum bag sealant tape

■ DESCRIPTION

Airseal 2 is a cost effective vacuum bag sealant tape for room and medium temperature applications. Airseal 2 has been specially formulated to provide excellent tack, firm feel, good clean-up and long shelf life. It can also be used for higher temperature envelope bag applications.

Airseal 2 - Standard tack version.

Airseal 2 Tacky - Superior tack for colder environments.

Airseal 2 Super Tacky - Very soft and very high tack version.

■ BENEFITS

- Lower material cost.
- Long shelf life reduces waste.
- Tacky versions have better tack for colder environments.

■ TECHNICAL DATA

Colour	Black
Base material	Synthetic rubber
Maximum use temperature	150°C (bag to tool) 180°C (bag to bag)
Shelf life	18 months from the date of manufacture
Storage conditions	Tape must be stored flat in original packaging at 22°C Do not refrigerate

■ SIZES

Dimensions	Dimensions	Packaging
3 mm x 12 mm x 15 m	1/8 inch x 1/2 inch x 50 feet	20 rolls per case
3 mm x 9 mm x 15 m	1/8 inch x 1/3 inch x 50 feet	20 rolls per case
2 mm x 10 mm x 20 m	1/12 inch x 2/5 inch x 65,6 feet	20 rolls per case
2 mm x 7 mm x 20 m	1/12 inch x 1/4 inch x 65,6 feet	20 rolls per case
4 mm diameter bead x 7,5 m	1/6 inch diameter bead x 25 feet	40 rolls per case



■ NOTES

- For clean removal from moulds, it is recommended to strip the tape from the mould surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated : 2015-10-14

Catalogue position : Vacuum bag sealant tapes

As the conditions or methods of use, including storage, are beyond our control, Airtech Europe does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech Europe disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes. This translation is provided for your convenience only. The official language is English and the official law is Luxembourg.