



SAFETY DATA SHEET

Permabond ET510B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond ET510B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Two-component, epoxy-based adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Permabond Engineering Adhesives GmbH
Niederkasseler Lohweg 18
40547 Düsseldorf
Germany
info.europe@permabond.com

Manufacturer Permabond Engineering Adhesives Ltd.
Wessex Way
Colden Common
Winchester
Hampshire SO21 1WP
United Kingdom
Tel: +44 (0)1962 711 661
Fax: +44 (0)1962 711 662
info@permabond.co.uk

1.4. Emergency telephone number

Emergency telephone CHEMTREC UK: +(44)-870-8200418 CHEMTREC US: 800-424-9300 (CCN: 829878)

National emergency telephone number CHEMTREC Ireland: +(353)-19014670
CHEMTREC Australia: +(61)-290372994
CHEMTREC New Zealand: +(64)-98010034

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word

Danger

PermaBond ET510B

Hazard statements	H315 Causes skin irritation. H318 Causes serious eye damage. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352a IF ON SKIN: Wash with plenty of soap and water P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Contains	POLYAMINOAMIDE, MERCAPTAN-TERMINATED OLIGOMER
Supplementary precautionary statements	P264 Wash contaminated skin thoroughly after handling. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P501 Dispose of contents/container in accordance with existing Community, National and local regulations.

2.3. Other hazards

None under normal conditions. This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

POLYAMINOAMIDE			60-100%
CAS number: 68082-29-1	EC number: 500-191-5	REACH registration number: 01-2119972320-44-XXXX	
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411			
MERCAPTAN-TERMINATED OLIGOMER			10-30%
CAS number: —	EC number: 701-196-7	REACH registration number: 01-2120118957-46-XXXX	
Classification Skin Sens. 1B - H317 Aquatic Chronic 3 - H412			

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. If symptoms develop, obtain medical attention

PermaBond ET510B

Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove any contact lenses and open eyelids wide apart. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact Skin irritation. Mild dermatitis, allergic skin rash.

Eye contact May cause serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products Burning produces irritating, toxic and obnoxious fumes. Nitrous gases (NOx). Carbon monoxide, carbon dioxide, and unknown hydrocarbons.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for disposal. Wash area with soap and water.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Do not ingest or inhale. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C.

7.3. Specific end use(s)

Specific end use(s) Adhesive. Sealant.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Permabond ET510B

POLYAMINOAMIDE (CAS: 68082-29-1)

DNEL	Workers - Inhalation; Long term systemic effects: 3.9 mg/m ³ Workers - Dermal; Long term systemic effects: 1.1 mg/kg/day
PNEC	Fresh water; 0.004 mg/l marine water; 0 mg/l STP; 3.84 mg/l Sediment (Freshwater); 434.02 mg/kg Sediment (Marinewater); 43.4 mg/kg

MERCAPTAN-TERMINATED OLIGOMER

DMEL	Workers - Inhalation; Long term systemic effects: 22 mg/m ³ Workers - Dermal; Long term systemic effects: 2.7 mg/kg/day
PNEC	Fresh water; 70 µg/l marine water; 7 µg/l STP; 10 mg/l Sediment (Freshwater); 322 µg/kg, dw Sediment (Marinewater); 32 µg/kg, dw Soil; 23 µg/kg, dw

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. Gloves should conform to EN 374. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 0.5 hours. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 8 hours. The breakthrough time for any glove material may be different for different glove manufacturers. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body protection

Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Use of good industrial hygiene practices is required.

PermaBond ET510B

Respiratory protection	Ensure adequate ventilation of the working area. Respiratory protection may be required if excessive airborne contamination occurs. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Organic vapour filter. Type A. (EN14387)
-------------------------------	---

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Amber.
Odour	Mild.
Odour threshold	Not available.
pH	Not available.
Melting point	Not determined.
Initial boiling point and range	Not applicable.
Flash point	>100°C
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not determined.
Vapour density	Not available.
Relative density	1.1
Solubility(ies)	Insoluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	Not available.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not available.
Viscosity	≈35000 mPa s @ 23°C
Explosive properties	Not determined.
Oxidising properties	Not determined.

9.2. Other information

Other information	Not relevant.
--------------------------	---------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Under normal conditions of storage and use, no hazardous reactions will occur.
-------------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
------------------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Reactions with the following materials may generate heat: Amines.
---	---

PermaBond ET510B

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified organic compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Skin sensitisation

Skin sensitisation May cause sensitisation by skin contact.

Aspiration hazard

Aspiration hazard None under normal conditions.

Inhalation

Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature. In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

Ingestion

No harmful effects expected from quantities likely to be ingested by accident.

Skin contact

Irritating to skin. May cause an allergic skin reaction.

Eye contact

Causes serious eye damage.

Toxicological information on ingredients.

POLYAMINOAMIDE

Acute toxicity - oral

Acute toxicity oral (LD₅₀) 2,000.1 mg/kg

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀) 2,000.1 mg/kg

Species Rat

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Irritating to eyes.

Respiratory sensitisation

PermaBond ET510B

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro No information available.

Carcinogenicity

Carcinogenicity No specific test data are available.

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEL 1000 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard Not available.

MERCAPTAN-TERMINATED OLIGOMER

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,600.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 10,200.0

Species Rabbit

Skin corrosion/irritation

Animal data Method: OECD 404, Rabbit Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Method: OECD 405, Rabbit Not irritating.

Skin sensitisation

Skin sensitisation Local Lymph Node Assay (LLNA) - Mouse: Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

PermaBond ET510B

Reproductive toxicity - fertility No information available.

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard No information available.

SECTION 12: Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects. Avoid release to the environment.

12.1. Toxicity

Toxicity The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Ecological information on ingredients.

POLYAMINOAMIDE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 7.07 mg/l, Danio rerio (Zebrafish)

Acute toxicity - aquatic invertebrates EC₅₀, 24 hours: 9.72 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 4.34 mg/l, Pseudokirchneriella subcapitata

Acute toxicity - microorganisms EC₅₀, 3 hours: 384 mg/l, Activated sludge

MERCAPTAN-TERMINATED OLIGOMER

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 87 mg/l, Danio rerio (Zebrafish)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 12 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: >733 mg/l, Desmodesmus subspicatus

Acute toxicity - microorganisms EC₅₀, 3 hours: > 1000 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 3.5 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

Permabond ET510B

12.3. Bioaccumulative potential

Partition coefficient Not available.

12.4. Mobility in soil

Mobility No data available. The product has poor water-solubility.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste disposal should be in accordance with existing Community, National and local regulations. Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.

Disposal methods Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Waste class 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances.

SECTION 14: Transport information

Road transport notes Applies only to inner containers >5 litres. See SP 375

Sea transport notes Applies only to inner containers >5 litres. See 2.10.2.7 of the IMDG code.

Air transport notes Applies only to inner containers >5 litres. See SP A197 (375)

14.1. UN number

3082


14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dimer Fatty Acid (C18) Polyaminoamide resin)

14.3. Transport hazard class(es)

9

Transport labels



14.4. Packing group

III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



PermaBond ET510B

14.6. Special precautions for user

EmS F-A, S-F

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	02/09/2021
Revision	6
Supersedes date	15/07/2021
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.