

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® CW 1446 BDF BD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Component used for the manufacture of electrical insulation parts

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40
E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : Centres Antipoison et de Toxicovigilance:
ANGERS: 02 41 48 21 21
BORDEAUX: 05 56 96 40 80
LILLE: 0 825 812 822
LYON: 04 72 11 69 11
MARSEILLE 04 91 75 25 25
NANCY: 03 83 32 36 36
PARIS: 01 40 05 48 48
RENNES: 02 99 59 22 22
STRASBOURG: 03 88 37 37 37
TOULOUSE: 05 61 77 74 47
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	15.08.2019	400001008738	15.11.2018
			Date of first issue: 15.11.2018

Print Date 19.11.2020

Eye irritation, Category 2

H319: Causes serious eye irritation.

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard,
Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

: Warning

Hazard statements

:	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

:	Prevention:	
	P261	Avoid breathing mist or vapours.
	P264	Wash skin thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ eye protection/ face protection.
	Response:	
	P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
	P391	Collect spillage.

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 30 - < 50

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

	01-2119456619-26	Aquatic Chronic 2; H411	
--	------------------	----------------------------	--

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|-------------------------|--|
| General advice | : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur. |
| If inhaled | : If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|--------------------------|
| Treatment | : Treat symptomatically. |
|-----------|--------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|--------------------------------|---|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | : High volume water jet |

5.2 Special hazards arising from the substance or mixture

- | | |
|--------------------------------------|---|
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
|--------------------------------------|---|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

Hazardous combustion products : Carbon oxides
Halogenated compounds
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information.,
For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma,

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version 1.1 Revision Date: 15.08.2019 SDS Number: 400001008738 Date of last issue: 15.11.2018
Date of first issue: 15.11.2018

Print Date 19.11.2020

allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Further information on storage stability : Stable under normal conditions.

Recommended storage temperature : 2 - 40 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Quartz (SiO ₂)	14808-60-7	TWA (Respirable dust)	0,1 mg/m ³	2004/37/EC
Further information	Carcinogens or mutagens			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Dermal	Systemic effects, Short-term exposure	8,33 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Short-term exposure	12,25 mg/m ³
	Workers	Dermal	Systemic effects,	8,33 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version
1.1

Revision Date:
15.08.2019

SDS Number:
400001008738

Date of last issue: 15.11.2018
Date of first issue: 15.11.2018

Print Date 19.11.2020

			Long-term exposure	bw/day
	Workers	Inhalation	Systemic effects, Long-term exposure	12,25 mg/m3
	Consumers	Dermal	Systemic effects, Short-term exposure	3,571 mg/kg bw/day
	Consumers	Oral	Systemic effects, Short-term exposure	0,75 mg/kg bw/day
	Consumers	Dermal	Systemic effects, Long-term exposure	3,571 mg/kg bw/day
	Consumers	Oral	Systemic effects, Long-term exposure	0,75 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0,006 mg/l
Remarks:	Assessment Factors	
	Marine water	0,0006 mg/l
	Assessment Factors	
	Freshwater - intermittent	0,018 mg/l
	Assessment Factors	
	Fresh water sediment	0,996 mg/kg
	Equilibrium method	
	Marine sediment	0,0996 mg/kg
	Equilibrium method	
	Soil	0,196 mg/kg
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Secondary Poisoning	11 mg/kg

8.2 Exposure controls

Engineering measures

effective ventilation in all processing areas

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	15.08.2019	400001008738	15.11.2018
			Date of first issue: 15.11.2018

Print Date 19.11.2020

Break through time	: > 8 h
Material	: Solvent-resistant gloves (butyl-rubber)
Material	: Nitrile rubber
Break through time	: 10 - 480 min
Material	: Neoprene gloves
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	: Wear respiratory protection when its use is identified for certain contributing scenario.
	W A R N I N G ! This product contains quartz, which has been classified by IARC as carcinogenic for humans (Group 1), and which can cause silicosis and lung cancer following exposure to respirable dust. It is therefore important to take particular care to avoid inhalation exposure when mechanically processing cured material (e.g. grinding, sanding, sawing). Workplace exposure limits (for total dust and inhalable quartz dust) must be complied with. If this is not possible, then suitable dust masks must be worn.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: brown
Odour	: slight
Odour Threshold	: No data is available on the product itself.
pH	: ca. 8 (20 °C) Concentration: 500 g/l
Freezing point	: No data is available on the product itself.
Melting point	: No data is available on the product itself.
Boiling point	: > 200 °C
Flash point	: > 200 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

Method: Pensky-Martens closed cup, closed cup

Evaporation rate	: No data is available on the product itself.
Flammability (solid, gas)	: No data is available on the product itself.
Burning rate	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Vapour pressure	: < 0,001 hPa (20 °C)
Relative vapour density	: No data is available on the product itself.
Relative density	: No data is available on the product itself.
Density	: 1,8 g/cm ³ (25 °C)
Solubility(ies)	
Water solubility	: practically insoluble (20 °C)
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.
Auto-ignition temperature	: No data is available on the product itself.
Decomposition temperature	: > 200 °C
Viscosity	
Viscosity, dynamic	: 3 800 - 6 800 mPa.s (50 °C)
Explosive properties	: No data is available on the product itself.
Oxidizing properties	: No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	15.08.2019	400001008738	15.11.2018
			Date of first issue: 15.11.2018

Print Date 19.11.2020

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents

None known.

10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide
carbon monoxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit
Assessment: Mild skin irritant
Method: OECD Test Guideline 404

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Assessment: Mild eye irritant

Method: OECD Test Guideline 405

Result: Irritating to eyes.

Respiratory or skin sensitisation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Exposure routes: Skin

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: Causes sensitisation.

Assessment: No data available

Germ cell mutagenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

: Concentration: 0 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo : Cell type: Germ

Application Route: Oral

Method: OECD Test Guideline 478

Result: negative

Cell type: Somatic

Application Route: Oral

Dose: 0 - 5000 mg/kg

Method: OPPTS 870.5395

Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

Application Route: Oral

Exposure time: 24 month(s)

Dose: 15 mg/kg

Frequency of Treatment: 7 days/week

Method: OECD Test Guideline 453

Result: negative

Species: Mouse, male

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 0.1 mg/kg

Frequency of Treatment: 3 days/week

Method: OECD Test Guideline 453

Result: negative

Species: Rat, female

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 1 mg/kg

Frequency of Treatment: 5 days/week

Method: OECD Test Guideline 453

Result: negative

Carcinogenicity - Assessment : No data available

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility

: Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: >750 milligram per kilogram

General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight

General Toxicity F1: No-observed-effect level: 540 mg/kg body weight

Symptoms: No adverse effects

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic development were detected.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development

: Species: Rabbit, female

Application Route: Dermal

General Toxicity Maternal: No observed adverse effect level: 30 mg/kg body weight

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

Method: Other guidelines
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - : No data available
Assessment

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: Ingestion

Exposure time: 14 WeeksNumber of exposures: 7 d

Method: Subchronic toxicity

Species: Rat, male and female

NOEL: 10 mg/kg

Application Route: Skin contact

Exposure time: 13 WeeksNumber of exposures: 5 d

Method: Subchronic toxicity

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 WeeksNumber of exposures: 3 d

Method: Subchronic toxicity

Repeated dose toxicity - : No data available
Assessment

Aspiration toxicity

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,5 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2,7 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): 9,4 mg/l
plants
Exposure time: 72 h
Test Type: static test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	15.08.2019	400001008738	15.11.2018
			Date of first issue: 15.11.2018

Print Date 19.11.2020

Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among : Koc: 445
environmental compartments

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological : An environmental hazard cannot be excluded in the event of
information : unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

IATA

14.1 UN number : UN 3082
14.2 UN proper shipping : Environmentally hazardous substance, liquid, n.o.s.
name : (BISPHENOL A EPOXY RESIN)

14.3 Transport hazard : 9
class(es)

14.4 Packing group : III

Labels : Class 9 - Miscellaneous dangerous substances and articles

Packing instruction (cargo) : 964

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

aircraft)
Packing instruction : 964
(passenger aircraft)

IMDG

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
EmS Code : F-A, S-F
14.5 Environmental hazards
Marine pollutant : yes

ADR

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
14.5 Environmental hazards
Environmentally hazardous : yes

RID

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
14.5 Environmental hazards
Environmentally hazardous : yes

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation : Not applicable
(Annex XIV)

REACH - List of substances subject to authorisation - : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

Future sunset date

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Occupational Illnesses (R-461-3, France) : 51, 25, 44

Installations classified for the protection of the environment (Environment Code R511-9) : 4511

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOI (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	15.08.2019	400001008738	15.11.2018
			Date of first issue: 15.11.2018

Print Date 19.11.2020

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2004/37/EC / TWA	: Long term exposure limit

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1446 BDF BD

Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2018
1.1	15.08.2019	400001008738	Date of first issue: 15.11.2018

Print Date 19.11.2020

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.