

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue: 17.09.2018
2.0	23.10.2020	400001008186	Date of first issue: 17.09.2018

Print Date 24.10.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® CW 5725 BD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Component used for the manufacture of electrical insulation parts

Recommended restrictions on use : For industrial use only.

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : Centres Antipoison et de Toxicovigilance:
ANGERS: 02 41 48 21 21
BORDEAUX: 05 56 96 40 80
LILLE: 0 825 812 822
LYON: 04 72 11 69 11
MARSEILLE 04 91 75 25 25
NANCY: 03 83 32 36 36
PARIS: 01 40 05 48 48
RENNES: 02 99 59 22 22
STRASBOURG: 03 88 37 37 37
TOULOUSE: 05 61 77 74 47
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	23.10.2020	400001008186	17.09.2018
			Date of first issue: 17.09.2018

Print Date 24.10.2020

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H411	Toxic to aquatic life with long lasting effects.

Precautionary statements	Prevention:	
	P261	Avoid breathing mist or vapours.
	P264	Wash skin thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ eye protection/ face protection.
	Response:	
	P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
	P391	Collect spillage.

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Oxirane, 2-(chloromethyl)-, polymer with alpha-hydro-omega-hydroxypoly[oxy(methyl-1,2-ethanediyl)]

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version 2.0 Revision Date: 23.10.2020 SDS Number: 400001008186 Date of last issue: 17.09.2018
Date of first issue: 17.09.2018

Print Date 24.10.2020

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 30 - < 50
Oxirane, 2-(chloromethyl)-, polymer with alpha-hydro-omega-hydroxypoly[oxy(methyl-1,2-ethanediyl)]	9072-62-2 Polymer	Skin Sens. 1; H317	>= 1 - < 10

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	23.10.2020	400001008186	17.09.2018
			Date of first issue: 17.09.2018

Print Date 24.10.2020

Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Exercise caution when using a high volume water jet as it may scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Halogenated compounds
Carbon monoxide
Carbon dioxide (CO₂)

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue: 17.09.2018
2.0	23.10.2020	400001008186	Date of first issue: 17.09.2018

Print Date 24.10.2020

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 2 - 40 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version 2.0 Revision Date: 23.10.2020 SDS Number: 400001008186 Date of last issue: 17.09.2018
Date of first issue: 17.09.2018

Print Date 24.10.2020

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
calcium carbonate	471-34-1	VME	10 mg/m3	FR VLE
Further information	Indicative exposure limits			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4,93 mg/m3
	Workers	Dermal	Long-term systemic effects	0,75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,87 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,5 mg/kg bw/day
calcium carbonate	Workers	Inhalation	Long-term local effects	6,36 mg/m3
	Consumers	Inhalation	Long-term local effects	1,06 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0,006 mg/l
Remarks:	Assessment Factors	
	Marine water	0,001 mg/l
	Assessment Factors	
	Fresh water sediment	0,341 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version 2.0 Revision Date: 23.10.2020 SDS Number: 400001008186 Date of last issue: 17.09.2018
Date of first issue: 17.09.2018

Print Date 24.10.2020

		weight (d.w.)
	Equilibrium method	
	Marine sediment	0,034 mg/kg dry weight (d.w.)
	Equilibrium method	
	Soil	0,065 mg/kg dry weight (d.w.)
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Secondary Poisoning	11 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 h

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves. The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : **W A R N I N G !** This product contains quartz, which has been classified by IARC as carcinogenic for humans (Group

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	23.10.2020	400001008186	17.09.2018
			Date of first issue: 17.09.2018

Print Date 24.10.2020

1), and which can cause silicosis and lung cancer following exposure to respirable dust. It is therefore important to take particular care to avoid inhalation exposure when mechanically processing cured material (e.g. grinding, sanding, sawing).

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: black
Odour	: slight
Odour Threshold	: No data is available on the product itself.
pH	: No data is available on the product itself.
Melting point/freezing point	: No data available
Boiling point	: > 200 °C
Flash point	: 200 °C Method: Pensky-Martens closed cup
Evaporation rate	: No data is available on the product itself.
Flammability (solid, gas)	: No data is available on the product itself.
Burning rate	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Vapour pressure	: < 0,0001 hPa (20 °C)
Relative vapour density	: No data is available on the product itself.
Relative density	: ca. 1,91 (20 °C)
Density	: ca. 1,91 g/cm ³ (20 °C)
Solubility(ies)	
Water solubility	: practically insoluble (20 °C)
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	23.10.2020	400001008186	17.09.2018
			Date of first issue: 17.09.2018

Print Date 24.10.2020

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C

Viscosity
Viscosity, dynamic : ca. 9 000 mPa.s (25 °C)

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

9.2 Other information

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide
carbon monoxide
Halogenated compounds

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: No mortality observed at this dose.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	23.10.2020	400001008186	17.09.2018
			Date of first issue: 17.09.2018

Print Date 24.10.2020

Oxirane, 2-(chloromethyl)-, polymer with alpha-hydro-omega-hydroxypoly[oxy(methyl-1,2-ethanediyl)]:

Acute oral toxicity : LD50 (Rat): > 2 000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Exposure time: 4 h

Assessment: Irritating to skin.

Method: OECD Test Guideline 404

Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Assessment: Irritating to eyes.

Method: OECD Test Guideline 405

Result: Irritating to eyes.

Oxirane, 2-(chloromethyl)-, polymer with alpha-hydro-omega-hydroxypoly[oxy(methyl-1,2-ethanediyl)]:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitisation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue: 17.09.2018
2.0	23.10.2020	400001008186	Date of first issue: 17.09.2018

Print Date 24.10.2020

Species: Mouse
Method: OECD Test Guideline 429
Result: The product is a skin sensitiser, sub-category 1B.

Oxirane, 2-(chloromethyl)-, polymer with alpha-hydro-omega-hydroxypoly[oxy(methyl-1,2-ethanediyl)]:

Exposure routes: Skin

Result: May cause sensitisation by skin contact.

Assessment: No data available

Germ cell mutagenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Test system: mouse lymphoma cells
Metabolic activation: without metabolic activation
Result: positive

: Test Type: reverse mutation assay
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
Result: negative

Oxirane, 2-(chloromethyl)-, polymer with alpha-hydro-omega-hydroxypoly[oxy(methyl-1,2-ethanediyl)]:

Genotoxicity in vitro : Metabolic activation: Metabolic activation
Method: OECD Test Guideline 471
Result: positive

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo : Test Type: in vivo assay
Test species: Mouse (male)
Cell type: Germ
Application Route: Oral
Dose: 3333, 10000 mg/kg
Result: negative

Test Type: gene mutation test
Test species: Rat (male)
Cell type: Somatic
Application Route: Oral
Dose: 50,250,500,1000 mg/kg bw/day
Method: OECD Test Guideline 488
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	23.10.2020	400001008186	17.09.2018
			Date of first issue: 17.09.2018

Print Date 24.10.2020

Germ cell mutagenicity- : No data available
Assessment

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male

Application Route: Oral

Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment: 7 days/week

No observed adverse effect level: 15 mg/kg bw/day

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Mouse, male

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 0, 0.1, 10, 100 mg/kg bw/day

Frequency of Treatment: 3 days/week

No-observed-effect level: 0.1 mg/kg body weight

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Rat, female

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 0.1, 100, 1000 mg/kg bw/day

Frequency of Treatment: 5 days/week

No-observed-effect level: 100 mg/kg body weight

Method: OECD Test Guideline 453

Result: negative

Species: Rat, female

Application Route: Oral

Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment: 7 days/week

No observed adverse effect level: 100 mg/kg bw/day

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Rat, females

Application Route: Oral

Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment: 7 days/week

No-observed-effect level: 2 mg/kg bw/day

Method: OECD Test Guideline 453

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue: 17.09.2018
2.0	23.10.2020	400001008186	Date of first issue: 17.09.2018

Print Date 24.10.2020

Result: negative
Target Organs: Digestive organs

Carcinogenicity - : No data available
Assessment

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 0, 50, 180, 540 or 750 milligram per kilogram
Duration of Single Treatment: 238 d
Frequency of Treatment: 1 daily
General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight
General Toxicity F1: No-observed-effect level: 750 mg/kg body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
Dose: 0, 30, 100 or 300 milligram per kilogram
Duration of Single Treatment: 28 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level: 30 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: 300 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rabbit, female
Application Route: Oral
Dose: 0, 20, 60 or 180 milligram per kilogram
Duration of Single Treatment: 13 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level: 60 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rat, female

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue: 17.09.2018
2.0	23.10.2020	400001008186	Date of first issue: 17.09.2018

Print Date 24.10.2020

Application Route: Oral
Dose: 0, 60, 180 and 540 milligram per kilogram
Duration of Single Treatment: 10 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level:
180 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: >
540 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - : No data available
Assessment

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: oral (gavage)

Exposure time: 14 WeeksNumber of exposures: 7 d

Dose: 0, 50, 250, 1000 mg/kg/day

Method: OECD Test Guideline 408

Species: Rat, male and female

NOAEL: >= 10 mg/kg

Application Route: Skin contact

Exposure time: 13 WeeksNumber of exposures: 5 d

Dose: 0, 10, 100, 1000 mg/kg/day

Method: OECD Test Guideline 411

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 WeeksNumber of exposures: 3 d

Dose: 0, 1, 10, 100 mg/kg/day

Method: OECD Test Guideline 411

Repeated dose toxicity - : No data available
Assessment

Aspiration toxicity

No data available

Experience with human exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue: 17.09.2018
2.0	23.10.2020	400001008186	Date of first issue: 17.09.2018

Print Date 24.10.2020

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l
aquatic invertebrates : Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 : 11 mg/l
plants : Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

NOEC : 4,2 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	23.10.2020	400001008186	17.09.2018
			Date of first issue: 17.09.2018

Print Date 24.10.2020

Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Ecotoxicology Assessment
Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Oxirane, 2-(chloromethyl)-, polymer with alpha-hydro-omega-hydroxypoly[oxy(methyl-1,2-ethanediyl)]:

Toxicity to fish : LC50 : > 100 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other aquatic invertebrates : EC50 : > 320 mg/l
Exposure time: 24 h
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to microorganisms : EC50 : > 100 mg/l
Exposure time: 3 h
Method: Information given is based on data obtained from similar substances.

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge, non-adapted
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	23.10.2020	400001008186	17.09.2018
			Date of first issue: 17.09.2018

Print Date 24.10.2020

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)

pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among environmental compartments : Koc: 445

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	23.10.2020	400001008186	17.09.2018
			Date of first issue: 17.09.2018

Print Date 24.10.2020

plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

IATA

14.1 UN number	: UN 3082
14.2 UN proper shipping name	: Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es)	: 9
14.4 Packing group	: III
Labels	: Miscellaneous
Packing instruction (cargo aircraft)	: 964
Packing instruction (passenger aircraft)	: 964

IMDG

14.1 UN number	: UN 3082
14.2 UN proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es)	: 9
14.4 Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
14.5 Environmental hazards	
Marine pollutant	: yes

ADR

14.1 UN number	: UN 3082
14.2 UN proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es)	: 9
14.4 Packing group	: III
Labels	: 9
14.5 Environmental hazards	
Environmentally hazardous	: yes

RID

14.1 UN number	: UN 3082
14.2 UN proper shipping	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue: 17.09.2018
2.0	23.10.2020	400001008186	Date of first issue: 17.09.2018

Print Date 24.10.2020

name N.O.S.
(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III
Labels : 9

14.5 Environmental hazards
Environmentally hazardous : yes

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL
HAZARDS

Occupational Illnesses (R-461-3, France) : 51

Installations classified for the protection of the environment (Environment Code R511-9) : 4511

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components listed in the Canadian NDSL.

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	23.10.2020	400001008186	17.09.2018
			Date of first issue: 17.09.2018

Print Date 24.10.2020

KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On or in compliance with the active portion of the TSCA inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
FR VLE	: France. Occupational Exposure Limits (INRS)
FR VLE / VME	: Time Weighted Average

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 5725 BD

Version	Revision Date:	SDS Number:	Date of last issue: 17.09.2018
2.0	23.10.2020	400001008186	Date of first issue: 17.09.2018

Print Date 24.10.2020

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.