

COPPER ANTI-SEIZE FLUID

Product Code: AGC

PRODUCT DESCRIPTION

Electrolube's **Copper Anti-Seize Fluid** is a long lasting and effective material for the protection of metals exposed to aggressive environments. It is ideal for use on threaded metal components, allowing them to be easily loosened even after exposure to high temperatures or corrosive chemical atmospheres. The high copper content ensures good lubrication on heavy, slow-moving applications.

PRODUCT USE

- * Provides anti-seize and anti-corrosion protection
- * Prevents metal/metal friction which causes seizing and lifting
- * Allows assembly and disassembly of metal parts exposed to the elements or to extreme temperatures.
- * For valves, connectors, nuts, bolts & pulleys, especially within naval, mining and petrochemical industries.
- * Highly resistant to water washing, the grease remains effective at high temperatures.
- * Protects the nozzles of automatic and semi-automatic welding units.
- * Effective against weld spatter on treated surfaces, avoiding blistering.

PREPARATION & APPLICATION

- * Shake the aerosol can well before use.
- * Spray the product cold onto the pieces to be treated applying an even film.
- * Do not overspray, one light coat is sufficient.
- * In order to avoid electrolytic reactions, do not use for applications where ammonia is present or in applications with direct contact with a salt atmosphere. Electrolube High Temperature Aluminium Grease (PAM400) is recommended in such circumstances.
- * Contains flammable material. See MSDS for full details.


**TECHNICAL
DATA
SHEET**



**Copyright
Electrolube
2003**

All information is given in good faith but without warranty.

Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



COPPER ANTI-SEIZE FLUID – Page 2

TYPICAL PROPERTIES

Product Type: Copper paste, insoluble in water.
Silicone free
Penetration (Worked) at 25°C: 345 - 375
Working Temperature Range: -25° and + 1000°C

PACKAGING

400ml net aerosol

ORDER CODE

AGC400

TECHNICAL
DATA
SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty.

Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

