

## SWNS

### Neutral pH Aqueous Cleaning Solution

SWNS has been specially formulated to offer highly effective degreasing at a neutral pH, making it suitable for even the most sensitive of surfaces. It is particularly suitable for the removal of excess resin residues during the construction of LCD screens. SWNS also contains a carefully selected corrosion inhibitor making it suitable for sensitive metals.

- Neutral pH; ideal for the removal of excess resin residues during the construction of LCD screens
- Low foaming cleaner; suitable for use in ultrasonic and spray under immersion equipment
- Ready to use product, no dilution required; increases production efficiency
- Non-flammable product, 100% ozone friendly; suitable for use in standard cleaning equipment

<b>Approvals</b>	<b>RoHS Compliant (2015/863/EU):</b>	<b>Yes</b>
<b>Typical Properties</b>	Appearance	Blue Liquid
	Boiling Point (°C)	98
	Flash Point (°C)	None
	Freezing Point (°C)	-5
	Density @ 20°C (g/ml)	1.002
	Conductivity @ 20°C (µS)	1.1-1.5
	pH	7.5-8

<u>Description</u>	<u>Packaging</u>	<u>Order Code</u>	<u>Shelf Life</u>
<u>Safewash Neutral S</u>	25 Litre	SWNS25L	48 Months

### Directions for Use

Suitable for use in ultrasonic or spray under immersion systems; does not require dilution. Ideal for removing excess resin residues during the manufacturing process. Can also be used for removing flux residues; the exact timings for cleaning will be dependent on the type of flux/paste, the reflow profile used, the age of residues, the temperature of the cleaner and the type of equipment used. Prior testing is advised to ensure compatibility of all materials and to refine the application parameters.

Revision 2: Jan 2019

#### Copyright Electrolube 2013

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way,  
Ashby de la Zouch,  
Leicestershire LE65 1JR

T +44 (0)1530 419 600

F +44 (0)1530 416 640

BS EN ISO 9001:2008  
Certificate No. FM 32082