

Data Sheet

FLASHBREAKER® PS1

Pressure sensitive tape with excellent tack

DESCRIPTION

Flashbreaker® PS1 is a high temperature/ high tensile strength polyester film coated with a high tack pressure sensitive silicone adhesive for oven or autoclave cures up to 204°C. The red colour provides high visibility when placed on parts and moulds.

Flashbreaker® pressure sensitive tapes are used for multi-purpose functions in metal bond and composites, such as holding down vacuum bagging materials, thermocouple wires, masking-off, chem-milling protection or in riveting shops. Flashbreaker® tapes remove easily after the cure.

BENEFITS

- Higher tack adhesive holds difficult materials in place more securely, easier, and quicker.
- Flashbreaker® PS1 tapes make removal of resin flash easier, reducing cleaning time.
- Fix position of consumable materials to avoid process errors and improve part quality.

TECHNICAL DATA

Maximum use temperature	204°C
Carrier type	Polyester
Adhesive type	Silicone
Colour	Red
Total thickness	120 µm (0,0047 inch)
Film thickness	25 µm (0,00098 inch)
Adhesive thickness	95 µm (0,0037 inch)
Elongation at break	100 %
Shelf life	18 months from date of shipment when stored in original packaging at 22°C

COMMONLY USED SIZES

Width	Length	Packaging
2,54 cm (1 inch)	66 m (72 yards)	48 rolls per case
5,08 cm (2 inches)	66 m (72 yards)	24 rolls per case

- Broken cases and other widths available on special order.



NOTES

- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated : 2019-05-15

Catalogue position : [Pressure sensitive tapes](#)

As the conditions or methods of use, including storage, are beyond our control, Airtech Europe does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech Europe disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes. This translation is provided for your convenience only. The official language is English and the official law is Luxembourg.