

EAD/EADI Air Duster

Page 1

EAD and EADI are non-flammable products designed for the safe removal of dust and airborne contamination from very delicate or inaccessible areas of electrical and electronic equipment. EAD is the standard version whereas EADI is the invertible version, which is particularly useful for very intricate equipment or items which cannot be moved for cleaning or maintenance.

- Inert, pure compressed gas for dust removal
- Ideal for removing particulates from inaccessible areas on delicate equipment
- Standard (EAD) or invertible (EADI) versions available
- Non-flammable propellant

Typical Properties

Colour	Colourless
Flash Point (°C)	None
Boiling Point (°C)	-26.2
GWP (vs. CO ₂ , 100yr ITH)	< 1

<u>Description</u>	<u>Packaging</u>	<u>Order Code</u>	<u>Shelf Life</u>
<u>Standard Airduster</u>	200ml Aerosol	EAD200D	48 months
	400ml Aerosol	EAD400D	48 months
<u>Invertible Airduster</u>	200ml Aerosol	EADI200D	48 months

Directions for Use

EAD should be used in a vertical position or at an angle of not greater than 60° to the vertical otherwise a freezing effect will result. If it is necessary to tilt the aerosol more than this, use the invertible version, EADI.

Caution: Do not use EAD/EADI for prolonged blasts as the surface of the can will form frost.

Revision 3: Jan 2019