

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® LY 5052

Unique Formula Identifier (UFI) : N30F-50A7-500F-AH4H

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy resin solution

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe) BV

Address : Everslaan 45
3078 Everberg
Belgium

Telephone : +41 61 299 20 41

Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : Centres Antipoison et de Toxicovigilance:

ANGERS: 02 41 48 21 21

BORDEAUX: 05 56 96 40 80

LILLE: 0 825 812 822

LYON: 04 72 11 69 11

MARSEILLE 04 91 75 25 25

NANCY: 03 83 32 36 36

PARIS: 01 40 05 48 48

RENNES: 02 99 59 22 22

STRASBOURG: 03 88 37 37 37

TOULOUSE: 05 61 77 74 47

EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011

China: +86 20 39377888
+86 532 83889090

India: + 91 22 42 87 5333

Australia: 1800 786 152

New Zealand: 0800 767 437

USA: +1 800-424-9300

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

- P261 Avoid breathing mist or vapours.
- P264 Wash skin thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ eye protection/ face protection.

Response:

- P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
- P391 Collect spillage.

Hazardous components which must be listed on the label:

Phenol, polymer with formaldehyde, glycidyl ether
1,4-bis(2,3 epoxypropoxy)butane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	02.12.2023	400001008763	02.02.2023
			Date of first issue: 11.10.2018

Print Date 26.03.2024

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Phenol, polymer with formaldehyde, glycidyl ether	28064-14-4 Polymer	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 50 - < 70
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7 01-2119494060-45	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Acute toxicity estimate Acute dermal toxicity: 1 100 mg/kg	>= 30 - < 50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

- | | | |
|-------------------------|---|--|
| If inhaled | : | Consult a physician after significant exposure.
If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : | If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : | Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : | Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|-------|---|--|
| Risks | : | Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
Harmful if inhaled. |
|-------|---|--|

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|------------------------|
| Treatment | : | Treat symptomatically. |
|-----------|---|------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|--------------------------------|---|--|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | Exercise caution when using a high volume water jet as it may scatter and spread fire |

5.2 Special hazards arising from the substance or mixture

- | | | |
|-------------------------|---|--|
| Specific hazards during | : | Do not allow run-off from fire fighting to enter drains or water |
|-------------------------|---|--|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	02.12.2023	400001008763	02.02.2023
			Date of first issue: 11.10.2018

Print Date 26.03.2024

firefighting

courses.

Hazardous combustion
products

: Carbon dioxide (CO₂)
Carbon monoxide
Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,4-bis(2,3 epoxypoxy)butane	Workers	Inhalation	Long-term systemic effects	4,7 mg/m3
	Workers	Dermal	Long-term systemic effects	6,66 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,16 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version
1.2

Revision Date:
02.12.2023

SDS Number:
400001008763

Date of last issue: 02.02.2023
Date of first issue: 11.10.2018

Print Date 26.03.2024

	Consumers	Dermal	Long-term systemic effects	3,33 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,33 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,4-bis(2,3 epoxypropoxy)butane	Fresh water	0,024 mg/l
	Remarks:Assessment Factors	
	Marine water	0,002 mg/l
	Remarks:Assessment Factors	
	Sewage treatment plant	100 mg/l
	Remarks:Assessment Factors	
	Fresh water sediment	0,084 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Marine sediment	0,008 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Soil	0,003 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Oral	0,028 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 hrs

Material : butyl-rubber
Break through time : > 8 hrs

Material : Neoprene
Break through time : > 10 - < 480 min

Material : Nitrile rubber
Break through time : > 10 - < 480 min

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines
Equipment should conform to EN 143

In the case of vapour formation use a respirator with an approved filter.

Filter type : Particulates type (P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : Clear

Odour : slight

Odour Threshold : No data is available on the product itself.

Melting point/freezing point : No data available

Boiling point : > 200 °C

Flammability (solid, gas) : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Flash point : 140 °C
Method: Pensky-Martens closed cup

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C

pH : ca. 7 (20 °C)
Concentration: 500 g/l

Viscosity
Viscosity, dynamic : 1 000 - 1 500 mPa.s (25 °C)

Solubility(ies)
Water solubility : insoluble (20 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Vapour pressure : < 0,002 hPa (20 °C)

Density : 1,16 - 1,18 g/cm³ (25 °C)

Relative density : 1,16 - 1,18 (25 °C)

Relative vapour density : No data is available on the product itself.

Particle characteristics : No data is available on the product itself.

9.2 Other information

Miscibility with water : immiscible

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids
Strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

Hazardous decomposition products : carbon dioxide
carbon monoxide

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Product:

- | | | |
|---------------------------|---|---|
| Acute oral toxicity | : | Acute toxicity estimate: > 2 000 mg/kg
Method: Calculation method |
| Acute inhalation toxicity | : | Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

Acute toxicity estimate: 4,29 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method |
| Acute dermal toxicity | : | Acute toxicity estimate: > 2 000 mg/kg
Method: Calculation method |

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

- | | | |
|-----------------------|---|--|
| Acute oral toxicity | : | LD50 (Rat, female): > 2 000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity |
| Acute dermal toxicity | : | LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity |

1,4-bis(2,3 epoxypropoxy)butane:

- | | | |
|---------------------------|---|---|
| Acute oral toxicity | : | LD50 (Rat, male and female): 1 163 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Assessment: The component/mixture is moderately toxic after single ingestion. |
| Acute inhalation toxicity | : | LC50 (Rat): > 2,068 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation., The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations. |
| Acute dermal toxicity | : | Acute toxicity estimate: 1 100 mg/kg
Method: Converted acute toxicity point estimate |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

Assessment: The component/mixture is moderately toxic after single contact with skin.

Skin corrosion/irritation

Causes skin irritation.

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Irritating to skin.

1,4-bis(2,3 epoxypoxoxy)butane:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Skin irritation
GLP	: yes

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: Irritating to eyes.

1,4-bis(2,3 epoxypoxoxy)butane:

Species	: Rabbit
Assessment	: Risk of serious damage to eyes.
Method	: OECD Test Guideline 405
GLP	: yes

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Exposure routes	: Skin
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: May cause sensitisation by skin contact.

1,4-bis(2,3 epoxypoxoxy)butane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

Exposure routes : Skin
Species : Guinea pig
Method : OECD Test Guideline 406
Result : May cause sensitisation by skin contact.
GLP : yes

Assessment : Harmful if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Result: positive

Concentration: 0 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Result: positive

Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Result: negative

1,4-bis(2,3 epoxypropoxy)butane:

Genotoxicity in vitro : Test Type: reverse mutation assay
Concentration: 10 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive
GLP: yes
Remarks: Not classified due to data which are conclusive although insufficient for classification.

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster lung cells
Concentration: 1 - 100 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: positive
GLP: yes
Remarks: Not classified due to data which are conclusive although insufficient for classification.

Test Type: In vitro mammalian cell gene mutation test
Test system: Chinese hamster lung cells
Metabolic activation: with and without metabolic activation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

Method: OECD Test Guideline 476
Result: positive
GLP: no
Remarks: Not classified due to data which are conclusive although insufficient for classification.

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse (male)
Cell type: Somatic
Application Route: Oral
Exposure time: 4 d
Dose: 187.5 - 750 mg/kg
Method: OECD Test Guideline 474
Result: negative
GLP: yes

Test Type: unscheduled DNA synthesis assay
Species: Rat
Cell type: Liver cells
Application Route: Oral
Method: OECD Test Guideline 486
Result: negative

Germ cell mutagenicity-Assessment : Weight of evidence does not support classification as a germ cell mutagen., Animal testing did not show any mutagenic effects.

Carcinogenicity

Not classified due to lack of data.

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Species : Rat, male and female
Application Route : Oral
Exposure time : 24 month(s)
Dose : 15 mg/kg
Frequency of Treatment : 7 daily
Method : OECD Test Guideline 453
Result : negative

Species : Mouse, male
Application Route : Dermal
Exposure time : 24 month(s)
Dose : .1 mg/kg
Frequency of Treatment : 3 daily
Method : OECD Test Guideline 453
Result : negative

Species : Rat, female
Application Route : Dermal
Exposure time : 24 month(s)
Dose : 1 mg/kg
Frequency of Treatment : 5 daily
Method : OECD Test Guideline 453

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

Result : negative

Reproductive toxicity

Not classified due to lack of data.

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

1,4-bis(2,3 epoxypropoxy)butane:

Effects on foetal development : Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 0/30/100/300 mg/kg bw/day
Duration of Single Treatment: 17 d
General Toxicity Maternal: NOAEL: 300 mg/kg body weight
Developmental Toxicity: NOAEL: 300 mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Repeated dose toxicity

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

Species : Rat, male and female
NOAEL : 50 mg/kg
Application Route : Ingestion
Exposure time : 14 Weeks
Number of exposures : 7 d
Method : Subchronic toxicity

Species : Rat, male and female
NOEL : 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks
Number of exposures : 5 d
Method : Subchronic toxicity

Species : Mouse, male
NOAEL : 100 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks
Number of exposures : 3 d
Method : Subchronic toxicity

1,4-bis(2,3 epoxypoxo)butane:

Species : Rat, male and female
NOAEL : 200 mg/kg
Application Route : Oral
Exposure time : 28 d
Number of exposures : daily
Dose : 25, 100, 200, 400 mg/kg
Method : Subacute toxicity

Species : Rat, male and female
NOAEL : 263 mg/kg
Application Route : Oral
Exposure time : 90 h
Number of exposures : daily
Dose : 0,30,100,300 mg/kg bw/day
Method : OECD Test Guideline 408
GLP : yes
Remarks : Information given is based on data obtained from similar substances.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,5 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,7 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

EC50 (Daphnia magna (Water flea)): 2,7 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): 9,4 mg/l
plants
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to fish (Chronic : GLP: yes
toxicity)

Toxicity to daphnia and other : NOEC: 0,3 mg/l
aquatic invertebrates
(Chronic toxicity)
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

1,4-bis(2,3 epoxypropoxy)butane:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 24 mg/l
End point: mortality
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 203
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 75 mg/l
End point: Immobilization
Exposure time: 24 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 202
GLP: no

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 160 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes

NOELR (Pseudokirchneriella subcapitata (green algae)): 40 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 209
GLP: no

12.2 Persistence and degradability

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	02.12.2023	400001008763	02.02.2023
			Date of first issue: 11.10.2018

Print Date 26.03.2024

Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

1,4-bis(2,3 epoxypropoxy)butane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 43 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

Test Type: aerobic
Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 38 %
Related to: Dissolved organic carbon (DOC)
Exposure time: 28 d
Method: OECD Test Guideline 301E
GLP: no

12.3 Bioaccumulative potential

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117

1,4-bis(2,3 epoxypropoxy)butane:

Partition coefficient: n-octanol/water : log Pow: -0,269 (25 °C)
pH: 6,7
Method: OECD Test Guideline 117
GLP: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

12.4 Mobility in soil

Components:

Phenol, polymer with formaldehyde, glycidyl ether:

Distribution among : Koc: 445
environmental compartments

1,4-bis(2,3 epoxypropoxy)butane:

Distribution among : Koc: 12,59
environmental compartments Method: OECD Test Guideline 121

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

12.7 Other adverse effects

Product:

Additional ecological : An environmental hazard cannot be excluded in the event of
information unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Dispose of contents and container in accordance with all local, regional, national and international regulations. Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 3082
ADR	:	UN 3082
RID	:	UN 3082
IMDG	:	UN 3082
IATA	:	UN 3082

14.2 UN proper shipping name

ADN	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY PHENOL NOVOLAC RESIN)
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY PHENOL NOVOLAC RESIN)
RID	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY PHENOL NOVOLAC RESIN)
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY PHENOL NOVOLAC RESIN)
IATA	:	Environmentally hazardous substance, liquid, n.o.s. (EPOXY PHENOL NOVOLAC RESIN)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	:	9
ADR	:	9
RID	:	9
IMDG	:	9
IATA	:	9

14.4 Packing group

ADN		
Packing group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9
ADR		
Packing group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9
Tunnel restriction code	:	(-)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

RID

Packing group	: III
Classification Code	: M6
Hazard Identification Number	: 90
Labels	: 9

IMDG

Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft)	: 964
Packing instruction (LQ)	: Y964
Packing group	: III
Labels	: Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft)	: 964
Packing instruction (LQ)	: Y964
Packing group	: III
Labels	: Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous	: yes
---------------------------	-------

ADR

Environmentally hazardous	: yes
---------------------------	-------

RID

Environmentally hazardous	: yes
---------------------------	-------

IMDG

Marine pollutant	: yes
------------------	-------

IATA (Passenger)

Environmentally hazardous	: yes
---------------------------	-------

IATA (Cargo)

Environmentally hazardous	: yes
---------------------------	-------

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: This product does not contain substances of very high concern.
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Number on list 75, 3 If you intend to use this product as tattoo ink, please contact your vendor.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

Occupational Illnesses (R-461-3, France) : 51

Installations classified for the protection of the environment (Environment Code R511-9) : 4511

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AIIC	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

TSCA : All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOIC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

Further information

Classification of the mixture:

Acute Tox. 4	H332
Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® LY 5052

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
1.2	02.12.2023	400001008763	Date of first issue: 11.10.2018

Print Date 26.03.2024

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.