

## Data Sheet

## GS-213-3

Higher temperature version of GS-213

### ■ DESCRIPTION

GS-213-3 is a higher temperature version of GS-213. It has slightly lower tack and excellent clean-up on any surface. It is usable up to 232°C.

### ■ BENEFITS

- Lower tack level, so vacuum bags can be easily repositioned.
- High temperature rating for safer high temperature cures.
- Removes cleanly after cure reducing cost of tool cleaning.

### ■ TECHNICAL DATA

|                         |                                                                              |
|-------------------------|------------------------------------------------------------------------------|
| Colour                  | Light green                                                                  |
| Base material           | Synthetic rubber                                                             |
| Maximum use temperature | 232°C                                                                        |
| Shelf life              | 12 months from date of manufacture                                           |
| Storage conditions      | Tape must be stored flat in original packaging at 22°C<br>Do not refrigerate |

### ■ SIZES

| Dimensions                                              | Packaging         |
|---------------------------------------------------------|-------------------|
| 3 mm x 12 mm x 7,5 m<br>(1/8 inch x 1/2 inch x 25 feet) | 32 rolls per case |
| 3 mm x 19 mm x 7,5 m<br>(1/8 inch x 3/4 inch x 25 feet) | 20 rolls per case |



### ■ NOTES

- For clean removal, it is recommended to strip the tape from the mould surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated : 2015-08-24

Catalogue position : **Vacuum bag sealant tapes**