

Data Sheet

VAC-GAUGE 30

Inexpensive vacuum gauge

■ DESCRIPTION

Vac-Gauge 30 is our durable, inexpensive vacuum gauge to determine how much vacuum is under your vacuum bag. A heavy ridged blue rubber jacket protects the gauge from damage in normal shop use. The Vac-Gauge 30 stem is a 1/4 inch male NPT fitting that fits easily into our Airlock 450TF & 550TF and AQD quick disconnects.

Note: Vac-Gauge 30 is an inexpensive reference gauge for shop use only.

■ BENEFITS

- Simple gauge provides indication of vacuum level and highlights any leaks present.
- Portable gauge can be transported easily around the workshop.
- Rubber jacket protects against bumps and knocks to keep gauge working.

■ TECHNICAL DATA

Screw thread	1/4 inch male NPT
Assembly style	Screwed
Range	0 - (-1) bar
Graduations	-0,02 bar
Accuracy	+/-2.5 %
Figure interval	-0,2 bar



■ DIRECTIONS FOR USE

Vacuum drop / Vacuum leak check:

- Attach Vac-Gauge 30 to through bag connector and attach vacuum source.
- Allow vacuum source to draw out air and apply increasing vacuum force, this will be indicated on the Vac-Gauge 30.
- Check and fix potential leakage areas until a stable and satisfactory reading is shown on the gauge.
- Disconnect vacuum source and monitor vacuum reading over period of time. Any drop in vacuum reading highlights a leakage.

Last updated : 2015-10-07

Catalogue position : [Vacuum valves and hoses](#)