

SAMARO SAMPLAST

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 15/12/2014 Revision date: 27/06/2022 Supersedes version of: 27/04/2021 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : SAMARO SAMPLAST
Product code : 700782 EXG
Product identification : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use
Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Mold release agent, lubricant

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Fabricant

SAMARO
Allée des petites Combes – ZI NORD
01700 BEYNSOT
FRANCE
T 04 26 680 680
info@samaro.fr - www.samaro.fr

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229
STOT SE 3 H336
Aquatic Chronic 2 H411
Full text of hazard classes, H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: Hydrocarbons, C6, isoalkanes, <5% n-hexane

SAMARO SAMPLAST

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe spray. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.
Extra phrases	: For professional use only. Not to be used for any purpose other than the one the product was designed for.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C6, isoalkanes, <5% n-hexane	EC-No.: 931-254-9 REACH-no: 01-2119484651-34	≥ 90	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Carbon dioxide (Propellant gas (Aerosol))	CAS-No.: 124-38-9 EC-No.: 204-696-9 REACH-no: exempté d'enregistrement	2 – 5	Press. Gas (Comp.), H280

Comments : Calculation of aerosol labeling excluding gas
Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.
Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest. Obtain medical attention if breathing difficulty persists.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Wash with plenty of water/.... Seek medical attention if ill effect or irritation develops.
First-aid measures after eye contact	: In case of eye contact, immediately rinse with clean water for 10-15 minutes. Consult an eye specialist immediately.

SAMARO SAMPLAST

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Allow the victim to rest.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Vapours may cause drowsiness and dizziness. Inhalation of vapours may cause respiratory irritation.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Stinging and temporary redness.

Symptoms/effects after ingestion : Ingestion unlikely.

4.3. Indication of any immediate medical attention and special treatment needed

Advice to physicians: Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : All extinguishing agents can be used.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Reactivity in case of fire : Prevent fire fighting water from entering the environment.

Hazardous decomposition products in case of fire : Incomplete combustion and thermolysis produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

5.3. Advice for firefighters

Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.

Firefighting instructions : During a fire, projections ignited aerosol that burst under excessive pressure have to be controlled. To avoid overpressure, cool aerosols with water. Exercise caution when fighting any chemical fire. Evacuate area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Measures to take in the case of crushing or piercing aerosols, causing the leaking of products contained in aerosols. Ventilate area. Do not smoke. Remove ignition sources. Provide local exhaust or general room ventilation. Evacuate and limit access.

6.1.1. For non-emergency personnel

Emergency procedures : Do not touch spilled material. Evacuate area.

6.1.2. For emergency responders

Protective equipment : Wear recommended personal protective equipment. Provide adequate ventilation. Remove all sources of ignition. Avoid contact with skin and eyes. Do not inhale vapour.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Collect the residue by means of a non-combustible absorbent material.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

SAMARO SAMPLAST

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Good ventilation of the workplace required. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Not to be used for any purpose other than the one the product was designed for. Do not breathe gas, fumes, vapour or spray. During the handling of a pallet, you have to take all precaution to avoid a start of a n accident perforation of the aerosol by a fork-lift truck.
During the load and unloading of the vehicle, you have to take all the precaution to avoid a fall a aerosol.
Do not spray tha aerosol neither close nor towards a flame, a white-hot body, an electrical appliance in runing, DO NOT SMOCKING. Container under pressure. Do not drill or burn even after use. Store and handle as though always a serious potential fire/explosion and health hazard exists.

Hygiene measures

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Keep at temperature not exceeding 50°C. Proper grounding procedures to avoid static electricity should be followed. Use grounded electrical/mechanical equipment.

Storage conditions

: Recommendations applicable to warehouses and reserves which are stored aerosols. It is recommended to de-normalize aerosols in stock . The " aerosol " or area must be set with a wire mesh of mesh max 5cm, forming a cage or using walls to avoid splashing the aerosols may ignite rest of the stock . Do not smoke.

To reduce the risk of falling, should position the pallet closest to the ground. If the packages are stacked, it should ensure that those lower layers do not crash (risk of leakage through compression).

It is recommended :

- Ventilate the premises and not store any sprays near heat sources, including sunlight, sparks and open flames
- To use the procedure of fire when working . Store in a dry, well ventilated place .

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Carbon dioxide (124-38-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Carbon dioxide
IOEL TWA	9000 mg/m³
IOEL TWA [ppm]	5000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

SAMARO SAMPLAST

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

8.2.2.2. Skin protection

Skin and body protection:

Skin protection appropriate to the conditions of use should be provided

Hand protection:

Use neoprene or rubber gloves EN 374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Since the product represents a preparation composed of several substances, the resistance of the glove materials cannot be calculated in advance and must be checked before use. The exact breakthrough time of the glove material has to be determined by the manufacturer of the protective gloves and has to be observed

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment Type AX

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Do not eat, drink or smoke during use. Provide local exhaust or general room ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: < 0 °C (PA)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: Not available
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: Not available

SAMARO SAMPLAST

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Relative vapour density at 20 °C : Not available
Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 93

9.2.2. Other safety characteristics

VOC content : 93 % (634 g/l)

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

The product is stable at normal handling and storage conditions. Extremely flammable aerosol. Heating may cause a fire or explosion.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

Open flame. Heat. Direct sunlight. Sparks. Avoid the build-up of electrostatic charge. Avoid contact with hot surfaces. Remove all sources of ignition.

10.5. Incompatible materials

Strong oxidizers. Aerosol cases in metal, do not bring into contact with oxidize, acids or basis.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soo.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Hydrocarbons, C6, isoalkanes, <5% n-hexane	
LD50 oral rat	> 16750 mg/kg
LD50 dermal rabbit	> 3350 mg/kg
LC50 Inhalation - Rat	259354 mg/l/4h

Skin corrosion/irritation : Not classified
pH: Not applicable
Additional information : Based on available data, the classification criteria are not met
Serious eye damage/irritation : Not classified
pH: Not applicable
Additional information : Based on available data, the classification criteria are not met
Respiratory or skin sensitisation : Not classified
Additional information : Based on available data, the classification criteria are not met
Germ cell mutagenicity : Not classified
Additional information : Based on available data, the classification criteria are not met
Carcinogenicity : Not classified

SAMARO SAMPLAST

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: May cause drowsiness or dizziness.
Additional information	: Based on available data, the classification criteria are not met

Hydrocarbons, C6, isoalkanes, <5% n-hexane

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met

SAMARO SAMPLAST

Product identification	Aerosol
------------------------	---------

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

11.2.2. Other information

Potential adverse human health effects and symptoms	: Eye contact :Stinging and temporary redness,Repeated exposure may cause skin dryness or cracking,May be irritating to the mucous membranes and to the respiratory system,Nausea
---	---

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Avoid release to the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Hydrocarbons, C6, isoalkanes, <5% n-hexane

LC50 - Fish [1]	18,27 mg/l
EC50 - Crustacea [1]	31,9 mg/l
EC50 72h - Algae [1]	13,56 mg/l

12.2. Persistence and degradability

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Persistence and degradability	Readily biodegradable.
Biodegradation	98 %

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

SAMARO SAMPLAST

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.7. Other adverse effects

Additional information : No other effects known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose used or damaged aerosol cans at permitted disposal sites. Dispose in a safe manner in accordance with local/national regulations. hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Ecology - waste materials : Avoid release to the environment.

HP Code : HP3 - "Flammable:"

- flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
- flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
- flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
- flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

SAMARO SAMPLAST

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations : Aerosol Generator Directive 75/324/EEC and its adaptations.

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(a)	SAMARO SAMPLAST ; Hydrocarbons, C6, isoalkanes, <5% n-hexane
3(b)	SAMARO SAMPLAST ; Hydrocarbons, C6, isoalkanes, <5% n-hexane
3(c)	SAMARO SAMPLAST ; Hydrocarbons, C6, isoalkanes, <5% n-hexane
40.	Hydrocarbons, C6, isoalkanes, <5% n-hexane

REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

SAMARO SAMPLAST

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

VOC Directive (2004/42)

VOC content : 93 % (634 g/l)

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
3	Composition/information on ingredients	Modified	
15.1	REACH Annex XVII	Added	

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : Imp. DL4.

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Flam. Liq. 2	Flammable liquids, Category 2
H222	Extremely flammable aerosol.

SAMARO SAMPLAST

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.