

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : RENLAM® LY 5210 CH

Unique Formula Identifier (UFI) : K5ME-T0D1-K00P-C24J

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy resin solution

Recommended restrictions on use : For industrial use only.

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe) BV
Address : Grijpenlaan 18
3300 Tienen
Belgium

Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone

Emergency telephone : Centres Antipoison et de Toxicovigilance:
ANGERS: 02 41 48 21 21
BORDEAUX: 05 56 96 40 80
LILLE: 0 825 812 822
LYON: 04 72 11 69 11
MARSEILLE 04 91 75 25 25
NANCY: 03 83 32 36 36
PARIS: 01 40 05 48 48
RENNES: 02 99 59 22 22
STRASBOURG: 03 88 37 37 37
TOULOUSE: 05 61 77 74 47
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1 800-424-9300

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	24.10.2024	400001010114	06.07.2023
			Date of first issue: 01.08.2018

Print Date 25.10.2024

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Germ cell mutagenicity, Category 2	H341: Suspected of causing genetic defects.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:													
Signal Word	:	Danger												
Hazard Statements	:	<table><tbody><tr><td>H315</td><td>Causes skin irritation.</td></tr><tr><td>H317</td><td>May cause an allergic skin reaction.</td></tr><tr><td>H318</td><td>Causes serious eye damage.</td></tr><tr><td>H341</td><td>Suspected of causing genetic defects.</td></tr><tr><td>H411</td><td>Toxic to aquatic life with long lasting effects.</td></tr></tbody></table>	H315	Causes skin irritation.	H317	May cause an allergic skin reaction.	H318	Causes serious eye damage.	H341	Suspected of causing genetic defects.	H411	Toxic to aquatic life with long lasting effects.		
H315	Causes skin irritation.													
H317	May cause an allergic skin reaction.													
H318	Causes serious eye damage.													
H341	Suspected of causing genetic defects.													
H411	Toxic to aquatic life with long lasting effects.													
Precautionary Statements	:	Prevention: <table><tbody><tr><td>P201</td><td>Obtain special instructions before use.</td></tr><tr><td>P261</td><td>Avoid breathing mist or vapors.</td></tr><tr><td>P273</td><td>Avoid release to the environment.</td></tr><tr><td>P280</td><td>Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.</td></tr></tbody></table> Response: <table><tbody><tr><td>P305 + P351 + P338 + P310</td><td>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.</td></tr><tr><td>P391</td><td>Collect spillage.</td></tr></tbody></table>	P201	Obtain special instructions before use.	P261	Avoid breathing mist or vapors.	P273	Avoid release to the environment.	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.	P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.	P391	Collect spillage.
P201	Obtain special instructions before use.													
P261	Avoid breathing mist or vapors.													
P273	Avoid release to the environment.													
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.													
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.													
P391	Collect spillage.													

Hazardous ingredients which must be listed on the label:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]
1,4-bis(2,3 epoxypropoxy)butane

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version 2.0 Revision Date: 24.10.2024 SDS Number: 400001010114 Date of last issue: 06.07.2023
Date of first issue: 01.08.2018

Print Date 25.10.2024

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	28768-32-3 249-204-3 01-2119472303-45	Skin Sens. 1; H317 Muta. 2; H341 Aquatic Chronic 2; H411	>= 70 - < 90
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7 01-2119494060-45	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Acute toxicity estimate Acute dermal toxicity: 1 100 mg/kg	>= 20 - < 25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	24.10.2024	400001010114	06.07.2023
			Date of first issue: 01.08.2018

Print Date 25.10.2024

and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

- | | |
|-------------------------|--|
| If inhaled | : Consult a physician after significant exposure.
If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|-------|--|
| Risks | : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
Suspected of causing genetic defects. |
|-------|--|

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|--------------------------|
| Treatment | : Treat symptomatically. |
|-----------|--------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|------------------------------|--|
| Suitable extinguishing media | : Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing | : Exercise caution when using a high volume water jet as it may |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

media

scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

and/or dermatitis and sensitization of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Keep in properly labeled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Further information on storage stability : Stable under normal conditions.

Recommended storage temperature : 2 - 8 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
4,4'-	Workers	Inhalation	Long-term systemic	3,5 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version
2.0

Revision Date:
24.10.2024

SDS Number:
400001010114

Date of last issue: 06.07.2023
Date of first issue: 01.08.2018

Print Date 25.10.2024

methylenebis[N,N-bis(2,3-epoxypropyl)aniline]			effects	
	Workers	Dermal	Long-term systemic effects	0,5 mg/kg bw/day
1,4-bis(2,3 epoxypropoxy)butane	Workers	Inhalation	Long-term systemic effects	4,7 mg/m3
	Workers	Dermal	Long-term systemic effects	6,66 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,16 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,33 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,33 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	Fresh water	0,005 mg/l
	Remarks:Assessment Factors	
	Sea water	0,0005 mg/l
	Remarks:Assessment Factors	
	Freshwater - intermittent	0,047 mg/l
	Remarks:Assessment Factors	
	Sewage treatment plant	1000 mg/l
	Remarks:Assessment Factors	
	Fresh water sediment	0,017 mg/kg
	Remarks:Equilibrium method	
	Sea sediment	0,002 mg/kg
	Remarks:Equilibrium method	
	Soil	0,011 mg/kg
	Remarks:Equilibrium method	
1,4-bis(2,3 epoxypropoxy)butane	Fresh water	0,024 mg/l
	Remarks:Assessment Factors	
	Sea water	0,002 mg/l
	Remarks:Assessment Factors	
	Sewage treatment plant	100 mg/l
	Remarks:Assessment Factors	
	Fresh water sediment	0,084 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Sea sediment	0,008 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Soil	0,003 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Oral	0,028 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 h

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines
Equipment should conform to EN 14387

Filter type : Combined particulates, organic gas and low boiling vapor type (AX-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : yellow

Odor : slight

Odor Threshold : No data is available on the product itself.

Melting point/freezing point : No data is available on the product itself.

Boiling point : > 200 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

Flammability (solid, gas)	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Flash point	: 170 °C Method: Pensky-Martens closed cup
Autoignition temperature	: No data is available on the product itself.
Decomposition temperature	: > 200 °C
pH	: 6 (20 °C) Concentration: 500 g/l
Viscosity	
Viscosity, dynamic	: 2 300 - 3 300 mPa.s (25 °C)
Solubility(ies)	
Water solubility	: practically insoluble (20 °C)
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.
Vapor pressure	: < 0,002 hPa (20 °C)
Density	: 1,17 g/cm ³ (25 °C)
Relative density	: 1,17 (25 °C)
Relative vapor density	: No data is available on the product itself.
Particle characteristics	: No data is available on the product itself.

9.2 Other information

No data is available on the product itself.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids
Strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2 000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2 000 mg/kg
Method: Calculation method

Components:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]:

Acute oral toxicity : LD50 (Rat, male and female): > 5 000 mg/kg
Method: OECD Test Guideline 401
GLP: no
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC50 (Rat, male and female): > 30 mg/m3
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit, male and female): > 3 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

1,4-bis(2,3 epoxypoxy)butane:

Acute oral toxicity : LD50 (Rat, male and female): 1 163 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): > 2,068 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Test atmosphere: dust/mist
Method: Expert judgment
Assessment: The component/mixture is moderately toxic after short term inhalation., The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

Acute dermal toxicity : Acute toxicity estimate: 1 100 mg/kg
Method: Converted acute toxicity point estimate

Assessment: The component/mixture is moderately toxic after single contact with skin.

Skin corrosion/irritation

Causes skin irritation.

Components:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation

1,4-bis(2,3 epoxypoxy)butane:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
GLP : yes

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

1,4-bis(2,3 epoxypropoxy)butane:

Species	:	Rabbit
Assessment	:	Risk of serious damage to eyes.
Method	:	OECD Test Guideline 405
GLP	:	yes

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]:

Test Type	:	Local lymph node assay (LLNA)
Exposure routes	:	Skin
Species	:	Mouse
Assessment	:	May cause sensitisation by skin contact.
Method	:	OECD Test Guideline 429
Result	:	May cause sensitisation by skin contact.

1,4-bis(2,3 epoxypropoxy)butane:

Exposure routes	:	Skin
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	May cause sensitisation by skin contact.
GLP	:	yes

Assessment	:	Harmful if inhaled.
------------	---	---------------------

Germ cell mutagenicity

Suspected of causing genetic defects.

Components:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]:

Genotoxicity in vitro	:	Test Type: reverse mutation assay Test system: Salmonella tryphimurium and E. coli Concentration: 500 µg/plate Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: positive
	:	Test Type: gene mutation test Test system: mouse lymphoma cells Metabolic activation: with and without metabolic activation Result: positive Remarks: Information given is based on data obtained from similar substances.

Genotoxicity in vivo	:	Test Type: Transgenic rodent germ cell gene mutation assay
----------------------	---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	24.10.2024	400001010114	06.07.2023
			Date of first issue: 01.08.2018

Print Date 25.10.2024

Species: Rat (male)
Cell type: Germ
Application Route: Oral
Dose: 10/100/300/1000 mg/kg bw/day
Method: OECD Test Guideline 488
Result: positive
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Test Type: In vivo mammalian alkaline comet assay
Species: Rat (male)
Cell type: Somatic
Dose: 500/1000/2000 mg/kg bw /day
Method: OECD Test Guideline 489
Result: positive
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Test Type: In vivo micronucleus test
Species: Mouse (male)
Cell type: Bone marrow
Application Route: Oral
Dose: 0, 50, 1000, 2000 mg/kg
Method: OECD Test Guideline 474
Result: negative
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Cell type: Germ
Application Route: Oral
Exposure time: 5 d
Method: OECD Test Guideline 483
Result: negative
GLP: yes

Germ cell mutagenicity-
Assessment : Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.

1,4-bis(2,3 epoxypropoxy)butane:

Genotoxicity in vitro : Test Type: reverse mutation assay
Concentration: 10 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive
GLP: yes
Remarks: Not classified due to data which are conclusive although insufficient for classification.

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster lung cells
Concentration: 1 - 100 µg/L

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	24.10.2024	400001010114	06.07.2023
			Date of first issue: 01.08.2018

Print Date 25.10.2024

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: positive
GLP: yes
Remarks: Not classified due to data which are conclusive although insufficient for classification.

Test Type: In vitro mammalian cell gene mutation test
Test system: Chinese hamster lung cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive
GLP: no
Remarks: Not classified due to data which are conclusive although insufficient for classification.

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse (male)
Cell type: Somatic
Application Route: Oral
Exposure time: 4 d
Dose: 187.5 - 750 mg/kg
Method: OECD Test Guideline 474
Result: negative
GLP: yes

Test Type: unscheduled DNA synthesis assay
Species: Rat
Cell type: Liver cells
Application Route: Oral
Method: OECD Test Guideline 486
Result: negative

Germ cell mutagenicity-Assessment : Weight of evidence does not support classification as a germ cell mutagen., Animal testing did not show any mutagenic effects.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

Components:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]:

Effects on fetal development : Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 30, 90 and 270 mg/kg/day
Duration of Single Treatment: 15 d
General Toxicity Maternal: NOAEL: 90 mg/kg body weight
Developmental Toxicity: NOAEL: 90 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	24.10.2024	400001010114	06.07.2023
			Date of first issue: 01.08.2018

Print Date 25.10.2024

GLP: yes

1,4-bis(2,3 epoxypropoxy)butane:

Effects on fetal development : Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 0/30/100/300 mg/kg bw/day
Duration of Single Treatment: 17 d
General Toxicity Maternal: NOAEL: 300 mg/kg body weight
Developmental Toxicity: NOAEL: 300 mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Repeated dose toxicity

Components:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]:

Species : Rat, male and female
NOAEL : 50 mg/kg
Application Route : Oral
Exposure time : 13 Weeks
Number of exposures : 7 d
Dose : 10, 50 and 200 mg/kg/day
Method : OECD Test Guideline 408
GLP : yes

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rat, male and female
NOAEL : 200 mg/kg
Application Route : Oral
Exposure time : 28 d
Number of exposures : daily
Dose : 25, 100, 200, 400 mg/kg
Method : Subacute toxicity

Species : Rat, male and female
NOAEL : 263 mg/kg
Application Route : Oral
Exposure time : 90 h
Number of exposures : daily
Dose : 0,30,100,300 mg/kg bw/day
Method : OECD Test Guideline 408
GLP : yes
Remarks : Information given is based on data obtained from similar substances.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

Repeated dose toxicity - Assessment : Harmful if inhaled.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 5,95 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203
GLP: no
Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): ca. 6,7 mg/l
Exposure time: 48 h
Test Type: semi-static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 0,19 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes

EC50 (*Pseudokirchneriella subcapitata* (green algae)): ca. 4,8 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : IC50 (*Pseudomonas putida*): > 10 000 mg/l
Exposure time: 24 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: DIN 38 412 Part 8
GLP: no
Remarks: Information given is based on data obtained from similar substances.

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

1,4-bis(2,3 epoxypropoxy)butane:

Toxicity to fish : LC50 (*Brachydanio rerio* (zebrafish)): 24 mg/l
End point: mortality
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 203
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 75 mg/l
End point: Immobilization
Exposure time: 24 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 202
GLP: no

Toxicity to algae/aquatic plants : EL50 (*Pseudokirchneriella subcapitata* (green algae)): > 160 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

GLP: yes

NOELR (Pseudokirchneriella subcapitata (green algae)): 40 mg/l

Exposure time: 72 h

Test Type: static test

Analytical monitoring: yes

Test substance: Fresh water

Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h

Test Type: static test

Analytical monitoring: no

Test substance: Fresh water

Method: OECD Test Guideline 209

GLP: no

12.2 Persistence and degradability

Components:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge, non-adapted
Concentration: 20 mg/l
Result: Biodegradable, but failing 10-d window
Biodegradation: ca. 48 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

1,4-bis(2,3 epoxypropoxy)butane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 43 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

Test Type: aerobic
Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 38 %
Related to: Dissolved organic carbon (DOC)
Exposure time: 28 d
Method: OECD Test Guideline 301E
GLP: no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

12.3 Bioaccumulative potential

Components:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]:

Partition coefficient: n-octanol/water : log Pow: ca. 2,12 (22 °C)
pH: 6,7
Method: OECD Test Guideline 107
GLP: yes

1,4-bis(2,3 epoxypropoxy)butane:

Partition coefficient: n-octanol/water : log Pow: -0,269 (25 °C)
pH: 6,7
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

Components:

4,4'-methylenebis[N,N-bis(2,3-epoxypropyl)aniline]:

Distribution among environmental compartments : Koc: < 18
Method: OECD Test Guideline 121

1,4-bis(2,3 epoxypropoxy)butane:

Distribution among environmental compartments : Koc: 12,59
Method: OECD Test Guideline 121

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | |
|------------------------|---|
| Product | : Dispose of contents and container in accordance with all local, regional, national and international regulations.
Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container. |
| Contaminated packaging | : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers. |

SECTION 14: Transport information

14.1 UN number or ID number

- | | |
|------|-----------|
| ADN | : UN 3082 |
| ADR | : UN 3082 |
| RID | : UN 3082 |
| IMDG | : UN 3082 |
| IATA | : UN 3082 |

14.2 UN proper shipping name

- | | |
|------|---|
| ADN | : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(TETRAGLYCIDYL METHYLENEDIANILINE) |
| ADR | : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(TETRAGLYCIDYL METHYLENEDIANILINE) |
| RID | : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(TETRAGLYCIDYL METHYLENEDIANILINE) |
| IMDG | : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(TETRAGLYCIDYL METHYLENEDIANILINE) |
| IATA | : Environmentally hazardous substance, liquid, n.o.s.
(TETRAGLYCIDYL METHYLENEDIANILINE) |

14.3 Transport hazard class(es)

- | | Class | Subsidiary risks |
|------|-------|------------------|
| ADN | : 9 | |
| ADR | : 9 | |
| RID | : 9 | |
| IMDG | : 9 | |
| IATA | : 9 | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

14.4 Packing group

ADN

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product does not contain substances of very high concern.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

Occupational Illnesses (R-461-3, France) : 51

Installations classified for the protection of the environment (Environment Code R511-9) : 4511

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	24.10.2024	400001010114	06.07.2023
			Date of first issue: 01.08.2018

Print Date 25.10.2024

AIIC	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: Not in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical Safety Assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H332	: Harmful if inhaled.
H341	: Suspected of causing genetic defects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Muta.	: Germ cell mutagenicity
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

RENLAM® LY 5210 CH

Version	Revision Date:	SDS Number:	Date of last issue: 06.07.2023
2.0	24.10.2024	400001010114	Date of first issue: 01.08.2018

Print Date 25.10.2024

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Muta. 2	H341
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.