

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® 420 A

Unique Formula Identifier (UFI) : TGGS-E08S-0002-CAP1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy constituents

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe) BV

Address : Grijpenlaan 18
3300 Tienen
Belgium

Telephone : +41 61 299 20 41

Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone

Emergency telephone : Centres Antipoison et de Toxicovigilance:

ANGERS: 02 41 48 21 21

BORDEAUX: 05 56 96 40 80

LILLE: 0 825 812 822

LYON: 04 72 11 69 11

MARSEILLE 04 91 75 25 25

NANCY: 03 83 32 36 36

PARIS: 01 40 05 48 48

RENNES: 02 99 59 22 22

STRASBOURG: 03 88 37 37 37

TOULOUSE: 05 61 77 74 47

EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011

China: +86 20 39377888

+86 532 83889090

India: + 91 22 42 87 5333

Australia: 1800 786 152

New Zealand: 0800 767 437

USA: +1 800-424-9300

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Warning

Hazard Statements	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**

P261	Avoid breathing mist or vapors.
P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P391	Collect spillage.

Hazardous ingredients which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version 1.3 Revision Date: 31.03.2026 SDS Number: 400001009537 Date of last issue: 05.08.2022
Date of first issue: 20.05.2015

Print Date 24.06.2026

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 ≥ 5 % Skin Irrit. 2; H315 ≥ 5 %	≥ 90 - ≤ 100
[3-(2,3-epoxypropoxy)propyl]trimethoxy silane	2530-83-8 219-784-2 01-2119513212-58	Eye Dam. 1; H318 Aquatic Chronic 3; H412	≥ 1 - < 2,5

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Exercise caution when using a high volume water jet as it may scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Phenolics

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
Do not breathe vapors or spray mist.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labeled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

Recommended storage temperature : 18 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4,93 mg/m3
	Workers	Dermal	Long-term systemic effects	0,75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,87 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,0893 mg/kg bw/day
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Consumers	Oral	Long-term systemic effects	0,5 mg/kg bw/day
	Workers	Dermal	Systemic effects, Long-term exposure	21 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Long-term exposure	147 mg/m3
	Consumers	Oral	Systemic effects, Long-term exposure	12,5 mg/kg bw/day
	Consumers	Inhalation	Systemic effects, Long-term exposure	43,5 mg/kg bw/day
	Consumers	Dermal	Systemic effects, Long-term exposure	12,5 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0,006 mg/l
	Sea water	0,001 mg/l
	Fresh water sediment	0,341 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version 1.3 Revision Date: 31.03.2026 SDS Number: 400001009537 Date of last issue: 05.08.2022
Date of first issue: 20.05.2015

Print Date 24.06.2026

		weight (d.w.)
	Sea sediment	0,034 mg/kg dry weight (d.w.)
	Soil	0,065 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Secondary Poisoning	11 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Fresh water	1 mg/l
	Sea water	0,1 mg/l
	Freshwater - intermittent	1 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	3,6 mg/kg
	Sea sediment	0,36 mg/kg
	Soil	0,14 mg/kg

8.2 Exposure controls

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 h

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines
Equipment should conform to EN 14387

Filter type : Combined particulates, inorganic and acidic gas/vapor, ammonia/amines and organic vapor type (ABEK-P)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Form	: paste
Color	: yellow
Odor	: slight
Odor Threshold	: No data is available on the product itself.
Melting point/freezing point	: No data is available on the product itself.
Boiling point	: No data is available on the product itself.
Flammability	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Flash point	: > 100 °C Method: Pensky-Martens closed cup
Autoignition temperature	: No data is available on the product itself.
Decomposition temperature	: > 200 °C
pH	: substance/mixture is non-soluble (in water)
Viscosity	
Viscosity, dynamic	: 100 000 - 300 000 mPa.s (25 °C)
Solubility(ies)	
Water solubility	: practically insoluble (20 °C)
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.
Vapor pressure	: No data is available on the product itself.
Density	: 1,2 g/cm ³ (25 °C)
Relative density	: No data is available on the product itself.
Relative vapor density	: No data is available on the product itself.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

Particle characteristics : No data is available on the product itself.

9.2 Other information

No data is available on the product itself.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids
Strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity	: LD50 (Rat, female): > 2 000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	: LD50 (Rat, male and female): > 2 000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Acute oral toxicity	: LD50 (Rat, male and female): 8 025 mg/kg Method: OECD Test Guideline 401 Assessment: The substance or mixture has no acute oral
---------------------	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

toxicity

Acute inhalation toxicity : LC50 (Rat, male and female): > 5,3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit, male): 4 250 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	: Rabbit
Exposure time	: 4 h
Assessment	: Irritating to skin.
Method	: OECD Test Guideline 404
Result	: Irritating to skin.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	: Rabbit
Assessment	: Irritating to eyes.
Method	: OECD Test Guideline 405
Result	: Irritating to eyes.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Species	: Rabbit
Assessment	: Severe eye irritation
Method	: OECD Test Guideline 405
Result	: Risk of serious damage to eyes.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: The product is a skin sensitiser, sub-category 1B.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Exposure routes	: Skin
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Test system: mouse lymphoma cells Metabolic activation: without metabolic activation Result: positive Test Type: reverse mutation assay Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay) Result: negative
Genotoxicity in vivo	: Test Type: in vivo assay Species: Mouse (male) Cell type: Germ Application Route: Oral Dose: 3333, 10000 mg/kg Result: negative Test Type: gene mutation test Species: Rat (male) Cell type: Somatic Application Route: Oral Dose: 50,250,500,1000 mg/kg bw/day Method: OECD Test Guideline 488 Result: negative

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Genotoxicity in vitro	: Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: positive Metabolic activation: with and without metabolic activation
-----------------------	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

Method: OECD Test Guideline 471

Result: positive

Genotoxicity in vivo : Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: positive

Application Route: Intraperitoneal injection

Dose: 1600 mg/kg

Result: negative

Application Route: Oral

Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male
Application Route : Oral
Exposure time : 24 month(s)
Dose : 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment : 7 days/week
NOAEL : 15 mg/kg bw/day
Method : OECD Test Guideline 453
Result : negative
Target Organs : Digestive organs

Species : Mouse, male
Application Route : Dermal
Exposure time : 24 month(s)
Dose : 0, 0.1, 10, 100 mg/kg bw/day
Frequency of Treatment : 3 days/week
NOEL : 0,1 mg/kg body weight
Method : OECD Test Guideline 453
Result : negative
Target Organs : Digestive organs

Species : Rat, female
Application Route : Dermal
Exposure time : 24 month(s)
Dose : 0.1, 100, 1000 mg/kg bw/day
Frequency of Treatment : 5 days/week
NOEL : 100 mg/kg body weight
Method : OECD Test Guideline 453
Result : negative

Species : Rat, female
Application Route : Oral
Exposure time : 24 month(s)
Dose : 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment : 7 days/week
NOAEL : 100 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

Method	:	OECD Test Guideline 453
Result	:	negative
Target Organs	:	Digestive organs
Species	:	Rat, females
Application Route	:	Oral
Exposure time	:	24 month(s)
Dose	:	0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment	:	7 days/week
NOEL	:	2 mg/kg bw/day
Method	:	OECD Test Guideline 453
Result	:	negative
Target Organs	:	Digestive organs

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Species	:	Mouse, male
Application Route	:	Dermal
Exposure time	:	482 days
Dose	:	5 mg/kg
Frequency of Treatment	:	3 daily
Result	:	negative

Reproductive toxicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility	:	Test Type: Two-generation study Species: Rat, male and female Application Route: Oral Dose: 0, 50, 180, 540 or 750 milligram per kilogram Duration of Single Treatment: 238 d Frequency of Treatment: 1 daily General Toxicity Parent: NOEL: 540 mg/kg body weight General Toxicity F1: NOEL: 750 mg/kg body weight Symptoms: No adverse effects Method: OECD Test Guideline 416 Result: No effects on fertility and early embryonic development were detected.
Effects on fetal development	:	Species: Rabbit, female Application Route: Dermal Dose: 0, 30, 100 or 300 milligram per kilogram Duration of Single Treatment: 28 d Frequency of Treatment: 1 daily General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight Method: Other guidelines Result: No teratogenic effects Test Type: Pre-natal Species: Rabbit, female Application Route: Oral

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

Dose: 0, 20, 60 or 180 milligram per kilogram
Duration of Single Treatment: 13 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 60 mg/kg body weight
Developmental Toxicity: NOAEL: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 0, 60, 180 and 540 milligram per kilogram
Duration of Single Treatment: 10 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 180 mg/kg body weight
Developmental Toxicity: NOAEL: > 540 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 415
Result: No effects on fertility and early embryonic development were detected.

Effects on fetal development : Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 200 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male and female
NOAEL : 50 mg/kg
Application Route : oral (gavage)
Exposure time : 14 Weeks
Number of exposures : 7 d
Dose : 0, 50, 250, 1000 mg/kg/day
Method : OECD Test Guideline 408

Species : Rat, male and female
NOAEL : >= 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

Number of exposures : 5 d
Dose : 0, 10, 100, 1000 mg/kg/day
Method : OECD Test Guideline 411

Species : Mouse, male
NOAEL : 100 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks
Number of exposures : 3 d
Dose : 0, 1, 10, 100 mg/kg/day
Method : OECD Test Guideline 411

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Species : Rat, male and female
NOEC : > 1000 mg/m³
Application Route : Inhalation
Test atmosphere : dust/mist
Exposure time : 672 h
Number of exposures : 5 d
Method : OECD Test Guideline 412

Species : Rat, male and female
NOAEL : 1000 mg/kg/d
Application Route : Ingestion
Exposure time : 2 160 h
Number of exposures : 7 d
Method : Subchronic toxicity

Aspiration hazard

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Assessment : Based on available data, the classification criteria are not met.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Assessment : Does not have endocrine disrupting properties.

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 : 11 mg/l
plants
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

NOEC : 4,2 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other : NOEC: 0,3 mg/l
aquatic invertebrates
(Chronic toxicity)
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 55 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.1.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

Toxicity to daphnia and other aquatic invertebrates : LC50 : 324 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Toxicity to algae/aquatic plants : EC50 : 119 mg/l
Exposure time: 168 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: >= 100 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge, non-adapted
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Biodegradability : Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 37 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.A.

Stability in water : Degradation half life (DT50): 6,5 hrs (24,5 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 0,15 hrs (24,5 °C)
pH: 5
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 0,13 hrs (24,5 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Partition coefficient: n-octanol/water : log Pow: -2,6 (25 °C)

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among environmental compartments : Koc: 445

12.5 Results of PBT and vPvB assessment

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Assessment : Not persistent, bioaccumulative, and toxic (PBT).
This substance is not considered to be very persistent and very bioaccumulating (vPvB).

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Assessment : Not persistent, bioaccumulative, and toxic (PBT).
This substance is not considered to be very persistent and very bioaccumulating (vPvB).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

12.6 Endocrine disrupting properties

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Assessment : Based on available data, the classification criteria are not met.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Assessment : Does not have endocrine disrupting properties.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Assessment : Not persistent, mobile, and toxic (PMT).
Not very persistent and very mobile (vPvM).

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Assessment : Not persistent, mobile, and toxic (PMT).
Not very persistent and very mobile (vPvM).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not dispose of waste into sewer.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: UN 3082
ADR	: UN 3082
RID	: UN 3082
IMDG	: UN 3082

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

IATA : UN 3082

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(BISPHENOL A EPOXY RESIN)

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(BISPHENOL A EPOXY RESIN)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(BISPHENOL A EPOXY RESIN)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(BISPHENOL A EPOXY RESIN)

IATA : Environmentally hazardous substance, liquid, n.o.s.
(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 9	
ADR	: 9	
RID	: 9	
IMDG	: 9	
IATA	: 9	

14.4 Packing group

ADN
Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

ADR
Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID
Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG
Packing group : III
Labels : 9
EmS Code : F-A, S-F

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

IATA (Cargo)

Packing instruction (cargo aircraft)	:	964
Packing instruction (LQ)	:	Y964
Packing group	:	III
Labels	:	Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft)	:	964
Packing instruction (LQ)	:	Y964
Packing group	:	III
Labels	:	Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous	:	yes
---------------------------	---	-----

ADR

Environmentally hazardous	:	yes
---------------------------	---	-----

RID

Environmentally hazardous	:	yes
---------------------------	---	-----

IMDG

Marine pollutant	:	yes
------------------	---	-----

IATA (Passenger)

Environmentally hazardous	:	yes
---------------------------	---	-----

IATA (Cargo)

Environmentally hazardous	:	yes
---------------------------	---	-----

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).	:	This product does not contain substances of very high concern.
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3 Number on list 40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.

Number on list 75
If you intend to use this product as tattoo ink, please contact your vendor.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Occupational Illnesses (R- : 51
461-3, France)

Installations classified for the : 4511
protection of the environment
(Environment Code R511-9)

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

Further information

Classification of the mixture:

Skin Irrit. 2 H315

Classification procedure:

Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

HUNTSMAN

Enriching lives through innovation

ARALDITE® 420 A

Version	Revision Date:	SDS Number:	Date of last issue: 05.08.2022
1.3	31.03.2026	400001009537	Date of first issue: 20.05.2015

Print Date 24.06.2026

Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.