

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® CW 1302 GB

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Component used for the manufacture of electrical insulation parts

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe) BV
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40
E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : Centres Antipoison et de Toxicovigilance:
ANGERS: 02 41 48 21 21
BORDEAUX: 05 56 96 40 80
LILLE: 0 825 812 822
LYON: 04 72 11 69 11
MARSEILLE 04 91 75 25 25
NANCY: 03 83 32 36 36
PARIS: 01 40 05 48 48
RENNES: 02 99 59 22 22
STRASBOURG: 03 88 37 37 37
TOULOUSE: 05 61 77 74 47
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Eye irritation, Category 2

H319: Causes serious eye irritation.

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard,
Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

:

Warning

Hazard statements

:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P261	Avoid breathing mist or vapours.
P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P391	Collect spillage.

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane
[[[(2-ethylhexyl)oxy]methyl]oxirane
bisphenol A - epoxy resins, number average MW >700 - <1100
3-aminopropyltriethoxysilane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version 3.1 Revision Date: 12.12.2023 SDS Number: 400001010599 Date of last issue: 15.12.2022
Date of first issue: 18.05.2018

Print Date 21.02.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Skin Irrit. 2; H315 ≥ 5 % Eye Irrit. 2; H319 ≥ 5 %	≥ 25 - < 30
[[2-ethylhexyl)oxy)methyl]oxirane	2461-15-6 219-553-6	Skin Irrit. 2; H315 Skin Sens. 1A; H317	≥ 1 - < 10
bisphenol A - epoxy resins, number average MW >700 - <1100	25068-38-6 Polymer	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	≥ 0,1 - < 1
3-aminopropyltriethoxysilane	919-30-2 213-048-4 612-108-00-0 01-2119480479-24	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Acute toxicity estimate Acute oral toxicity: 1 491 mg/kg	≥ 0,1 - < 1
Substances with a workplace exposure limit :			
kaolin	1332-58-7 310-194-1		≥ 1 - < 10

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue:
3.1	12.12.2023	400001010599	15.12.2022
			Date of first issue: 18.05.2018

Print Date 21.02.2024

If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

If inhaled	:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	:	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
-------	---	---

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically.
-----------	---	------------------------

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	Exercise caution when using a high volume water jet as it may scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Metal oxides Carbon oxides

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue:
3.1	12.12.2023	400001010599	15.12.2022
			Date of first issue: 18.05.2018

Print Date 21.02.2024

Phenolics

5.3 Advice for firefighters

- | | | |
|---|---|---|
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- | | | |
|----------------------|---|--|
| Personal precautions | : | Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8. |
|----------------------|---|--|

6.2 Environmental precautions

- | | | |
|---------------------------|---|---|
| Environmental precautions | : | Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
|---------------------------|---|---|

6.3 Methods and material for containment and cleaning up

- | | | |
|-------------------------|---|---|
| Methods for cleaning up | : | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal. |
|-------------------------|---|---|

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | | |
|-------------------------|---|--|
| Advice on safe handling | : | Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the |
|-------------------------|---|--|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version 3.1 Revision Date: 12.12.2023 SDS Number: 400001010599 Date of last issue: 15.12.2022
Date of first issue: 18.05.2018

Print Date 21.02.2024

application area.

Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
kaolin	1332-58-7	VME	10 mg/m3	FR VLE
Further information	Indicative exposure limits			
		TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
Further information	Carcinogens or mutagens			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4,93 mg/m3
	Workers	Dermal	Long-term systemic	0,75 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GBVersion
3.1Revision Date:
12.12.2023SDS Number:
400001010599Date of last issue: 15.12.2022
Date of first issue: 18.05.2018

Print Date 21.02.2024

			effects	bw/day
	Consumers	Inhalation	Long-term systemic effects	0,87 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,5 mg/kg bw/day
3-aminopropyltriethoxysilane	Workers	Inhalation	Long-term systemic effects	59 mg/m3
	Workers	Inhalation	Systemic effects, Short-term exposure	59 mg/m3
	Workers	Dermal	Long-term systemic effects	8,3 mg/kg bw/day
	Workers	Dermal	Systemic effects, Short-term exposure	8,3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	17,4 mg/m3
	Consumers	Inhalation	Systemic effects, Short-term exposure	17,4 mg/m3
	Consumers	Dermal	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Dermal	Systemic effects, Short-term exposure	5 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0,006 mg/l
	Marine water	0,001 mg/l
	Fresh water sediment	0,341 mg/kg dry weight (d.w.)
	Marine sediment	0,034 mg/kg dry weight (d.w.)
	Soil	0,065 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Secondary Poisoning	11 mg/kg
[[2-ethylhexyl)oxy)methyl]oxirane	Fresh water	0,0072 mg/l
	Remarks:Assessment Factors	
	Marine water	0,001 mg/l
	Remarks:Assessment Factors	
	Freshwater - intermittent	0,072 mg/l
	Remarks:Assessment Factors	
	Sewage treatment plant	10 mg/l
	Remarks:Assessment Factors	
	Fresh water sediment	286,66 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Marine sediment	28,66 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version 3.1 Revision Date: 12.12.2023 SDS Number: 400001010599 Date of last issue: 15.12.2022
Date of first issue: 18.05.2018

Print Date 21.02.2024

	Soil	57,16 mg/kg
	Remarks:Equilibrium method	
3-aminopropyltriethoxysilane	Fresh water	0,33 mg/l
	Remarks:Assessment Factors	
	Marine water	0,033 mg/l
	Remarks:Assessment Factors	
	Sewage treatment plant	13 mg/l
	Remarks:Assessment Factors	
	Fresh water sediment	1,2 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Marine sediment	0,12 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Soil	0,05 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 h

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves. The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : No data is available on the product itself.

Odour : slight

Odour Threshold : No data is available on the product itself.

Melting point/freezing point : No data available

Boiling point : > 200 °C

Flammability (solid, gas) : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Flash point : > 100 °C
Method: closed cup

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C

pH : substance/mixture is non-soluble (in water)

Viscosity
Viscosity, dynamic : 20 000 - 27 000 mPa.s (25 °C)
Method: ISO 3219

Solubility(ies)
Water solubility : practically insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Partition coefficient: n-octanol/water : No data is available on the product itself.

Vapour pressure : 0,01 hPa (20 °C)

Density : 1,74 - 1,77 g/cm³ (20 °C)

Relative density : 1,74 - 1,77 (20 °C)

Relative vapour density : No data is available on the product itself.

Particle characteristics : No data is available on the product itself.

9.2 Other information

Miscibility with water : immiscible

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue:
3.1	12.12.2023	400001010599	15.12.2022
			Date of first issue: 18.05.2018

Print Date 21.02.2024

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

[[[(2-ethylhexyl)oxy]methyl]oxirane:

Acute oral toxicity : LD50 (Rat, male and female): > 5 000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 0,15 mg/l
Exposure time: 7 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity : LD50 (Rat, male and female): > 4 000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Information given is based on data obtained from similar substances.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

3-aminopropyltriethoxysilane:

Acute oral toxicity : LD50 (Rat, male and female): 1 491 - 2 688 mg/kg
Method: Acute Oral Toxicity

Acute toxicity estimate: 1 491 mg/kg
Method: Calculation method

Acute inhalation toxicity : LC50 (Rat, male): > 5 ppm
Exposure time: 6 h
Test atmosphere: vapour

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit, male and female): 4 075 mg/kg
Method: Acute Dermal Toxicity
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	: Rabbit
Exposure time	: 4 h
Assessment	: Irritating to skin.
Method	: OECD Test Guideline 404
Result	: Irritating to skin.

[(2-ethylhexyl)oxy]methyl]oxirane:

Species	: Rabbit
Assessment	: Irritating to skin.
Result	: Irritating to skin.
GLP	: yes

bisphenol A - epoxy resins, number average MW >700 - <1100:

Method	: OECD Test Guideline 404
Result	: Skin irritation

3-aminopropyltriethoxysilane:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Causes burns.

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	: Rabbit
Assessment	: Irritating to eyes.
Method	: OECD Test Guideline 405
Result	: Irritating to eyes.

[(2-ethylhexyl)oxy]methyl]oxirane:

Species	: Rabbit
Assessment	: No eye irritation
Method	: OECD Test Guideline 405
Result	: slight irritation
GLP	: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	Eye irritation

3-aminopropyltriethoxysilane:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	Risk of serious damage to eyes.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type	:	Local lymph node assay (LLNA)
Exposure routes	:	Skin
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	The product is a skin sensitiser, sub-category 1B.

[[[(2-ethylhexyl)oxy]methyl]oxirane:

Test Type	:	Maurer optimisation test
Exposure routes	:	Skin
Species	:	Guinea pig
Assessment	:	Probability or evidence of high skin sensitisation rate in humans
Method	:	OECD Test Guideline 406
Result	:	Probability or evidence of high skin sensitisation rate in humans
GLP	:	yes

bisphenol A - epoxy resins, number average MW >700 - <1100:

Exposure routes	:	Skin
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	May cause sensitisation by skin contact.

3-aminopropyltriethoxysilane:

Exposure routes	:	Skin
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	The product is a skin sensitiser, sub-category 1B.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Germ cell mutagenicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Test system: mouse lymphoma cells
Metabolic activation: without metabolic activation
Result: positive

Test Type: reverse mutation assay
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
Result: negative

Genotoxicity in vivo : Test Type: in vivo assay
Species: Mouse (male)
Cell type: Germ
Application Route: Oral
Dose: 3333, 10000 mg/kg
Result: negative

Test Type: gene mutation test
Species: Rat (male)
Cell type: Somatic
Application Route: Oral
Dose: 50,250,500,1000 mg/kg bw/day
Method: OECD Test Guideline 488
Result: negative

[[2-ethylhexyl]oxy]methyl]oxirane:

Genotoxicity in vitro : Test Type: gene mutation test
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Test Type: reverse mutation assay
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse (male and female)
Cell type: Bone marrow

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Application Route: Intraperitoneal injection
Dose: 0/1000/2000/4000 mg/kg bw/day
Method: OECD Test Guideline 474
Result: negative
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Test Type: Chromosome aberration test in vitro
Species: Rat (male and female)
Cell type: Bone marrow
Application Route: Intraperitoneal injection
Dose: 213.8/712.5/2137.5 mg/kg
Method: OECD Test Guideline 475
Result: negative
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: Positive results were obtained in some in vitro tests.

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Method: OPPTS 870.5395
Result: negative

3-aminopropyltriethoxysilane:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	: Rat, male
Application Route	: Oral
Exposure time	: 24 month(s)
Dose	: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment	: 7 days/week
NOAEL	: 15 mg/kg bw/day
Method	: OECD Test Guideline 453
Result	: negative
Target Organs	: Digestive organs

Species	: Mouse, male
Application Route	: Dermal
Exposure time	: 24 month(s)
Dose	: 0, 0.1, 10, 100 mg/kg bw/day
Frequency of Treatment	: 3 days/week
NOEL	: 0,1 mg/kg body weight
Method	: OECD Test Guideline 453
Result	: negative
Target Organs	: Digestive organs

Species	: Rat, female
Application Route	: Dermal
Exposure time	: 24 month(s)
Dose	: 0.1, 100, 1000 mg/kg bw/day
Frequency of Treatment	: 5 days/week
NOEL	: 100 mg/kg body weight
Method	: OECD Test Guideline 453
Result	: negative

Species	: Rat, female
Application Route	: Oral
Exposure time	: 24 month(s)
Dose	: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment	: 7 days/week
NOAEL	: 100 mg/kg bw/day
Method	: OECD Test Guideline 453
Result	: negative
Target Organs	: Digestive organs

Species	: Rat, females
Application Route	: Oral
Exposure time	: 24 month(s)
Dose	: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment	: 7 days/week
NOEL	: 2 mg/kg bw/day
Method	: OECD Test Guideline 453
Result	: negative
Target Organs	: Digestive organs

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species	: Rat, male and female
Application Route	: Oral

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Exposure time : 24 month(s)
Dose : 15 mg/kg
Frequency of Treatment : 7 daily
Method : OECD Test Guideline 453
Result : negative

Reproductive toxicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 0, 50, 180, 540 or 750 milligram per kilogram
Duration of Single Treatment: 238 d
Frequency of Treatment: 1 daily
General Toxicity - Parent: NOEL: 540 mg/kg body weight
General Toxicity F1: NOEL: 750 mg/kg body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
Dose: 0, 30, 100 or 300 milligram per kilogram
Duration of Single Treatment: 28 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Developmental Toxicity: NOAEL: 300 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rabbit, female
Application Route: Oral
Dose: 0, 20, 60 or 180 milligram per kilogram
Duration of Single Treatment: 13 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 60 mg/kg body weight
Developmental Toxicity: NOAEL: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 0, 60, 180 and 540 milligram per kilogram
Duration of Single Treatment: 10 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 180 mg/kg body weight
Developmental Toxicity: NOAEL: > 540 mg/kg body weight
Method: OECD Test Guideline 414

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Result: No teratogenic effects

[[2-ethylhexyl]oxy]methyl]oxirane:

Effects on fertility : Species: Rat, female
Application Route: Dermal
Dose: 0/1/10/50/100/200
Duration of Single Treatment: 10 d
Frequency of Treatment: 7 days/week
General Toxicity - Parent: NOAEL: $\geq$ 200 mg/kg body weight
General Toxicity F1: NOAEL: $\geq$ 200 mg/kg body weight
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Effects on foetal development : Test Type: Pre-natal
Species: Rat, females
Application Route: Dermal
Dose: 0/1/10/50/100/200 milligram per kilogram
Duration of Single Treatment: 10 d
Frequency of Treatment: 7 days/week
General Toxicity Maternal: NOAEL: $\geq$ 200 mg/kg body weight
Developmental Toxicity: NOAEL: $\geq$ 200 mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
General Toxicity - Parent: NOEL: 750 mg/kg body weight
General Toxicity F1: NOEL: 750 mg/kg body weight
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	: Rat, male and female
NOAEL	: 50 mg/kg
Application Route	: oral (gavage)
Exposure time	: 14 Weeks
Number of exposures	: 7 d
Dose	: 0, 50, 250, 1000 mg/kg/day
Method	: OECD Test Guideline 408

Species	: Rat, male and female
NOAEL	: ≥ 10 mg/kg
Application Route	: Skin contact
Exposure time	: 13 Weeks
Number of exposures	: 5 d
Dose	: 0, 10, 100, 1000 mg/kg/day
Method	: OECD Test Guideline 411

Species	: Mouse, male
NOAEL	: 100 mg/kg
Application Route	: Skin contact
Exposure time	: 13 Weeks
Number of exposures	: 3 d
Dose	: 0, 1, 10, 100 mg/kg/day
Method	: OECD Test Guideline 411

[(2-ethylhexyl)oxy]methyl]oxirane:

Species	: Rat, male and female
NOEL	: 100 mg/kg/d
Application Route	: Skin contact
Exposure time	: 13 Weeks
Number of exposures	: 5 days/week
Dose	: 0/10/10/100 mg/kg bw/day
Method	: Subchronic toxicity
Remarks	: Information given is based on data obtained from similar substances.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species	: Rat, male and female
NOAEL	: 50 mg/kg
Application Route	: Ingestion
Exposure time	: 14 Weeks
Number of exposures	: 7 d
Method	: Subchronic toxicity

Species	: Rat, male and female
---------	------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

NOEL : 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks
Number of exposures : 5 d
Method : Subchronic toxicity

3-aminopropyltriethoxysilane:

Species : Rat, male and female
NOAEL : 200 mg/kg
Application Route : Ingestion
Exposure time : 2 160 h
Method : Subchronic toxicity

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Toxicity to algae/aquatic plants : EC50 : 11 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

NOEC : 4,2 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

[[[(2-ethylhexyl)oxy]methyl]oxirane:

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 7,2 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 202
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Toxicity to algae/aquatic plants : IC50 (Selenastrum capricornutum (green algae)): 843,75 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

NOEC (Selenastrum capricornutum (green algae)): 500 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue:
3.1	12.12.2023	400001010599	15.12.2022
			Date of first issue: 18.05.2018

Print Date 21.02.2024

Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Toxicity to microorganisms : NOEC (Bacteria): 100 mg/l
Exposure time: 28 d
Test Type: static test
GLP: yes

Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility, This product has no known ecotoxicological effects.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EgC50 (Selenastrum capricornutum (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

3-aminopropyltriethoxysilane:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 934 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 331 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1 000 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.3.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue:
3.1	12.12.2023	400001010599	15.12.2022
			Date of first issue: 18.05.2018

Print Date 21.02.2024

Toxicity to microorganisms : EC50 (*Pseudomonas putida*): 43 mg/l
Exposure time: 5,75 h
Test Type: static test
Test substance: Fresh water

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge, non-adapted
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

[[2-ethylhexyl]oxy]methyl]oxirane:

Biodegradability : Inoculum: activated sludge
Concentration: 100 mg/l
Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 0,3 hrs (20 °C)
pH: 4
Method: No information available.
GLP: No information available.
Remarks: Fresh water

Degradation half life (DT50): 20 d (20 °C)
pH: 7
Method: No information available.
GLP: No information available.
Remarks: Fresh water

pH: 9
Method: No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue:
3.1	12.12.2023	400001010599	15.12.2022
			Date of first issue: 18.05.2018

Print Date 21.02.2024

GLP: No information available.
Remarks: see user defined free text

bisphenol A - epoxy resins, number average MW >700 - <1100:

Biodegradability : Test Type: aerobic
Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not biodegradable
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

3-aminopropyltriethoxysilane:

Biodegradability : Inoculum: activated sludge
Concentration: 8,95 mg/l
Result: Not readily biodegradable.
Biodegradation: 67 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.A.

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117

[(2-ethylhexyl)oxy]methyl]oxirane:

Partition coefficient: n-octanol/water : Pow: 6 730 (40 °C)
log Pow: 3,83 (40 °C)
pH: 6,34
Method: OECD Test Guideline 117
GLP: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

bisphenol A - epoxy resins, number average MW >700 - <1100:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

3-aminopropyltriethoxysilane:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 3,4
Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 1,7 (20 °C)
octanol/water pH: 7

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among : Koc: 445
environmental compartments

[[[(2-ethylhexyl)oxy]methyl]oxirane:

Distribution among : Koc: > 426580, log Koc: > 5,63
environmental compartments Method: OECD Test Guideline 121
Remarks: Information taken from reference works and the literature.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Distribution among : Koc: 445
environmental compartments

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue:
3.1	12.12.2023	400001010599	15.12.2022
			Date of first issue: 18.05.2018

Print Date 21.02.2024

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local, regional, national and international regulations.
Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 3082
ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA : UN 3082

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)

IATA : Environmentally hazardous substance, liquid, n.o.s.
(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 9	
ADR	: 9	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

RID : 9

IMDG : 9

IATA : 9

14.4 Packing group

ADN

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Occupational Illnesses (R-461-3, France) : 51, 84, 25

Installations classified for the protection of the environment (Environment Code R511-9) : 4511

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue:
3.1	12.12.2023	400001010599	15.12.2022
			Date of first issue: 18.05.2018

Print Date 21.02.2024

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AIIC	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Corr.	: Skin corrosion

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® CW 1302 GB

Version	Revision Date:	SDS Number:	Date of last issue: 15.12.2022
3.1	12.12.2023	400001010599	Date of first issue: 18.05.2018

Print Date 21.02.2024

Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
FR VLE	:	France. Occupational Exposure Limits
2004/37/EC / TWA	:	Long term exposure limit
FR VLE / VME	:	Time Weighted Average

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.