

Data Sheet

IPPLON® DP1000

Soft nylon film with an excellent elongation

DESCRIPTION

Ipplon® DP1000 is a vacuum bagging film with a high elongation and is suitable for cure temperatures up to 212°C. It is recommended for bagging applications where a higher softness is required.

BENEFITS

- Softness and high elongation makes bagging easier and faster to complete, reducing labor cost.
- Wider film means less seams for safer high temperature cures of large parts in shorter cycle times.
- High elongation reduces bridging and rework due to resin rich corners.

TECHNICAL DATA

		Test method
Material type	Nylon	
Elongation at break	450 %	ASTM D 882
Tensile strength	48 MPa	ASTM D 882
Maximum use temperature	212°C	
Flammability (self extinguishing)	Yes	ATP-5034
Materials to avoid	Phenolic resins/Strong oxidizers	
Colour	Salmon pink	
Shelf life	Unlimited when stored in original packaging at 22°C	


SIZES

Thickness	Width	Forms Available*
50 µm (0,002 inch)	up to 7,11 m (280 inches)	SHT, CF, LFT
75 µm (0,003 inch)	up to 7,11 m (280 inches)	SHT, CF, LFT


- For more sizes, see the *Commonly Used Sizes* chart in this section.
- Custom shapes and sizes are available, please contact Airtech for more information.



*SHT=Sheeting




CF=Centerfold



LFT=Lay-Flat
Tubing



GT=Gusseted
Tubing



G=Gusseted

← Slit
Open Edge

NOTES

- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.
- Watch a video of Wide Films in the "Media Centre" on our website.