AIRTECH EUROPE SARL
18, ZI Haneboesch
L-4562 Differdange
LUXEMBOURG
Phone : +352 58 22 82 1
Fax : +352 58 49 35
E-mail : sales@airtech.lu
Website : www.airtech.lu

Data Sheet

AHTC-1000 QTD

High temperature, all metallic, quick turn disconnect

DESCRIPTION

The AHTC-1000 QTD Quick Turn Disconnect is designed for use up to 538°C. The ferrule expands to create a seal at elevated temperatures. There are no organic materials to break down under high temperature applications. The end fittings are female NPT style and work well with our Vac Valve 409 SS HTR, Airflow 800, and BBH 1080 autoclave hoses.

BENEFITS


- Standard thread design compatible with Vac Valves and Hoses.
- Highest temperature and pressure resistance for high end applications.
- Highly durable construction for long in-service life.

TECHNICAL DATA

Material type	All metallic
Connection to hose	Threaded
Screw thread	1/2 or 1/4 inch female NPT
Service temperature	538°C
Max autoclave pressure	69 bar

SIZES

Socket Type	Product Reference
Female threaded	AHTC-1000 QTD



NOTES

- Available upon request only. Minimum order may apply.

Last updated : 2016-02-15

Catalogue position : Vacuum valves and hoses

As the conditions or methods of use, including storage, are beyond our control, Airtech Europe does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech Europe disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes. This translation is provided for your convenience only. The official language is English and the official law is Luxembourg.