HARDENER 2023 B

Version	Revision Date:	SDS Number:	Date of last issue: 01.12.2021
1.1	16.03.2023	400000012364	Date of first issue: 01.12.2021

Print Date 13.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : HARDENER 2023 B

Unique Formula Identifier (UFI) : YS01-D0WY-W00E-KTG6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Hardener

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe) BV
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : Centres Antipoison et de Toxicovigilance:
ANGERS: 02 41 48 21 21
BORDEAUX: 05 56 96 40 80
LILLE: 0 825 812 822
LYON: 04 72 11 69 11
MARSEILLE 04 91 75 25 25
NANCY: 03 83 32 36 36
PARIS: 01 40 05 48 48
RENNES: 02 99 59 22 22
STRASBOURG: 03 88 37 37 37
TOULOUSE: 05 61 77 74 47
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Organic peroxides, Type E	H242: Heating may cause a fire.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements :
H242 Heating may cause a fire.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234 Keep only in original packaging.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Hazardous components which must be listed on the label:

dibenzoyl peroxide
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
dibenzoyl peroxide	94-36-0 202-327-6 617-008-00-0 01-2119511472-50	Org. Perox. B; H241 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	>= 20 - < 25
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Skin Irrit. 2; H315 >= 5 % Eye Irrit. 2; H319 >= 5 %	>= 2,5 - < 5
Substances with a workplace exposure limit :			
silicon dioxide	7631-86-9 231-545-4 01-2119379499-16		>= 1 - < 10

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO2)
Dry chemical

Unsuitable extinguishing : Exercise caution when using a high volume water jet as it may

media		scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon oxides Halogenated compounds

5.3 Advice for firefighters

Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Avoid dust formation. Avoid breathing dust. Remove all sources of ignition. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Advice on protection against fire and explosion	:	Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from open flames, hot surfaces and sources of ignition.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Store in cool place. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Keep in properly labelled containers.
Advice on common storage	:	For incompatible materials please refer to Section 10 of this SDS.
Further information on storage stability	:	Stable under normal conditions.
Recommended storage temperature	:	2 - 8 °C
		Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s)	:	No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dibenzoyl peroxide	94-36-0	VME	5 mg/m3	FR VLE
Further information	Indicative exposure limits			
silicon dioxide	7631-86-9	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
Further information	Carcinogens or mutagens			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4,93 mg/m3
	Workers	Dermal	Long-term systemic effects	0,75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,87 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,5 mg/kg bw/day
silicon dioxide	Workers	Inhalation	Long-term systemic effects	4 mg/m3
Benzoic acid, C9-11-branched alkyl esters	Workers	Inhalation	Long-term systemic effects	181 mg/m3
	Workers	Dermal	Long-term systemic effects	206 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	53 mg/m3
	Consumers	Dermal	Long-term systemic effects	29 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	15,48 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0,006 mg/l
	Marine water	0,001 mg/l
	Fresh water sediment	0,341 mg/kg dry weight (d.w.)
	Marine sediment	0,034 mg/kg dry weight (d.w.)
	Soil	0,065 mg/kg dry weight (d.w.)

	Sewage treatment plant	10 mg/l
	Secondary Poisoning	11 mg/kg
Benzoic acid, C9-11-branched alkyl esters	Fresh water sediment	0,065 mg/kg dry weight (d.w.)
	Remarks:Assessment Factors	
	Oral	6667 mg/kg
	Remarks:Assessment Factors	

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : black

Odour : slight

Odour Threshold : No data is available on the product itself.

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flash point : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Upper explosion limit / Upper flammability limit	:	No data is available on the product itself.
Lower explosion limit / Lower flammability limit	:	No data is available on the product itself.
Vapour pressure	:	No data is available on the product itself.
Relative vapour density	:	No data is available on the product itself.
Relative density	:	No data is available on the product itself.
Density	:	1,1 g/cm3 (25 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data is available on the product itself.
Partition coefficient: n-octanol/water	:	No data is available on the product itself.
Auto-ignition temperature	:	No data is available on the product itself.
Decomposition temperature	:	Decomposition energy (mass): 281 KJ/kg
Viscosity		
Viscosity, dynamic	:	60 000 - 80 000 mPa.s (25 °C)

9.2 Other information

Explosive properties	:	No data is available on the product itself.
Self-Accelerating decomposition temperature (SADT)	:	50 °C
Oxidizing properties	:	No data is available on the product itself.
Burning rate	:	No data is available on the product itself.
Evaporation rate	:	No data is available on the product itself.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

Hazardous decomposition products : carbon dioxide
carbon monoxide
Halogenated compounds

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Components:

dibenzoyl peroxide:

Acute oral toxicity : LD50 (Mouse, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat, male): > 24,3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 5 000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity	:	LC50 (Rat, male and female): > 58,8 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
Acute dermal toxicity	:	LD50 (Rabbit): > 5 000 mg/kg

Skin corrosion/irritation

Components:

dibenzoyl peroxide:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	:	Rabbit
Exposure time	:	4 h
Assessment	:	Irritating to skin.
Method	:	OECD Test Guideline 404
Result	:	Irritating to skin.

silicon dioxide:

Species	:	Rabbit
Assessment	:	No skin irritation
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

Serious eye damage/eye irritation

Components:

dibenzoyl peroxide:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	Irritating to eyes.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	:	Rabbit
Assessment	:	Irritating to eyes.
Method	:	OECD Test Guideline 405
Result	:	Irritating to eyes.

silicon dioxide:

Species	:	Rabbit
Assessment	:	No eye irritation
Method	:	OECD Test Guideline 405
Result	:	No eye irritation

Respiratory or skin sensitisation

Components:

dibenzoyl peroxide:

Exposure routes	:	Skin
Species	:	Mouse
Assessment	:	May cause sensitisation by skin contact.
Method	:	OECD Test Guideline 429
Result	:	Causes sensitisation.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type	:	Local lymph node assay (LLNA)
Exposure routes	:	Skin
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Components:

dibenzoyl peroxide:

Genotoxicity in vitro	:	Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	:	Cell type: Somatic Application Route: Intraperitoneal injection Dose: 0, 50, 100, 200 mg/kg b.w. Method: OECD Test Guideline 474 Result: negative

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Test system: mouse lymphoma cells Metabolic activation: without metabolic activation Result: positive Test Type: reverse mutation assay Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay) Result: negative
Genotoxicity in vivo	:	Test Type: in vivo assay Species: Mouse (male) Cell type: Germ Application Route: Oral Dose: 3333, 10000 mg/kg

Result: negative

Test Type: gene mutation test
Species: Rat (male)
Cell type: Somatic
Application Route: Oral
Dose: 50,250,500,1000 mg/kg bw/day
Method: OECD Test Guideline 488
Result: negative

silicon dioxide:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Application Route: Inhalation
Dose: 50 mg/m3
Result: negative

Carcinogenicity

Components:

dibenzoyl peroxide:

Species	:	Mouse, male and female
Application Route	:	Dermal
Exposure time	:	104 weeks
Result	:	negative

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	:	Rat, male
Application Route	:	Oral
Exposure time	:	24 month(s)
Dose	:	0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment	:	7 days/week
NOAEL	:	15 mg/kg bw/day
Method	:	OECD Test Guideline 453
Result	:	negative
Target Organs	:	Digestive organs

Species	:	Mouse, male
Application Route	:	Dermal
Exposure time	:	24 month(s)
Dose	:	0, 0.1, 10, 100 mg/kg bw/day
Frequency of Treatment	:	3 days/week
NOEL	:	0,1 mg/kg body weight

Method	:	OECD Test Guideline 453
Result	:	negative
Target Organs	:	Digestive organs

Species	:	Rat, female
Application Route	:	Dermal
Exposure time	:	24 month(s)
Dose	:	0.1, 100, 1000 mg/kg bw/day
Frequency of Treatment	:	5 days/week
NOEL	:	100 mg/kg body weight
Method	:	OECD Test Guideline 453
Result	:	negative

Species	:	Rat, female
Application Route	:	Oral
Exposure time	:	24 month(s)
Dose	:	0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment	:	7 days/week
NOAEL	:	100 mg/kg bw/day
Method	:	OECD Test Guideline 453
Result	:	negative
Target Organs	:	Digestive organs

Species	:	Rat, females
Application Route	:	Oral
Exposure time	:	24 month(s)
Dose	:	0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment	:	7 days/week
NOEL	:	2 mg/kg bw/day
Method	:	OECD Test Guideline 453
Result	:	negative
Target Organs	:	Digestive organs

silicon dioxide:

Species	:	Rat, male and female
Application Route	:	Oral
Exposure time	:	103 weeks
Dose	:	1800 - 3200 mg/kg
Frequency of Treatment	:	7 daily
Method	:	OECD Test Guideline 453
Result	:	negative

Reproductive toxicity

Components:

dibenzoyl peroxide:

Effects on fertility	:	Species: Rat, male and female Application Route: Oral Dose: 0, 250, 500, 1,000 mg/kg b.w/ General Toxicity - Parent: NOAEL: 500 mg/kg body weight General Toxicity F1: NOAEL: 500 mg/kg body weight Method: OECD Test Guideline 422
Effects on foetal	:	Species: Rat

development

Dose: 100, 300 or 1000 mg/kg/day
General Toxicity Maternal: NOAEL: 300 mg/kg body weight
Developmental Toxicity: NOAEL: 300 mg/kg body weight
Method: OECD Test Guideline 414

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 0, 50, 180, 540 or 750 milligram per kilogram
Duration of Single Treatment: 238 d
Frequency of Treatment: 1 daily
General Toxicity - Parent: NOEL: 540 mg/kg body weight
General Toxicity F1: NOEL: 750 mg/kg body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
Dose: 0, 30, 100 or 300 milligram per kilogram
Duration of Single Treatment: 28 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Developmental Toxicity: NOAEL: 300 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rabbit, female
Application Route: Oral
Dose: 0, 20, 60 or 180 milligram per kilogram
Duration of Single Treatment: 13 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 60 mg/kg body weight
Developmental Toxicity: NOAEL: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 0, 60, 180 and 540 milligram per kilogram
Duration of Single Treatment: 10 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 180 mg/kg body weight
Developmental Toxicity: NOAEL: > 540 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

silicon dioxide:

Effects on foetal development : Species: Mouse
Application Route: Oral

General Toxicity Maternal: NOAEL: 1 340 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rabbit
Application Route: Oral
General Toxicity Maternal: NOAEL: 1 600 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat
Application Route: Oral
General Toxicity Maternal: NOAEL: 1 350 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

dibenzoyl peroxide:

Species	:	Rat, male and female
NOAEL	:	> 100 mg/kg
Application Route	:	Skin contact
Number of exposures	:	2 years
Method	:	OECD Test Guideline 451

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species	:	Rat, male and female
NOAEL	:	50 mg/kg
Application Route	:	oral (gavage)
Exposure time	:	14 Weeks
Number of exposures	:	7 d
Dose	:	0, 50, 250, 1000 mg/kg/day
Method	:	OECD Test Guideline 408

Species	:	Rat, male and female
NOAEL	:	>= 10 mg/kg
Application Route	:	Skin contact
Exposure time	:	13 Weeks
Number of exposures	:	5 d
Dose	:	0, 10, 100, 1000 mg/kg/day
Method	:	OECD Test Guideline 411

Species	:	Mouse, male
NOAEL	:	100 mg/kg
Application Route	:	Skin contact
Exposure time	:	13 Weeks
Number of exposures	:	3 d

Dose : 0, 1, 10, 100 mg/kg/day
Method : OECD Test Guideline 411

silicon dioxide:

Species : Rat, male and female
NOEC : 4000 - 4500 mg/m3
Application Route : Ingestion
Test atmosphere : dust/mist
Exposure time : 13 Weeks
Number of exposures : 7 d
Method : OECD Test Guideline 413

Aspiration toxicity

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

dibenzoyl peroxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,0602 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,11 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants	:	EbC50 (Selenastrum capricornutum (green algae)): 0,0422 mg/l Exposure time: 72 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	:	10
Toxicity to microorganisms	:	EC50 (activated sludge): 35 mg/l Exposure time: 0,5 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 209
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	EC10: 0,001 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Method: OECD Test Guideline 211
M-Factor (Chronic aquatic toxicity)	:	10

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EC50 : 11 mg/l Exposure time: 72 h Test Type: static test Test substance: Fresh water Method: EPA-660/3-75-009 NOEC : 4,2 mg/l Exposure time: 72 h Test Type: static test Test substance: Fresh water Method: EPA-660/3-75-009
Toxicity to microorganisms	:	IC50 (activated sludge): > 100 mg/l Exposure time: 3 h Test Type: static test Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 0,3 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Test substance: Fresh water Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.

silicon dioxide:

Toxicity to fish	:	LL50 (Brachydanio rerio (zebrafish)): > 10 000 mg/l Exposure time: 96 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 202
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): >= 1 000 mg/l Exposure time: 24 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EL50 (Desmodesmus subspicatus (green algae)): > 10 000 mg/l Exposure time: 72 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 201

12.2 Persistence and degradability

Components:

dibenzoyl peroxide:

Biodegradability	:	Inoculum: activated sludge Concentration: 4 mg/l Result: Readily biodegradable. Biodegradation: 68 % Exposure time: 28 d Method: OECD Test Guideline 301D

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability	:	Test Type: aerobic Inoculum: activated sludge, non-adapted Concentration: 20 mg/l Result: Not readily biodegradable. Biodegradation: 5 % Exposure time: 28 d Method: OECD Test Guideline 301F
Stability in water	:	Degradation half life (DT50): 4,83 d (25 °C)

pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

12.3 Bioaccumulative potential

Components:

dibenzoyl peroxide:

Partition coefficient: n-octanol/water : log Pow: 3,2 (22 °C)
pH: 7,02
Method: OECD Test Guideline 117

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117

12.4 Mobility in soil

Components:

dibenzoyl peroxide:

Distribution among environmental compartments : Koc: 6309,57
Method: OECD Test Guideline 121

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among environmental compartments : Koc: 445

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local, regional, national and international regulations.
Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 3108

ADR : UN 3108

RID : UN 3108

IMDG : UN 3108

IATA : UN 3108

14.2 UN proper shipping name

ADN : ORGANIC PEROXIDE TYPE E, SOLID

ADR : ORGANIC PEROXIDE TYPE E, SOLID

RID : ORGANIC PEROXIDE TYPE E, SOLID

IMDG : ORGANIC PEROXIDE TYPE E, SOLID

IATA : Organic peroxide type E, solid

14.3 Transport hazard class(es)

		Class	Subsidiary risks
ADN	:	5.2	

ADR	:	5.2	
RID	:	5.2	
IMDG	:	5.2	
IATA	:	5.2	HEAT

14.4 Packing group

ADN

Packing group	:	Not assigned by regulation
Classification Code	:	P1
Labels	:	5.2

ADR

Packing group	:	Not assigned by regulation
Classification Code	:	P1
Labels	:	5.2
Tunnel restriction code	:	(D)

RID

Packing group	:	Not assigned by regulation
Classification Code	:	P1
Hazard Identification Number	:	539
Labels	:	5.2

IMDG

Packing group	:	Not assigned by regulation
Labels	:	5.2
EmS Code	:	F-J, S-R

IATA (Cargo)

Packing instruction (cargo aircraft)	:	570
Packing group	:	Not assigned by regulation
Labels	:	Organic Peroxides, Keep Away From Heat

IATA (Passenger)

Packing instruction (passenger aircraft)	:	570
Packing group	:	Not assigned by regulation
Labels	:	Organic Peroxides, Keep Away From Heat

14.5 Environmental hazards

ADN

Environmentally hazardous	:	yes

ADR

Environmentally hazardous	:	yes

RID

Environmentally hazardous	:	yes

IMDG

Marine pollutant	:	yes(DIBENZOYL PEROXIDE)

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75
If you intend to use this product as tattoo ink, please contact your vendor.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	P6b	SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
	E1	ENVIRONMENTAL HAZARDS

Occupational Illnesses (R-461-3, France) : 51

Installations classified for the protection of the environment (Environment Code R511-9) : 4422, 4510

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not on the Canadian DSL nor NDSL.

AIIC : All components are listed on the inventory, regulatory obligations/restrictions apply. Please contact your sales representative for more information before import into Australia

ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	Not in compliance with the inventory
PICCS	:	Not in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	On or in compliance with the active portion of the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H241	:	Heating may cause a fire or explosion.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Org. Perox.	:	Organic peroxides
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work

FR VLE	:	France. Occupational Exposure Limits
2004/37/EC / TWA	:	Long term exposure limit
FR VLE / VME	:	Time Weighted Average

Further information

Classification of the mixture:		**Classification procedure:**
Org. Perox. E	H242	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.