AIRTECH EUROPE Sarl

ZI Haneboesch
L-4562 Differdange
LUXEMBOURG

Phone : +352 58 22 82 1
Fax : +352 58 49 35

E-mail : sales@airtech.lu
Website : www.airtech.lu

Data Sheet

RESIN INFUSION AUXILIARY MATERIALS


Tubing, spiral tubing and fittings

Room temperature - 230°C	
Sil-tube (Silicone tubing)	14 mm O.D. x 8 mm I.D. / 25 m/ roll
	18 mm O.D. x 10 mm I.D. / 25 m/ roll
	21 mm O.D. x 12 mm I.D. / 25 m/ roll

Sil-tube Hose Clamp 'A'	Sil-tub Hose Clamp 'B'
Open gap height: 20 mm max	Open gap height: 20 mm max
Open gap width: 25 mm max	Open gap width: 20 mm max

Room temperature - 121°C	
Polyethylene tubing:	1/2" O.D. x 3/8" I.D. x 25 m (use with 3/8" fittings)
	5/8" O.D. x 1/2" I.D. x 25 m (use with 1/2" fittings)
	3/4" O.D. x 5/8" I.D. x 25 m (use with 5/8" fittings)
Polyethylene spiral tubing:	3/8" O.D. x 1/4" I.D. x 25 m
	1/2" O.D. x 3/8" I.D. x 25 m (use with 3/8" fittings)
	5/8" O.D. x 1/2" I.D. x 25 m (use with 1/2" fittings)
	3/4" O.D. x 5/8" I.D. x 25 m (use with 5/8" fittings)

Room temperature - 177°C	
Nylon tubing:	1/2" O.D. x 3/8" I.D. x 25 m
Nylon spiral tubing:	1/2" O.D. x 3/8" I.D. x 25 m
NTF - Nylon barb "T" fittings:	NTF 38 - 3/8" x 3/8" x 3/8" / NTF 12 - 1/2" x 1/2" x 1/2" / NTF 58 - 5/8" x 5/8" x 5/8"
NEF - Nylon barb elbow fittings:	NEF 38 - 3/8" x 3/8" / NEF 12 - 1/2" x 1/2" / NEF 58 - 5/8" x 5/8"
NCF - Nylon barb coupling fittings:	NCF 38 - 3/8" x 3/8" / NCF 12 - 1/2" x 1/2" / NCF 58 - 5/8" x 5/8"
Infusion valve:	This valve is designed with two fittings which can be connected with our tubes of 12,7 mm (1/2") outside diameter.



Last updated : 2015-08-11

Catalogue position : Resin infusion products

As the conditions or methods of use, including storage, are beyond our control, Airtech Europe does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech Europe disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes. This translation is provided for your convenience only. The official language is English and the official law is Luxembourg.